CHECK FLIGHT CERTIFICATE

MD Helicopters/Hughes 369 Series **CFS 163 issue 2**

Date:	Crew:	Observer:	Registration:

Performance Climb #1

Average Weight			
Average Altitude			ft
Average Temp.			°C
Speed			KIAS
Achieved Rate			fpm
Scheduled Rate			fpm
Margin			fpm
Permitted Margin	-70		fpm

Airfield:

Start Weight Kg/Lbs*:

Takeoff cg:

Performance:

SATIS/UNSATIS/NOT APPLICABLE*

*(delete as applicable)**

Defects

No.	Defect	-/R/FT	Action?

(use a continuation sheet as necessary)

Conclusions/Comments

I CERTIFY that I have tested the above aircraft and have detailed the deficiencies and unsatisfactory features above. Those items annotated R or FT must be dealt with as shown in the notes on the reverse side.

Name:	Signed:	Date:	Licence No.:
For CAA Use only	Report Logged by:	Date:	Report No.:

NOTES

General

Only CAA personnel or pilots specifically briefed to carry out CAA airtests may conduct the test.

General notes on test conduct can be found in the CAA Handbook for Airworthiness Flight Testing.

This sheet replaces any flight test certificate given in the schedule.

Registration: If the aircraft is not on the UK register, add the manufacturers serial number and expected UK registration (if known).

Crew: Captain, co-pilot, Flight engineer (where applicable).

Airfield: Departure airfield.

Start Weight: Actual all up weight at first engine start. Also delete Kg or Lbs as appropriate.

Takeoff cg: Actual cg at lift-off, preferably as a % of the Mean Aerodynamic Chord.

Performance

A full description of climb analysis is given in the CAA Handbook for Airworthiness Flight Testing.

Climb#1/Climb#2: Enter in these columns data from the first and second climbs.

Average Weight: The aircraft all up weight at the midpoint of the measured climb.

Average Altitude: The altitude at which the line drawn to average the measured points passes through at the mid time.

Average Temp: The temperature at which the line drawn to average the measured points passes through at the mid time.

Speed: The target climb speed (Indicated Airspeed.)

Achieved Rate: The climb rate as given by the slope of the line drawn to average the measured altitude points in feet per minute.

Scheduled Rate: The expected gross rate of climb read from the appropriate graph in the Flight Manual with any adjustments for configuration differences. For large aircraft, the basic gross data are normally to be found in a separate supplement labelled 'Additional Flight Test Data'.

Margin: The difference between the Scheduled and Achieved rates of climb (negative if achieved is lower than scheduled).

Defects

Enter all defects from the flight. All defects must also be entered in the Technical Log. Procedural items entered in the Technical Log (such as re-stowing oxygen masks) need not be entered here. Items affecting flight safety which were known before the flight, whether or not they were deferred should be entered. In the latter case, the defect should be annotated accordingly after the details.

No.: The first column is to allow the items to be numbered.

Defect: Enter details of the defect.

-/R/FT: Classify each defect according to its impact on safety, regardless of whether it can be deferred according to the MEL. Any deferrals should be dealt with in the normal way in the Technical Log. Items requiring rectification (or deferral under the MEL) before further flight for hire or reward or before the issue of the CofA should be marked 'R'. Additionally, items that require re-checking in-flight following rectification (such as inadequate climb performance) should be marked 'FT'. Items requiring both should be marked 'R/FT'.

Action?: This column should be left blank unless further information is required from the engineers or the item is considered to be of sufficient import that CAA action is considered necessary, then the person/department/agency from whom further action is required should be noted in this column. Annotate accordingly if an MOR or similar report is to be raised.

Conclusions/Comments

Any conclusions, notes or comments useful for tracking defects may be entered.

Name: Only the pilot who carried out the test may sign this sheet

CAA Check Flight Schedules

All CAA Check Flight Schedules (CFSs) are prepared based on a design standard which, before September 2003, was the UK Type Certificate. Following the creation of EASA there may be different design standards in service within the European Union (EU) - this may include modifications approved in any EU country.

It is the responsibility of the flight crew to ensure that the exercises and limitations in the CFS are correct for the aircraft under test.

The prime source of information will be the aircraft flight manual and in the event of conflict the flight manual should be taken as overriding.

CAA policy is that pilots who conduct airtests on the behalf of the Authority must be acceptable to the Authority, must have been briefed on techniques and safety considerations before carrying out the tests in these schedules and must have carried out an airtest within the last 4 years.

The CAA does not accept responsibility for the use of a CAA CFS on a test flight not directly under their control.

CHECK FLIGHT SCHEDULE

MD Helicopters/Hughes 369C/D/E **CFS 163 Issue 2**

Registration		Test Date	

1. INTRODUCTION

This scheduled is applicable to the M^{D} Helicopters 369 Series helicopters. It is based on the assumption that the every day operation of the helicopter serves as a continuous check on the correct functioning of all normal services.

The Flight Test must be carried out by an experienced pilot acceptable to the CAA, in accordance with this schedule and the general guidance given in the CAA Handbook for Airworthiness Flight Testing. The crew are expected generally to monitor the behaviour of all equipment and report any unserviceable items.

In addition to completing all the tests in this schedule any characteristics which are considered to be unsafe or undesirable must be recorded.

WARNING

1. It is illegal to carry passengers on a test flight without a current Certificate of Airworthiness except passengers performing duties in the aircraft in connection with the flight. Although it may be legal to carry passengers on a test flight with a C of A in force, it is strongly recommended, for Check Flights and other tests entailing greater risk than normal flight, that:

   a) It is preferable to use ballast, and

   b) Before accepting any passengers on a test flight the pilot in command should inform them that the risk is greater than on an ordinary flight.

2. Under no circumstances are the limitations contained in the CAA approved Flight Manual to be exceeded.

3. If a clipboard or kneeboard is used to record the results there is a possibility of fouling the controls especially the duals, if fitted. To reduce this possibility, the pilot must have briefed the observer on the need to ensure that the clipboard is well clear of the controls especially during manoeuvres requiring large control deflections such as low speed envelope and autorotation. The pilot should monitor the position of the clipboard during the flight to ensure that it is not in a potentially hazardous position. Whenever possible, flexible, rather than rigid, clipboards should be used. Consideration should be given to removing the dual controls if flying with an inexperienced observer.

Should there be any query about the Flight Test or its results, the local CAA Surveyor or the Helicopter Flight Test Section at Aviation House, Gatwick must be consulted.

It is recommended that the tests are performed in the sequence given. The results are to be written in ink in the spaces provided.

INDEX

Paragraph	Page
1. Pre-flight Info.	6
2. Loading	6
3. General Flight Info.	6
4. Pre-start Checks	7
5. Starting/Pre-flight Checks	8
6. Hover Checks	10
7. Performance Climb	11
8. Autorotation	12
9. Handling/ Engine power Check	13
10. Landing	14
11. Shut Down	15
12. Post-flight Action	15
13. Flight Test Certificate	Frontpage
Appendix 1	16
Appendix 2	17

1. Pre-Flight Information

Aircraft Variant	MDH/Hughes 369C/HE/HS/D/E/F	Engine Variant	RR Allison 250-C18/C18A/ C20/C20B/C20R

Registration		Engine Nr	
Airframe Nr		Hours total	
Airframe Hrs		TSO	
Landing Gear			Eg High/low skid
Intake Configuration	Gauze Inlet/ Particle Separator/ Mist Eliminator		
Operator/Maint. Organisation			
Airfield			

Pilot(s)	
Observer	

2. Loading

Note: The helicopter shall be loaded to maximum all up weight if possible. Any ballast must be securely installed. Additionally, it will be necessary to land and reduce weight to <2500lb enable the autorotative rotor rpm to be checked.

Take-off Weight		lb
Fuel		lb
CoG Position		in

3. General Flight Information

Airfield Press. Alt.		ft	QFE/QNH	/	
Wind	/		OAT		°C
Weather					

Engine Start		Land	
Take-Off		Shut down	

4. Pre-Start Checks

		Satis.	Remarks
4.1	Carry out the normal external inspection		
4.2	Confirm correct functioning of external lighting		
4.3	Doors & windows : Condition & operation		
	Seats & harnesses		
	Placards : Legibility & accuracy		
4.4	Instrument marking : Legibility, general condition & accuracy of colour bands & marking (where fitted).		
	ASI		
	Rotor/N_2 Tachometer		
	Torquemeter		
	TOT		
	N_1 Tachometer		
	Engine Oil Pressure		
	Engine Oil Temperature		
4.5	Freedom, range of travel, friction of :		
	Cyclic control		
	Collective control		
	Fuel flow control (collective twistgrip)		
	Flight idle stop		
	Yaw control		
	Fuel shut off control		
4.6	Select battery ON, check:		
	Battery voltage (if applicable)		
	Warning lamps and dimmer		
4.7	Operate pilot and co-pilot cyclic beep trim in turn. Confirm satisfactory operation of longitudinal and lateral trim motors		
4.8	Operate pilot and co-pilot N_2 beep switches in turn. Confirm (by listening) that trim motor runs		

5. Starting

5.1 During engine start, note and record:

Residual TOT	°C
Max TOT	ºC
N_1 at start of rotor rotation (max 25%)	%
Satisfactory acceleration to idle	

5.2 Advance twistgrip to fully open and, with collective fully down, check

Correct disc response to ***small*** cyclic inputs:		
All indications in normal range		
All warning lights extinguished		

N_2/N_R beep range

Aircraft	369HE/HS/HM/C		369D/E	
Max	(104-105%)	%	(104-105%)	%
Min	(<100%)	%	(<98%)	%

5.3 Select Engine Anti ice ON

Note TOT rise	ºC
Select engine Anti-ice OFF	
Note TOT fall	ºC

5.4 Select Cabin Heat ON (if installed)

Note TOT rise	ºC	
Confirm satisfactory heater operation		
Select Cabin Heat OFF		
Note TOT fall	ºC	

5.5 Snap the twistgrip to idle

Confirm engine does not flame out		

Allow to stabilise and record idle N_1

Aircraft	369HE/HS/HM/C		369D/E
Engine	250-C18	250-C20	
	(62⇒67%)	(61⇒65%)	(64⇒65%)
	%	%	%

Repeat with Co-Pilot twistgrip (if fitted)		

5.6 Cyclic One-Way lock

At 100% N_R, move the cyclic beeper aft with no aft pressure on cyclic control. Confirm cyclic **does not** move		
Return trim to approximately neutral		

5.7 Check the engine out warning system/ Auto-Reignition Systems described in the flight manual		

5.8 Check for correct functioning of:

Intercomm		
Radio		
Cockpit lighting (if possible)		

Complete all pre-flight checks as required.

6. Take off and Low Speed Envelope

Take off Time

		Satis.	Remarks
6.1	On the ground, adjust N_2/N_R to 98%/467 rpm Lift to a low hover and confirm N_R increases by 1-2%		

6.2 In a low hover, assess the vibration level, control response and position (adequate control margin) during the following manoeuvres (see Appendix 1 for test method)

Axial Turns	Left		
	Right		
Sidewards flight to 17 kt (20mph)	Left		
	Right		
Rearwards flight to 17 kt			

7. Performance, Maximum Continuous Power Climb

With the altimeter set to 1013 mb (29.91 in hg), climb at MAXIMUM CONTINUOUS POWER for 3 min. The climb should be carried out in stable, non-turbulent conditions away from cloud.

Associated Conditions (Do not exceed any of the following)

Engine Type	C18	C20	C20B	C20R
TOT ºC	693	737	738	752
Tq Psi	70	56	81.3	81.3

N_R	(369C/HE/HM/HS)	103% (484rpm)
	(369D/E)	103% (492rpm)

Engine Bleeds	OFF (unless specifically required)
IAS	62kt @ SL reducing in accordance with FM Section 5

When a stable condition has been established on a steady heading with zero yaw, and in as calm conditions as possible, record the following:

Fuel at start of climb [ ] Time [ ]

Time	***Alt***	***OAT***	***IAS***	***Tq***	***TOT***	***N_1***	***N_2/N_R***	***Eng***	
								Temp	***Press***
0									
0.30									
1.00									
1.30									
2.00									
2.30									
3.00									

Fuel at end of climb [ ]

After the climb, obtain an accurate OAT by flying at approx mid-climb altitude at climb speed for 1 min to allow OAT to stabilise.

Alt		ft
OAT		°C

NOTE The climb performance must be analysed and compared with the schedule performance. See Section 12 of this document.

8. Autorotation

See Appendix 2 for measurement of rotor rpm in autorotation

8.1 Perform a gentle entry to a steady autorotative descent at 60kt with the collective lever fully down.

Note: It may be necessary to reduce the engine speed to achieve a full “needles split” autorotation.

DO NOT EXCEED POWER-OFF ROTOR RPM LIMITATIONS

Minimum from RFM =

Maximum from RFM =

Note: Controllability on entry		

8.2 Carry out turns left & right in autorotation		

8.3 Carry out a rapid recovery from autorotation (N_2/N_R needles just joined) to 60 psi Tq in approx 3 sec.

Note: Minimum N_R (a)		rpm
Steady state N_R, post recovery (b)		rpm
Transient rotor droop (b-a)		rpm
Engine response and absence of surge		

9. Handling

9.1 Engine Power Check (369C/D/E)

Carry out power check in accordance with the RFM with all engine bleeds OFF (unless operationally essential), establish level flight at the appropriate power ***(do not exceed V_{NE})***. Note that more accurate data is obtained at higher TOT values.

Record the following when stabilised:

P. Alt		ft	N_1		%
OAT		°C	IAS		kt
Tq		%			
TOT		ºC			

Note: The engine power data must be analysed and compared with the schedule. See Section 12 of this document

9.2 General Handling

With engine bleeds as required, establish level flight at maximum continuous power ***(do not exceed V_{NE})***.

9.2.1 Note:

Vibration level		
Control response		
Lack of pedal creep		

9.2.2 Steep turns left & right (approx 30° at Max. Continuous Power)

Note:

Vibration level		
Control response		

9.2.3 Confirm satisfactory operation of both cyclic trim switches

9.3 Maximum speed test

9.3.1 At a safe altitude, increase speed progressively using max. continuous power.

Note:

P. Alt		ft	OAT		°C
Fuel		lb	Placard V_{NE}		kt
AUW		lb	IAS		kt

Note:

Vibration level		
Control response		

9.3.2 Carry out gentle turns left & right (approx 10º)

Note:

Vibration level		
Control response		
No excessive cyclic or collective feedback		

10. Landing

Landing Time

Confirm no tendency to ground resonance during a smooth landing with a slow gentle. collective lowering

NOTE: Should any divergent oscillations be noted, lift off immediately, reposition the aircraft and carry out a normal landing.

11. Shut down

Shut down time

Shut down the engine in accordance with normal procedures.
Note:

11.1 Satisfactory shut down

11.2 Satisfactory rotor brake performance

12. Post-flight Action

12.1 Performance Climb (see para 7)

Plot the data and determine the achieved rate of climb. The scheduled performance must be obtained from the flight manual and compared with the achieved performance.

Achieved RoC (a)		fpm
Scheduled RoC (b)		fpm
Delta ROC (b-a)		fpm

12.2 Engine Power Check (see para 6.3 or 9)

Use the power check chart in the flight manual to analyse the engine condition

Observed TOT		°C
Schedule TOT		°C
Observed - Scheduled		°C

12.3 Autorotation (see Appendix 2)

Use the chart in the maintenance manual or method in Appendix 2 to determine the minimum scheduled autorevs
.

Achieved autorevs		rpm
Schedule autorevs		rpm
Achieved - scheduled		rpm

13. FLIGHT TEST CERTIFICATE

Complete a statement of defects, sign the Flight Test Certificate stating clearly whether the helicopter needs to be reflown.
When complete, the Report must be passed to the appropriate local surveyor with the performance graph.

Appendix 1

Sidewards & Rearwards Flight

For the sidewards flight tests the helicopter should be rotated so that the natural wind is on the side of the aircraft. The aircraft should then be gently accelerated into the wind and stabilised. The mean natural wind should be added to the estimated ground speed to give the required relative air speed.

For rearwards flight the helicopter should be aligned tail into wind and gently accelerated rearwards to achieve the required relative airspeed.



Appendix 2

Rotor rpm in Autorotation

This test will normally be performed as a separate flight. The aircraft weight must be less than 2500lb

At an acceptable altitude, lower the collective to enter autorotation at 60 kt. Allow to stabilise with the collective fully lowered and record:

Note: It may be necessary to reduce the engine speed to achieve a full "needles split" autorotation.

DO NOT EXCEED POWER-OFF ROTOR RPM LIMITATIONS

Minimum from RFM =

Maximum from RFM =

P. Alt	OAT	IAS	N_R	N_2	Fuel	AUW
Ft	ºC	Kt	Rpm	%	lb	lb

Autorevs at 2516lb, sea level 485 ±5 rpm

Rotor speed will DECREASE by approx 7 rpm for each 100lb REDUCTION in aircraft weight

Rotor speed will INCREASE by approx 6 rpm for each 1000ft INCREASE in density altitude

NOTE: Record achieved and schedule autorevs in section 12 of this document

Record of Changes

Changes from Issue 2 to Issue 3

General Reissue

Changes from CFS Issue 1 to Issue 2

Change to manufacturer's name.

Page 7 para 4.6 Add "If applicable"

Page 10 para 6.3 Delete power check ~ all models now an in-flight check

Page 11 para 7 Add time of start of climb to assist fuel burn calculation for aircraft weight.

Page 12 para 8.1 Delete RPM limits and add lines for limits to be inserted for model type.

Page 13 para 9.1 Changes to refer to RFM for power check procedure and removal of 'Associated Conditions' which were in conflict with RFM procedure. Delete boxes for weight.

Page 15 para 12.2 Change to TOT (was incorrectly torque) and add box for subtracted value

Page 15 para 12.3 Change to rpm from % and add box for subtracted value.

Page 17 Appendix 2 Delete RPM limits and add lines for limits to be inserted for model type. Add note for reducing engine speed.



AIRCRAFT TYPE
REGISTRATION
DATE OF TEST

Mean Weight

_____ lb

Mean Altitude

_____ feet

Mean OAT

_____ °C

SCHEDULED ROC

Basic _____ ft/min

Correction _____ ft/min
(if applicable)

Correction _____ ft/min
(if applicable)

Final SROC _____ ft/min

Observed ROC

_____ ft/min

Difference from Scheduled

_____ ft/min
(Observed ROC minus Final SROC)