



European Aviation Safety Agency

EASA
TYPE-CERTIFICATE
DATA SHEET

EASA.A.563

SKYCAR

Type Certificate Holder:

OMA SUD SPA
Sky Technologies
Via Marra Loc. Silvagni
81043 Capua (CE)
Italy

For model: SKYCAR

Issue 3; 09 July 2010

CONTENT

SECTION A: SKYCAR

- A.I. General
- A.II. Certification Basis
- A.III. Technical Characteristics and Operational Limitations
- A.IV. Operating and Service Instructions
- A.V. Notes

ADMINISTRATIVE SECTION

- I. Acronyms
- II. Type Certificate Holder Record;
- III. Change Record

SECTION 1 SKYCAR

A.I. General

Data Sheet No.EASA.A.563

1. a) Type: SKYCAR

2. Airworthiness Category:
 - a) Normal

3. Type Certificate Holder:

OMA SUD SPA
Sky Technologies
Via Marra Loc. Silvagni
81043 Capua (CE)
Italy
EASA.21J.257

4. Manufacturer:

OMA SUD SPA
Sky Technologies
Via Marra Loc. Silvagni
81043 Capua (CE)
Italy
IT.21G.0038

5. Certification Application Date:

Original Application	17-May-2004
Extension Application	28-Aug-2008

6. EASA Recommendation Date : 08 January 2010

7. EASA Certification Date: 08 January 2010

A.II. Certification Basis

1. Reference Date for determining the applicable requirements: 01-Jan-2007

2. (Reserved)

3. (Reserved)

4. Certification Basis: As defined in CRI A-01, latest Issue

5. Airworthiness Requirements: CS-23, effective 14-Nov-2003

6. Requirements elected to comply: CS-23.1305 (b)(3) "Powerplant instruments"

7. Special Conditions: CRI F-01 HIRF Protection

8. (Reserved):
9. Equivalent Safety Findings: CRI F-11 "Installation of PFD with primary heading information on the top through heading tape"
CRI E-02 "Cowling and nacelle fire protection"
10. Environmental Standards: CS-36
ICAO, Annex 16, Volume 1, Fourth Edition, July 2005

A.III. Technical Characteristics and Operational Limitations

1. Type Design Definition: Doc.No SKC-00-04-01
2. Description: Twin engine, four or five seats, high wing airplane, retractable tricycle landing gear, double T-Tail with high horizontal tail plane
3. Equipment: Equipment list, Doc.No SKC-00-38-03
4. Dimensions:
- | | | |
|-----------|---------------------|--------------|
| Span | 12 m | (39 ft 4 in) |
| Length | 8.92 m | (29 ft 3 in) |
| Height | 2.7 m | (8 ft 9 in) |
| Wing Area | 16.8 m ² | (181 sqft) |
5. Engines: 2 Textron Lycoming IO-360-C1E6
(see EASA list ref. FAA Engine Type Certificate Data Sheet 1E10)
- 5.1 Engine Limits: Max take-off rotational speed 2700 r.p.m.
Max continuous rotational speed 2700 r.p.m.
- For power-plants limits refer to AFM Doc. No SKC-00-38-01
6. (Reserved)
7. Propellers: 2 Hartzell HC-C2YR-2CLUF/FLC7666A-4
(see EASA list ref. FAA TCDS nr. P-920)
- 7.1 Propeller limits
- | | |
|------------------|-----------------|
| Maximum Diameter | 1880 mm (74 in) |
| Minimum Diameter | 1829 mm (72 in) |

8. Fluids:
- 8.1 Fuel: AVGAS 100 LL
- 8.2 Oil: Oils conforming to spec. SAE J1899 / MIL-L-22851
For more details see AFM, SKC-00-38-01, Section 1
- 8.3 Brake MIL-PRF-83282
- 8.4 Shock Absorber MIL-H-5606 colour red
9. Fluid capacities:
- 9.1 Fuel: Standard Fuel Tank
- | | | |
|---------|--------------|-------------------|
| Total: | 2x250 litres | (2x66 US Gallons) |
| Usable: | 2x236 litres | (2x62 US Gallons) |
- 9.2 Oil:
- | | | |
|----------|---------------|------------------|
| Maximum: | 2x7,58 litres | (2x2 US Gallons) |
| Minimum: | 2x1,90 litres | (2x2 US Gallons) |
10. Air Speeds:
- | | | | |
|---|-------------------|----------|------------|
| Minimum Control Speed V_{MC} | | 69 KIAS | (69 KCAS) |
| Design Manoeuvring Speed V_A : | | 134 KIAS | (132 KCAS) |
| Flap Extended Speed V_{FE} : | Flap setting: 15° | 140 KIAS | (140 KCAS) |
| | Flap setting: 35° | 109 KIAS | (110 KCAS) |
| Maximum structural cruising speed V_{NO}
(= Maximum structural design speed V_C): | | 152 KIAS | (150 KCAS) |
| Never exceed speed V_{NE} : | | 168 KIAS | (168 KCAS) |
| Maximum Landing Gear Extended Speed V_{LE} | | 130 KIAS | (130 KCAS) |
| Maximum Landing Gear Operating Speed V_{LO} | | 130 KIAS | (130 KCAS) |
11. Maximum Operating Altitude: 5486.4 m (18000 ft)
12. All weather Capability: Day-VFR
Night VFR
Day and Night IFR Single Pilot
The flight cannot be operated in known icing condition.
13. Maximum Masses:
- | | |
|----------|-------------------|
| Take-off | 1995 kg (4398 lb) |
| Landing | 1895 kg (4178 lb) |
14. Centre of Gravity Range:
- | | |
|---------------|--|
| Forward limit | - 0.336 m (13.23 inches) equivalent to 24% of MAC, aft of datum at MTOW;
- 0.308 m (12.13 inches) equivalent to 22% of MAC aft of datum at 1825 kg (4023 lbs) or less.
Straight line variation between points indicated. |
| Rear limit: | - 0.504 m (19.84 inches) equivalent to 36% of MAC, aft of datum at MTOW; |
15. Datum: The datum line is located at wing leading edge.
16. (reserved)

- | | |
|---|--|
| 17. Levelling Means: | Longitudinal: pilot seat RH sliding track
Lateral: across the pilot seat sliding tracks |
| 18. Minimum Flight Crew: | 1 (Pilot) |
| 19. Maximum Passenger Seating Capacity: | 3 (see note 2) |
| 20. (Reserved) | |
| 21. Baggage / Cargo Compartments | |
| Location | Max. allowable Load |
| Behind Rear Seats | 334 kg (735 lb)
See note 1 |
| 22. Wheels and Tyres | |
| Nose Wheel Tyre Size | 5.00 – 5 |
| Main Wheel Tyre Size | 6.00 – 6
For approved Types and rating
see AMM, Doc. No. SKC-00-39-01 |

A.IV. Operating and Service Instructions

- | | |
|--|---------------------------|
| Airplane Flight Manual (AFM) | Document No. SKC-00-38-01 |
| Airplane Maintenance Manual (AMM)
(incl. Airworthiness Limitations) | Document No. SKC-00-39-01 |
| Service Information and Service Bulletins | |

A.V. Notes

Note 1: the baggage compartment is divided in two areas.

 Zone A behind rear seats Max. allowable Load 200 kg (440 lb)

 Zone B behind rear seats Max. allowable Load 134 kg (295 lb)

Note 2: Maximum passengers seating capacity is 4, when Change to Type Design SKC.03/2010 "Rear Three Seats Bench Installation" is included.

ADMINISTRATIVE SECTION

I. Acronyms
N/A

II. Type Certificate Holder Record:
OMA SUD SPA Sky Technologies

III. Change Record

Issue	Date	Changes	TC Issue No. & Date
1	08 January 2010	Initial Issue	8 January 2010
2	28 June 2010	Modified sec. A.III points 1, 3 and 12 Single Pilot IFR Operation	8 January 2010
3	09 July 2010	Modified sec. A.III points 2, and 19; Note 2 added. Revised standardised TCDS format	8 January 2010