Issue: 15 Date: 09 September 2020



TYPE-CERTIFICATE DATA SHEET

No. EASA.A.110

AIRBUS A380

Type Certificate Holder:

AIRBUS S.A.S

2 ROND-POINT EMILE DEWOITINE

31700 BLAGNAC

FRANCE

Airworthiness Category: Large Aeroplanes

For Models: A380-841/-842

A380-861



Intentionally left blank

Date: 09 September 2020

Issue: 15

TABLE OF CONTENTS

SECTION 1: A380-800 SERIES	5
I. General	5
1. Type/ Model/ Variant	5
2. Performance Class	5
3. Certifying Authority	5
4. Manufacturer	5
5. EASA Type Certification Application Date	5
6. EASA Type Certification Date	5
II. Certification Basis	5
1. EASA Certification Basis	5
2. Special Conditions	5
3. Exemption / Deviation	7
4. Equivalent Safety Findings (JAR 21.21(c)(2))	7
5. Environmental Protection	8
6. Elect to Comply	8
7. Operational Suitability Data	9
III. Technical Characteristics and Operational Limitations	9
1 A380-841/-842 Powered by RR Engines	9
1.1. Type Design Definition	
1.2. Description	10
1.3 Engines	10
1.4. Fluids (Fuel, Oil, Additives, Hydraulics)	10
1.5. Airspeed Limits	10
1.6. Centre of Gravity	11
1.7 Maximum Certified Mass	
2 A380-861 Powered by GP Engines	
2.1. Type Design Definition	
2.2. Description	
2.3 Engines	
2.4. Fluids (Fuel, Oil, Additives, Hydraulics)	
2.5. Airspeed Limits	
2.6. Centre of Gravity	
2.7 Maximum Certified Mass	
3 Data Pertinent to all A380-800 series	
3.1. Equipment	
3.2. Auxiliary Power unit	
3.3 Fluid Capacities	
3.4. Flight Envelope	
3.5. Operating Limitations	
3.6. All Weather Capabilities	
3.7. Minimum Flight Crew	
3.8. Maximum Seating Capacity	
3.9. Minimum Cabin Crew	
3.10. Baggage/ Cargo Compartment	
3.11. Wheels and Tyres	
3.12. Electrical Power Center Configuration Data File Tool	
IV. Operating and Service Instructions	15



TE.CERT.00051-001 © European Aviation Safety Agency, 2020. All rights reserved. ISO9001 Certified. Page 3 of 20 Proprietary document. Copies are not controlled. Confirm revision status through the EASA-Internet/Intranet.

Airbus A380

TCDS No.: A.110

Issue: 15 Date: 09 September 2020

1.	Airplane Flight Manual (AFM)	15
2.	Instructions for Continued Airworthiness and Airworthiness Limitations	15
V. Op	erational suitability Data (OSD)	15
1.	Master Minimum Equipment List	15
	Flight Crew Data	
	Cabin Crew Data	
SECTION	I: ADMINISTRATIVE	17
	onyms and Abbreviations	
	pe Certificate Holder Record	
	ange Record	

SECTION 1: A380-800 SERIES

I. General

1. Type/ Model/ Variant

A380-800

2. Performance Class

Α

3. Certifying Authority

EASA

4. Manufacturer

AIRBUS S.A.S

2 Rond-point Emile Dewoitine

31700 Blagnac FRANCE

5. EASA Type Certification Application Date

A80-841/-842: 20 December 2001 A380-861: 30 April 2003

6. EASA Type Certification Date

A380-841/-842: 12 December 2006 A380-861: 14 December 2007

II. Certification Basis

Non-proprietary data contained in selected SC, ESF, or Deviation that are part of the Certification Basis are published in an Explanatory Note annex to the TCDS with the number: 01. The document is not exhaustive and will be gradually updated. An update of the Explanatory Note will not cause an update of the TCDS.

1. EASA Certification Basis

The following EASA/JAA airworthiness standards effective on the reference date:

- JAR 1 at change 5 plus orange papers 1/97/1 and 1/99/1
- JAR 25 at change 15
- JAR AWO at change 2 (post TC for autoland)

2. Special Conditions

2.1 Special Conditions issued because the product has novel or unusual design features relative to the design practices on which the applicable JAR 25 are based (JAR 21.16(a)(1)):

SC B-01	Stalling and scheduled operating speeds
SC B-02	Motion and effects of cockpit control

SC B-04 Static directional, lateral and longitudinal stability and low energy awareness



TE.CERT.00051-001 © European Aviation Safety Agency, 2020. All rights reserved. ISO9001 Certified. Page 5 of 20 Proprietary document. Copies are not controlled. Confirm revision status through the EASA-Internet/Intranet.

TCDS No.: A.110 Issue: 15 Date: 09 September 2020

SC B-05	Flight envelope protection
SC B-06	Normal load factor limiting system
SC B-10	Human factors evaluation of novel features in the flight deck
SC B-15	Soft Go-Around mode (Post TC)
SC C-01	Crashworthiness of Large Aircraft Structures
SC C-02	Discrete gust
SC C-03	Loading conditions for multi leg landing gear
SC C-04	Undercarriage lateral turning loads
SC C-05	Jacking by landing gear
SC C-06	Dynamic braking
SC C-11	Interaction of systems and structures
SC C-13	Design manoeuvre requirements
SC C-15	Design dive speed Vd
SC C-16	Limit pilot forces
SC D-03	Emergency exit arrangement-outside viewing
SC D-04	Crew rest compartments (Post TC)
SC D-06	Use of stairs between decks
SC D-07	Fire detection and protection in passenger cabin
SC D-12	Design for security
SC D-28	Harmonised 671/672
SC D-33	Extendable length escape slide
SC D-39	Inertia Locking Device in Dynamic Seats (optional)
SC D-41	Installation of Suite Type Seating (optional)
SC D-42	Type C Passenger Exits (optional)
SC D-45	Trolley Stowage/ Lift Systems with Proximity to Upper Deck Staircase
SC D-47	Installation of Inflatable Seat Belts (Optional)
SC D-52	Installation of structure mounted airbag (optional)
SC D-54	Installation of Suite Type Seating for two Passengers (Optional)
SC D-57	Installation High Wall Suite Type seating (optional)
SC D-55	Shower installation (optional)
SC F-01	JAR 25.1301 and 1309 compliance: Design assurance and safety assessment process
SC F-02	Slide/ Raft portability
SC F-12	HIRF Protection
SC F-26	Flight recorders, data link recording
SC F-52	Lithium – Ion battery installation

- 2.2 Special Conditions issued because the intended use of the product is unconventional (JAR 21.16(a)(2):
 - SC D-20 Towbarless towing SC D-31 High altitude operation
 - SC G-06 Ferrying one engine unserviceable (optional)
- 2.3 Special Conditions issued because experience from other products has shown that unsafe conditions may develop (JAR 21.16(a)(3)):



SC D-13 SC D-15	Fire protection of thermal and acoustic insulation material Brakes and braking system – NPA 25D291
SC D-43	Heat Release and Smoke Density to Seat Materials
SC D-46	PED Charging Stowage
SC E-02	Fuel tank safety
SC E-04	Thrust reverser system requirements
SC E-05	Sustained engine imbalance

SC F-GEN-01 Non-rechargeable lithium battery installations, applicable from the issue date of this TCDS at issue 14.

SC H-01 ICA on EWIS

3. Exemption / Deviation

None

4. Equivalent Safety Findings (JAR 21.21(c)(2))

- ESF C-12 Vibration, buffet and aeroelastic stability requirements ESF C-14 Proof of structure ESF C-19 Checked Pitching manoeuvre loads ESF C-20 Engine failure loads ESF C-21 Continuous turbulence loads ESF D-17 Fuselage doors ESF D-19 Casting factors ESF D-21 Allowable carbon dioxide concentration in aeroplane cabins and cabin ozone concentration ESF D-24 Packs off operation ESF D-48 Belly Fairing Thermal/acoustic Insulation Materials ESF D-49 Improved flammability standards for Lower Deck crew ESF D-50 Composite Pressure Bulkhead Thermal/acoustic Insulation Materials ESF D-56 Forward facing seat with more than 18° to a/c centerline ESF E-06 Falling and blowing snow ESF E-09 Fuel tank crashworthiness ESF E-10 Fuel tank access covers ESF E-11 Rolls-Royce Trent turbine overheat detection (for A380-841/-842 models only) ESF E-12 GP 7200 Fan zone as a non fire zone (for A380-861 model only)
- EST E 15 Marriag magnet for anging fivel filters (for
- ESF E-15 Warning means for engine fuel filters (for A380-841/-842 models only)
- ESF E-16 Thrust reverser testing
- ESF E-17 Oil temperature indication
- ESF E-19: Engine fuel filter location (for A380-861 model only)
- ESF E-20 Fire extinguishing agent concentration compliance with JAR 25.1195(c) (Post TC –
- A380-841/-842 models only)
- ESF F-11 Pneumatic systems



TE.CERT.00051-001 © European Aviation Safety Agency, 2020. All rights reserved. ISO9001 Certified. Page 7 of 20 Proprietary document. Copies are not controlled. Confirm revision status through the EASA-Internet/Intranet.

Issue: 15 Date: 09 September 2020

ESF F-15 Hydraulic systems

ESF F-23 Landing light switch

ESF F-29 New Harmonised JAR 25.1329

ESF F-38 Overpressure relief valves and outflow valves

ESF F-48 Use of computer simulation and similarity approach for high energy rotor

containment demonstration

ESF F-53 Supplemental Cooling System – Impeller Pump Containment Test

ESF J-02 APU installation requirements

ESF K-06 Localizer excessive deviation alerts

ESF K-07 Limit Risk (NPA AWO 14)

5. Environmental Protection Requirements

5.1 Noise:

See TCDSN No EASA.A.110

5.2 Fuel venting:

ICAO Annex 16, Second Edition, Volume 2, Amdt 4, Part II and Part III, Chapter 2.

6. Elect to Comply

The following paragraphs of JAR 25 at amendment 16 issued May 1st, 2003 are elected to comply by Airbus:

JAR25.21(d)	JAR25.791	JAR25.954	JAR25.1321	JAR25.1521(d)
JAR25.25	JAR25.803	JAR25.961	JAR25.1325 title	JAR25X1524
JAR25.149(e)	JAR25.807	JAR25.967	JAR25.1415	JAR25.1527
JAR25.251	JAR25.812	JAR25.975(a)(5)	JAR25.1441	JAR25.1545
JAR25X261	JAR25.815	JAR25.981	JAR25.1443	JAR25.1547
JAR25.337	JAR25.853	JAR25.993	JAR25.1445(a)	JAR25.1549
JAR25.493	JAR25.857	JAR25.994	JAR25.1447	JAR25.1581
JAR25.562(b)	JAR25.863(b)(4)	JAR25.997	JAR25.1449	JAR25.1583
JAR25.605	JAR25.904	JAR25.1013	JAR25.1450	JAR25.1585
JAR25.607	JAR25.907	JAR25.1015	JAR25.1457	JAR25.1587
JAR25.701	JAR25.933	JAR25.1019	JAR25.1513	
JAR25.733	JAR25.939	JAR25.1145	JAR25X1516	
JAR25.777	JAR25.951	JAR25.1303	JAR25.1517	
JAR25.781	JAR25.952	JAR25.1305	JAR25.1519	

Appendix D paragraph (b)

Appendix H subparagraph H25.3(e)

Appendix I

Note: JAR 25.1517, as in amendment 16 of JAR 25, is amended by Equivalent Safety Finding ESF C-21.



Issue: 15 Date: 09 September 2020

The following paragraphs of CS 25 at amendment 3 issued September 12, 2007, are elected to comply by Airbus for A/C fitted with modification 71249:

CS 25.811(d), (g) CS 25.811(g) CS 25.812(b)(1)(i) CS 25.812(b)(1)(ii)

The following paragraph of CS 25 at amendment 6 issued July 6, 2009, is elected to comply by Airbus for A/C fitted with modification 67860:

CS 25.856(b)

EASA Certification Specification 25.851 (a) and (c) at Amendment 17 for the installation of halon free hand-held fire extinguisher.

CS-ACNS initial issue for ELS, EHS and ADS-B Out is elected to comply by Airbus for A/C fitted with modification 76012.

The following paragraphs of JAR AWO as modified per NPA AWO 8 and 10, adopted by the JAAC on 07 February 2003, that are elected to comply by Airbus per their letter AI/LE-A 828.0005/99 issue 3 dated 20 July 2001:

Introduction to JAR AWO Subpart 3, section B, 3rd paragraph, Introduction to JAR AWO Subpart 3, section C, 2nd paragraph, Introduction to JAR AWO Subpart 3, section D, 1st paragraph, Introduction to JAR AWO Subpart 4, 2nd paragraph

JAR AWO 131(c)(2)	JAR AWO 313	JAR AWO 316(a)	JAR AWO 381
JAR AWO 304(b)	JAR AWO 314	JAR AWO 321(c)(4)	JAR AWO 481(a)
JAR AWO 305	JAR AWO 316 title	JAR AWO 321(d)(4)	

7. Operational Suitability Data

The EASA Type Certification basis with respect to Grandfathering of Operational Suitability Data (OSD) is defined as follows:

CCD: The certification Basis is defined in CRI CCD-01

MMEL: The Grandfathered OSD certification basis is JAR-MMEL Subpart B Amendment 1

FCD: Certification Specifications for Operational Suitability Data (OSD) Flight Crew Data CS-FCD Initial Issue dated 31 January 2014

III. Technical Characteristics and Operational Limitations

1 A380-841/-842 Powered by RR Engines



TE.CERT.00051-001 © European Aviation Safety Agency, 2020. All rights reserved. ISO9001 Certified. Page 9 of 20 Proprietary document. Copies are not controlled. Confirm revision status through the EASA-Internet/Intranet.

1.1. Type Design Definition

A380-841: 00L000H0841/C0S, Issue 3, October 2007 A380-842: 00L000H0842/C0S, Issue 1, December 2006

1.2. Description

Four turbo-fan, long range, twin-aisle, large category airplane.

1.3 Engines

A380-841: Four (4) RB211 Trent 970-84 or RB211 Trent 970B-84 turbofan engines
A380-842: Four (4) RB211 Trent 972-84 or RB211 Trent 972B-84 or RB211 Trent 972E-84
turbofan engines

Engine Limits:

ENGINE LIMITS DATA SHEET EASA E.012	A380-841	A380-842	A380-842
	RB211 Trent 970B-84	RB211 Trent 972B-84	RB211 Trent 972E-84
Static thrust at sea level: -Take-off (5mn)* (flat rated 30°C)	348.31 kN	356.81 kN	341.41 kN

^{*10} minutes at take-off thrust allowed only in case of engine failure (at take-off or during go-around) in accordance with EASA TCDS paragraph IV-1.

Other engine limitations: See the relevant Engine Type Certificate Data Sheet.

1.4. Fluids (Fuel, Oil, Additives, Hydraulics)

Fuel: The fuel system has been certified with JET A, JET A1, JP5, JP8, N° 3 Jet Fuel,

RT(GOST), TS-1(GOST). The above mentioned fuel types are also suitable for the

APU.

Refer to the applicable Consumable Material List (CML) for comprehensive fuel

types specification.

Oil: Refer to the applicable Consumable Material List (CML).

Refer also to the Engine Manufacturer Operating Instructions.

Additives: Refer to the applicable Consumable Material List (CML).

Hydraulics: Refer to the applicable Consumable Material List (CML).

1.5. Airspeed Limits



TE.CERT.00051-001 © European Aviation Safety Agency, 2020. All rights reserved. ISO9001 Certified. Page 10 of 20 Proprietary document. Copies are not controlled. Confirm revision status through the EASA-Internet/Intranet.

Issue: 15 Date: 09 September 2020

Refer to approved Airplane Flight Manual.

1.6. Centre of Gravity

Refer to approved Airplane Flight Manual.

1.7 Maximum Certified Mass

VARIANT (Modification Number)	000 Basic	001 (64636)	002 (64605)	003 (66611)	004 (69436)	005 (69879)	006 (73786)	007 (71127)
MTW (T)	562	512	571	512	562	562	575	492
MTOW (T)	560	510	569	510	560	560	573	490
MLW (T)	386	394	391	395	391	386	393	395
MZFW (T)	361	372	366	373	366	366	368	373

VARIANT (Modification Number)	008 (73787)	009 (74293)	010 (74294)	011 (75724)	012 (76092)	013 (77844)	014 (77854)
MTW (T)	577	512	482	577	571	494	574
MTOW (T)	575	510	480	575	569	492	572
MLW (T)	394	386	386	395	395	386	391
MZFW (T)	369	361	361	369	366	361	366

2 A380-861 Powered by GP Engines

2.1. Type Design Definition

A380-861: 00L 000H0861/C01, Issue 2, June 2008

2.2. Description

Four turbo-fan, long range, twin-aisle, large category airplane.

2.3 Engines

A380-861: Four (4) Engine Alliance GP7270 P/N GP7270GP01 turbofan engines

Engine Limits:

ENGINE LIMITS	A380-861
DATA SHEET	Engine Alliance
FAA E00072EN	GP7270

Issue: 15 Date: 09 September 2020

Static thrust at sea level:		
- Take-off (5mn)* (flat rated 30°C)	332.44 kN	

^{*}The normal 5 minute takeoff rating may be extended to 10 minutes for engine out contingency in accordance with the FAA TCDS Note 2.

Other engine limitations: See the relevant Engine Type Certificate Data Sheet.

2.4. Fluids (Fuel, Oil, Additives, Hydraulics)

Fuel: The fuel system has been certified with JET A, JET A1, JP5, JP8, N° 3 Jet Fuel,

RT(GOST), TS-1(GOST). The above mentioned fuel types are also suitable for the

APU.

Refer to the applicable Consumable Material List (CML) for comprehensive fuel

types specification.

Oil: Refer to the applicable Consumable Material List (CML).

Refer also to the Engine Manufacturer Operating Instructions.

Additives: Refer to the applicable Consumable Material List (CML).

Hydraulics: Refer to the applicable Consumable Material List (CML).

2.5. Airspeed Limits

Refer to approved Airplane Flight Manual.

2.6. Centre of Gravity

Refer to approved Airplane Flight Manual.

2.7 Maximum Certified Mass

VARIANT (Modification Number)	000 Basic	001 (64636)	002 (64605)	003 (66611)	004 (69436)	005 (69879)	006 (73786)	007 (71127)
MTW (T)	562	512	571	512	562	562	575	492
MTOW (T)	560	510	569	510	560	560	573	490
MLW (T)	386	394	391	395	391	386	393	395
MZFW (T)	361	372	366	373	366	366	368	373

VARIANT (Modification Number)	008 (73787)	009 (74293)	010 (74294)	011 (75724)	012 (76092)	013 (77844)	014 (77854
MTW (T)	577	512	482	577	571	494	574
MTOW (T)	575	510	480	575	569	492	572
MLW (T)	394	386	386	395	395	386	391
MZFW (T)	369	361	361	369	366	361	366



3 <u>Data Pertinent to all A380-800 series</u>

3.1. Equipment

The equipment required by the applicable requirements shall be installed.

Cabin furnishings, equipment and arrangement shall conform to the following specification:

- 00L252C0028/C01 for cabin seats,
- 00L252C0027/C01 for galley,
- 00L252C0032/C01 for cabin attendant seats.

3.2. Auxiliary Power unit

One Pratt & Whitney Canada PW980A

Oils: Refer to the Consumable Material List (CML).

Refer to APU Manufacturers Operating Instructions

3.3 Fluid Capacities

Tanks		Usable Fuel	Unusable Fuel
		Litres (Kg)	Litres (Kg)
	Outer Left	10 340 (8 272)	38 (30)
	Feed 1	27 632 (22 106)	82 (66)
	Mid Left	36 461 (29 169)	50 (40)
	Inner Left	46 142 (36 914)	70 (56)
	Feed 2	29 349 (23 479)	88 (70)
Wing	Feed 3	29 349 (23 479)	88 (70)
	Inner Right	46 142 (36 914)	70 (56)
	Mid Right	36 461 (29 169)	50 (40)
	Feed 4	27 632 (22 106)	82 (66)
	Outer Right	10 340 (8 272)	38 (30)
Trim		23 698 (18 958)	49 (39)
Systems		793 (634)	382 (305)
Total		324339 (259471)	1086 (869)

3.4. Flight Envelope

Refer to approved Airplane Flight Manual.

3.5. Operating Limitations

Refer to approved Airplane Flight Manual.

3.6. All Weather Capabilities



TE.CERT.00051-001 © European Aviation Safety Agency, 2020. All rights reserved. ISO9001 Certified. Page 13 of 20 Proprietary document. Copies are not controlled. Confirm revision status through the EASA-Internet/Intranet.

The aircraft is qualified to Cat 3 precision approach and autoland.

3.7. Minimum Flight Crew

Two (2): Pilot and Co-pilot

3.8. Maximum Seating Capacity

The maximum number of passengers approved for emergency evacuation is: 868

Upper deck: 330 pax Main deck: 538 pax

3.9. Minimum Cabin Crew

In accordance with the following;

	Installed Passenger Seats	Minimum Cabin Crew
Upper Deck	301 to 330	7
Upper Deck	300 or fewer	6*
Main Deck	501 to 538	11
Main Deck	500 or fewer	10

^{*} An additional cabin crew is needed at the fwd stair if the number of installed seats fwd of door U1 L/R is above 30.

NOTE: The above minimum cabin crew numbers are those demonstrated by the type certificate holder. A lower number is acceptable in the case of specific cabin layouts if documented in an EASA approved major design change or Supplemental Type Certificate (STC).

3.10. Baggage/ Cargo Compartment

Cargo compartment	Maximum load (kg)
Forward	28577 kg or 63000 lb
Aft	20310 kg or 44775 lb
Rear (bulk)	2515 kg or 5540 lb

For the positions and the loading conditions authorized in each position (references of containers, pallets and associated weights), see Weight and Balance Manual Chapter 1.10 ref.: 00L080H0001/COS.

3.11. Wheels and Tyres

Tyres mixability: See Service Bulletin A380-32-8021 (Landing Gear – Tires – General Procedures) for allowable combinations.



3.12. Electrical Power Center Configuration Data File Tool

An Airline Configuration Tool (ACTS) has been developed and qualified to allow airlines to manage the Configuration Data File of Secondary Power Distribution Boxes (SPDB). This ACTS tool shall be used in accordance with the SIL "Guidance on Electrical system Configuration Data File update" reference "SIL 24-085".

Applicable version of the ACTS tool is version 2 (CSCI 51220010-7)

IV. Operating and Service Instructions

1. Airplane Flight Manual (AFM)

Approved Aircraft Flight Manual: STL 38000

2. Instructions for Continued Airworthiness and Airworthiness Limitations

Limitations applicable to Safe Life Airworthiness Limitation Items are provided in the A380 Airworthiness Limitations Section Part 1,

Limitations applicable to Damage-Tolerant Airworthiness Limitation Items are provided in the A380 Airworthiness Limitations Section Part 2,

Limitations applicable to Certification Maintenance Requirements are provided in the A380 Airworthiness Limitations Section Part 3,

Limitations applicable to Ageing System Maintenance are provided in the A380 Airworthiness Limitations Section Part 4,

Limitations applicable to Fuel Airworthiness Limitations are provided in the A380 Airworthiness Limitations Section Part 5,

A380 Maintenance Review Board Report.

V. Operational suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Aviation Safety Agency under the EASA Type Certificate [original TC number] as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014.

- 1. Master Minimum Equipment List
 - a. Grandfathered Master Minimum Equipment List applicable on 17 February 2014 and later EASA approved revisions. STL38100 reference introduced from November 2015.
 - b. The Grandfathered OSD certification basis is JAR-MMEL Subpart B Amendment 1
 - c. Required for entry into service by EU operator

2. Flight Crew Data



TE.CERT.00051-001 © European Aviation Safety Agency, 2020. All rights reserved. ISO9001 Certified. Page 15 of 20 Proprietary document. Copies are not controlled. Confirm revision status through the EASA-Internet/Intranet.

Issue: 15 Date: 09 September 2020

a. The Flight Crew data (FCD) reference "A380 Family Operational Suitability Data Flight Crew - L01RP1528235" at the latest applicable revision,

- b. The certification basis is CS-FCD, Initial Issue, dated 31 Jan 2014
- c. Required for entry into service by EU operator
- d. Pilot Type Rating: A 380

3. Cabin Crew Data

- a. The Cabin Crew Data (CCD) reference "A380 Operational Suitability Data Cabin Crew (Ref: L01RP1534107)" at the latest applicable revision as per the defined Operational Suitability Data Certification Basis recorded in CRI CCD-01.
- b. Required for entry into service by EU operator.
- c. The A380-800 aircraft model is a new type for cabin crew

SECTION: ADMINISTRATIVE

I. Acronyms and Abbreviations

APU	Auxiliary Power Unit
AWO	All Weather Operations
CRI	Certification Review Item
EASA	European Aviation Safety Agency
ESF	Equivalent Safety Finding
EWIS	Enhanced Wiring Interconnection System
HIRF	High Intensity Radiated Field
ICA	Instructions for Continued Airworthiness
ICAO	International Civil Aviation Organization
JAA (C)	Joint Aviation Authorities (Central)
JAR	Joint Aviation Requirements
NPA	Notice of Proposed Amendment
PED	Portable Electronic Device
RR	Rolls Royce
SC	Special Condition

TCDS Type Certificate Data Sheet

TCDSN Type Certificate Data Sheet for Noise

II. Type Certificate Holder Record

AIRBUS S.A.S 2 Rond-point Emile Dewoitine 31700 Blagnac **FRANCE**

III. Change Record

Issue	Date	Changes	TC issue
Issue 01	12/12/06	Initial Issue	Initial Issue,
			12/12/06
Issue 02	12/10/07	Section 2, III, 1.1: Correction of Type Definition reference	Initial Issue,
		Section 2, III, 2.9: Update to All Weather Capabilities	12/12/06
		Section 2, III, 2.12: Update to Operational, Maintenance	
		Instructions and Airworthiness Limitation	
Issue 03	14/12/07	Section 2, II, 1.: Inclusion of A380-861 reference	Issue 02,
		Section 2, II, 2.: Inclusion of A380-861 reference	14/12/07
		Section 2, II, 6.: New ESF E-19	
		Section 2, II, 8.: Removal of Additional National Requirements	
		Section 2, II, 8.: Re-number of para 9 to 8, Elect to Comply	

	T	T	
		Section 2, III, 2.: New Section to include A380-861 data	
		Section 2, III, 3.: Re-numbered Section, General Data	
		Section 2, III, 3.12.:Update to Operational, Maintenance	
		Instructions and Airworthiness Limitation	
Issue 04	20/02/09	Section 2, II, 4.1: New Special Conditions, D-39,-41,-42,-45	Issue 02,
		Removal of erroneous CRI Reference	14/12/07
		Section 2, II, 4.3: New Special Conditions, D-43	
		Section 2, II, 5.: Removal of para 5, Temporary Deviation	
		Section 2, II, 5.: Re-numbering of following paragraphs	
		Section 2, III, 1.3: Correction to, plus additional fuel refs	
		Section 2, III, 1.6: Additional Weight Variant	
		Section 2, III, 2.1: Update to Type Definition A380-861	
		Section 2, III, 2.2.1: Additional Engine variant, GP7270E, note	
		Section 2, III, 2.3: Correction to, plus additional fuel refs	
		Section 2, III, 2.6: Additional Weight Variant	
		Section 2, III, 3.8: Correction to Equipment references	
		Section 2, III, 3.12: Update to Operational, Maintenance	
		Instructions and Airworthiness Limitation	
Issue 05	01/12/09	Addition of Change Record	Issue 02,
		Section 2, II, 4.3: New Special Condition D-46	14/12/07
		Section 2, III, 1.6: Additional Weight Variants	
		Section 2, III, 2.6: Additional Weight Variant	
		Section 2, III, 3.10: Wheels and Tyres mixability allowed	
		Section 2, III, 3.11: Correction to Hydraulic Fluid Specification	
		Section 2, III, 3.12: Update to Operational, Maintenance	
		Instructions and Airworthiness Limitation	
Issue 06	28/07/11	Section 2, II, 4.1: New Special Condition D-47	Issue 02,
		Section 2, II, 5: New ESF, D-48, D-49 and D-50	14/12/07
		Section 2, III, 1.6: Additional Weight Variant 007	
		Section 2, III, 2.6: Additional Weight Variant 007	
		Section 2, III, 3.9: Addition of "Electrical Power Center	
		Configuration Data File Tool paragraph	
		Section 2, III, 3.13: Update to Operational, Maintenance	
		Instructions and Airworthiness Limitation	
Issue 07	16/09/11	Section 1, II, 5.3: Addition of SC H-01 "ICA on EWIS"	Issue 02,
		Correction of errors in Change Record Issue 06	14/12/07
		Content restructured and completed to match new TCDS	
		format (new numbering scheme)	
Issue 08	24/09/13	Section 1, II, 3.1: Addition of SC B-15, D-52 and D-55	Issue 02,
		Section 1, II, 4: Addition of ESF D-56 and E-20	14/12/07
		Section 1, III, 1.4: Correction of fuel specifications	
		Section 1, III, 1.7: Addition of Weight Variants 006 and 008	
		Section 1, III, 2.3: Deletion of reference to GP7270E according	
		to the Engine Alliance GP7270 TCDS	
		Section 1, III, 2.4: Correction of fuel specifications	
		Section 1, III, 2.7: Addition of Weight Variants 006 and 008	
		Section 1, III, 2.8: Deletion of Note related to Engine Alliance	
		GP7270E	
		Section 1, IV, 2: Update of Instructions for Continued	

		Airmonthia and Airmonthia and Liucitation and Airmonthia	
1 22	44/42/45	Airworthiness and Airworthiness Limitations references	1
Issue 09	11/12/15	New EASA Template - change of Logo Section 1, II: Introduction on Explanatory Note to the TCDS Section 1, II, 1: deletion of TCDS No. § re-numbering of following § Section 1, II, 2.1: Addition of SC, D-54, D-57 Section 1, II, 6: Addition of Elect to Comply by Airbus of CS25.811 (d),(g) and CS25.812(b)(1)(i),(ii) at amendment3 for	Issue 02, 14/12/07
		A/C fitted with modification 71249 Section 1, II, 6: Addition of Elect to Comply by Airbus of CS25.856(b) at amendment 6 for A/C fitted with modification 67860 Section 1, II, 7: Addition of new § for OSD Section 1, III, 1.7: Addition of WV009, WV0010, WV011 and WV012 Section 1, III, 2.7: Addition of WV009, WV0010, WV011 and WV012 Section 1, III, 3.3: deletion of 6 propeller re-numbering of following § Section 1, III, 3.8: Update Maximum Seating Capacity Section 1, III, 3.9: Addition of new § Minimum Cabin Crew Section 1, IV, 2: Update of Instructions for Continued Airworthiness and Airworthiness Limitations references Section V: Addition of § Operational Suitability Data Addition of Annex 1 – List of SC, ESF and Deviations	
Issue 10	12/07/17	Section 1, II, 7: correction of Typo for JAR-MMEL Subpart B Section 1, III, 1.3: Addition of engine Model Trent 972E correction of typo on referenced TCDS § numbering Section 1, V, 1: addition of § c. Section 1, V, 2: correction of § numbering. Section 1, IV, 2: suppression of ALS revision numbers and deletion of ALS part 6 following approval of security handbook, and deletion of Note	Issue 02, 14/12/07
Issue 11	18/09/17	Cover Page update with new Airbus headquarter address Section 1, II, 6: Addition of Elect to Comply to § CS 25.851(a),(c) at Amdt.17 by Airbus CRI D-GEN-AIRBUS-01.	Issue 02, 14/12/07
Issue 12	27/09/17	Section 1, I, 4: TC holder address update Section Administrative II: TC holder address update	Issue 3, 27/09/17
Issue 13	15/11/18	Section 1, II, 5: New Noise requirements Section 1, II, 6: Elect to Comply with CS-ACNS Section 1, III, 1.7 and 2.7: introduction of WV013 & 014	Issue 3, 27/09/17
Issue 14	12/07/19	Section 1, II, 2.3: Addition of SC F-GEN-01, Section 1, II, 6: Paragraph related to CS 25.851 (a) (c) amended for harmonisation with other Airbus program and CRI D-GEN-AIRBUS-01 reference removed.	Issue 3, 27/09/17
Issue 15	09/09/20	Section 1, II, 5.2: correction of header Section 1, III, 1.3 and 2.3, deleted "approved oil" line (covered now in 1.4 and 2.4)	Issue 3, 27/09/17

Section 1, III, 1.4 and 2.4: Approved fuel types, oil types and fuel additives section content harmonised with other Airbus	
programmes.	

-END-