



TYPE-CERTIFICATE DATA SHEET

No. EASA.IM.A.205

for

Boeing 757

Type Certificate Holder:

The Boeing Company

P.O. Box 3707
Seattle, WA 98124-2207
USA

For Models: 757-200
757-200PF
757-300



TABLE OF CONTENTS

TABLE OF CONTENTS	2
SECTION 1: 757-200	3
I. GENERAL	3
II. CERTIFICATION BASIS.....	3
III. TECHNICAL CHARACTERISTICS AND OPERATIONAL LIMITATIONS	4
IV. OPERATING AND SERVICE INSTRUCTIONS	8
V. OPERATIONAL SUITABILITY DATA (OSD)	9
VI. NOTES	9
SECTION 2: 757-200PF	10
I. GENERAL	10
II. CERTIFICATION BASIS.....	10
III. TECHNICAL CHARACTERISTICS AND OPERATIONAL LIMITATIONS	11
IV. OPERATING AND SERVICE INSTRUCTIONS	14
V. OPERATIONAL SUITABILITY DATA (OSD)	15
VI. NOTES	15
SECTION 3: 757-300	16
I. GENERAL	16
II. CERTIFICATION BASIS.....	16
III. TECHNICAL CHARACTERISTICS AND OPERATIONAL LIMITATIONS	19
IV. OPERATING AND SERVICE INSTRUCTIONS	22
V. OPERATIONAL SUITABILITY DATA (OSD)	22
VI. NOTES	23
SECTION: ADMINISTRATIVE	24
I. ACRONYMS AND ABBREVIATIONS	24
II. TYPE CERTIFICATE HOLDER RECORD.....	24
III. CHANGE RECORD.....	24



SECTION 1: 757-200

I. General

1. Type/Model/Variant

Type: 757
Model: 200

2. Performance Class

A

3. Certifying Authority

Federal Aviation Authority (FAA) USA
Seattle Aircraft Certification Office
1601 Lind Avenue S.W.
Seattle, Washington 98055-4056
USA

4. Manufacturer

The Boeing Company
P.O. Box 3707
Seattle, Washington 98124-2207
USA

5. FAA Certification Application Date

28 February 1978

6. EASA Validation Application Date

In accordance with Regulation (EC) 1702/2003

7. FAA Type Certificate Date

21 December 1982

8. EASA Type Certification Date

03 February 1984

II. Certification Basis

1. Reference Date for determining the applicable requirements

In accordance with Regulation (EC) 1702/2003

2. FAA Type Certification Data Sheet No.

Refer to FAA TCDS A2NM

3. FAA Certification Basis

Refer to FAA TCDS A2NM



SECTION 1: 757-200 – continued

4. EASA Airworthiness Requirements

In accordance with Regulation (EC) 1702/2003.
FAA Certification Basis Refer to FAA TCDS A2NM

5. Special Conditions

SC H-01 Enhanced Airworthiness Programme for Aeroplane Systems - ICA on EWIS
Adopted FAA Special Conditions see FAA TCDS A2NM

6. Exemptions

Adopted FAA Exemptions see FAA TCDS A2NM

7. Deviations

Adopted FAA Deviations see FAA TCDS A2NM

8. Equivalent Safety Findings

Adopted FAA Equivalent Safety Findings see FAA TCDS A2NM

9. Environmental Protection

Noise: ICAO Annex 16, Volume I
Fuel Venting & Emissions: ICAO Annex 16, Volume II

III. Technical Characteristics and Operational Limitations

1. Type Design Definition

Refer to FAA TCDS A2NM

2. Description

Low wing jet transport with a conventional tail unit configuration, powered by two high bypass turbofan engines mounted on pylons beneath the wings.



SECTION 1: 757-200 – continued

3. Equipment

Refer to FAA TCDS A2NM

4. Dimensions

Length	47.32 m	(155 ft 3 ins)
Wing Span	38.02 m	(124 ft 10 ins)
Height	13.74 m	(45 ft 1 ins)

5. Engines

Two (2) Rolls-Royce RB211-535C-37 or RB211-535E4-37 or RB211-535E4-B-37 Turbofan Engines

Engine data sheet: FAA TCDS E12EU

Or

Two (2) Pratt and Whitney Turbofan Engines PW2040 or PW2037

Engine data sheet: FAA TCDS E17NE

For limitations see engine datasheet, airplane data sheet (A2NM) and Airplane Flight Manual

For engine operating limits see CAA-UK Engine Type Certificate Data Sheet No. 1044 for Rolls Royce RB211-535C-37, RB211-535E4-37, or RB211-535E4-B-37 engine; TC Data Sheet No. E17NE for the Pratt & Whitney PW2037, PW2037(M) or PW2040, or the EASA-approved Airplane Flight Manual. Except for Rolls Royce RB211-535-C-37 engine, the normal 5 minute take-off time limit may be extended to 10 minutes for engine out contingency if permitted by the Limitations Section of the EASA approved Airplane Flight Manual.

6. Auxiliary Power Unit

Garrett GTCP 331-200A or Garrett GTCP 331-200ER

Limitations: Refer to the APU TCDS / TSO

7. Propellers

Reserved

8. Fluids (Fuel, Oil, Additives, Hydraulics)

Refer to applicable approved manuals and FAA TCDS A2NM



SECTION 1: 757-200 – continued

9. Fluid Capacities

Refer to applicable approved manuals and FAA TCDS A2NM

10. Airspeed Limits

For airspeed limits see the FAA TCDS A2NM and appropriate FAA Approved Airplane Flight Manual.

11. Flight Envelope

12,800 m (42,000 ft) pressure altitude

12. Operating Limitations

12.1 Approved Operations

See the appropriate FAA Approved Airplane Flight Manual and FAA TCDS A2NM

12.2 Other Limitations

See the appropriate FAA Approved Airplane Flight Manual and FAA TCDS A2NM

13. Maximum Certified Masses

13.1 Aircraft Line Numbers 1 through 124*

	<u>Kilograms</u>	<u>Pounds</u>
MTW	109315	241000
MTOW	108862	240000
MLW	90000	198400
MZFW	83500	184100

13.2 Aircraft Line Numbers 125 through 209*

	<u>Kilograms</u>	<u>Pounds</u>
MTW	116119	256000
MTOW	115893	255500
MLW	90000	198400
MZFW	83500	184100



SECTION 1: 757-200 – continued

13.3 Aircraft Line Numbers 210 through 299 with Rolls Royce Engines*

	<u>Kilograms</u>	<u>Pounds</u>
MTW	116119	256000
MTOW	115893	255500
MLW	95254	210000
MZFW	84368	186000

13.4 Aircraft Line Numbers 210 through 299 with Pratt and Whitney Engines*

	<u>Kilograms</u>	<u>Pounds</u>
MTW	116119	256000
MTOW	115893	255500
MLW	95254	210000
MZFW	84368	186000

13.5 Aircraft Line Numbers 300 and above*

	<u>Kilograms</u>	<u>Pounds</u>
MTW	116119	256000
MTOW	115893	255500
MLW	95254	210000
MZFW	90718	200000

*Refer to the Weight & Balance Manual for eligible serial numbers and restrictions

14. Centre of Gravity Range

See the appropriate FAA Approved Airplane Flight Manual and Weight and Balance Manual

15. Datum

Refer to FAA TCDS A2NM

16. Mean Aerodynamic Chord (MAC)

Refer to FAA TCDS A2NM

17. Levelling Means



SECTION 1: 757-200 – continued

Refer to FAA TCDS A2NM

18. Minimum Flight Crew

Two (2): Pilot and Co-pilot

19. Maximum Seating Capacity

Refer to FAA TCDS A2NM

20. Baggage/ Cargo Compartment

See Weight & Balance Manual

21. Wheels and Tyres

See appropriate Airplane Flight Manual and FAA TCDS A2NM for details

IV. Operating and Service Instructions

1. Airplane Flight Manual (AFM)

Boeing Document No. D631N001 is the basic FAA-Approved Flight Manual for Model 757-200 airplanes powered by RB211-535-C-37 engines.

Boeing Document No. D631N002 is the basic FAA-Approved Flight Manual for Model 757-200 airplanes powered by P&W 2037 and P&W 2040 engines, and for Model 757-200PF airplanes powered by P&W 2037 and 2040 engines.

Boeing Document No. D631N005 is the basic FAA-Approved Flight Manual for Model 757-200 airplanes powered by RB211-535-E4-37 and RB211-535-E4-B-37 engines, and for Model 757-200PF powered by RB211-535-E4-37 engines.

Boeing Document No. D631N007.F00 is the basic FAA-Approved Flight Manual for Model 757-300 airplanes powered by RB211-535E4-37, RB211-535E4-B-37, or RB211-535E4-C-37 engines.

Boeing Document No. D631N007.F01 is the basic FAA-Approved Flight Manual for Model 757-300 airplanes powered by PW2037, PW2040 or PW2043 engines.



SECTION 1: 757-200 – continued

2. Instructions for Continued Airworthiness and Airworthiness Limitations

Boeing Document No. D332N402, Maintenance Planning Document

3. Weight and Balance Manual (WBM)

Boeing Document No. D043N302, Weight and Balance Manual

V. Operational Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Aviation Safety Agency under the EASA Type Certificate [original TC number] as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014.

1. Master Minimum Equipment List

No EASA MMEL available (not required per COMMISSION REGULATION (EU) No 69/2014 of 27 January 2014).

2. Flight Crew Data

- a. The Flight Crew data D6-85798, Revision New, as per the defined Operational Suitability Data Certification Basis recorded in document D6-85798, or later recorded CRI A-FCD.
- b. Required for entry into service by EU operator.
- c. Pilot Type Rating: "B757/767".

Note: These data cover the models B757-300 and -300 series and the B767-200, -300, -300F and -400ER series aircraft. Differences are addressed in D6-85798.

3. Cabin Crew Data

No CCD available (not required per COMMISSION REGULATION (EU) No 69/2014 of 27 January 2014).

VI. Notes

Refer to FAA TCDS A2NM for applicable notes



SECTION 2: 757-200PF

I. General

1. Type/Model/Variant

Type: 757

Model: 200PF

2. Performance Class

A

3. Certifying Authority

Federal Aviation Authority (FAA) USA
Seattle Aircraft Certification Office
1601 Lind Avenue S.W.
Seattle, Washington 98055-4056
USA

4. Manufacturer

The Boeing Company
P.O. Box 3707
Seattle, Washington 98124-2207
USA

5. FAA Certification Application Date

23 April 1985

6. EASA Validation Application Date

In accordance with Regulation (EC) 1702/2003

7. FAA Type Certificate Date

03 September 1987

8. EASA Type Certification Date

17 September 1991

II. Certification Basis

1. Reference Date for determining the applicable requirements

In accordance with Regulation (EC) 1702/2003

2. FAA Type Certification Data Sheet No.

Refer to FAA TCDS A2NM

3. FAA Certification Basis

Refer to FAA TCDS A2NM



SECTION 2: 757-200PF – continued

4. EASA Airworthiness Requirements

In accordance with Regulation (EC) 1702/2003.
FAA Certification Basis Refer to FAA TCDS A2NM

5. Special Conditions

SC H-01 Enhanced Airworthiness Programme for Aeroplane Systems - ICA on EWIS
Adopted FAA Special Conditions see FAA TCDS A2NM

6. Exemptions

Adopted FAA Exemptions see FAA TCDS A2NM

7. Deviations

Adopted FAA Deviations see FAA TCDS A2NM

8. Equivalent Safety Findings

Adopted FAA Equivalent Safety Findings see FAA TCDS A2NM

9. Environmental Protection

Noise: ICAO Annex 16, Volume I
Fuel Venting & Emissions: ICAO Annex 16, Volume II

III. Technical Characteristics and Operational Limitations

1. Type Design Definition

Refer to FAA TCDS A2NM

2. Description

Low wing jet transport with a conventional tail unit configuration, powered by two high bypass turbofan engines mounted on pylons beneath the wings. The Model 757-200PF



SECTION 2: 757-200PF – continued

(Package Freighter) is a derivative of the Model 757-200 and is designed for commercial transportation of palletized and bulk cargo

3. Equipment

Refer to FAA TCDS A2NM

4. Dimensions

Length	47.32 m	(155 ft 3 ins)
Wing Span	38.02 m	(124 ft 10 ins)
Height	13.74 m	(45 ft 1 ins)

5. Engines

2 Pratt & Whitney PW2037, 2 Pratt & Whitney PW2040

Engine data sheet: FAA TCDS E17NE

Or

2 Rolls-Royce RB211-535E4-37, 2 Rolls Royce RB211-535E4-B-37

Engine data sheet: FAA TCDS E12EU

Refer to FAA-Approved Airplane Flight Manual for aircraft engine intermix eligibility

6. Auxiliary Power Unit

Garrett GTCP 331-200A or Garrett GTCP 331-200ER

Limitations: Refer to the APU TCDS / TSO

7. Propellers

Reserved

8. Fluids (Fuel, Oil, Additives, Hydraulics)

Refer to applicable approved manuals and FAA TCDS A2NM

9. Fluid Capacities

Refer to applicable approved manuals and FAA TCDS A2NM



SECTION 2: 757-200PF – continued

10. Airspeed Limits

For airspeed limits see the FAA TCDS A2NM and appropriate FAA Approved Airplane Flight Manual.

11. Flight Envelope

12,800 m (42,000 ft) pressure altitude

12. Operating Limitations

12.1 Approved Operations

See the appropriate FAA Approved Airplane Flight Manual and FAA TCDS A2NM

12.2 Other Limitations

See the appropriate FAA Approved Airplane Flight Manual and FAA TCDS A2NM

13. Maximum Certified Masses

	<u>Kilograms</u>	<u>Pounds</u>
MTW	116119	256000
MTOW	115892	255500
MLW	95254	210000
MZFW	90718	200000

Refer to the Weight & Balance Manual for eligible serial numbers and restrictions

14. Centre of Gravity Range

See the appropriate FAA Approved Airplane Flight Manual and Weight and Balance Manual

15. Datum

Refer to FAA TCDS A2NM

16. Mean Aerodynamic Chord (MAC)

Refer to FAA TCDS A2NM



SECTION 2: 757-200PF – continued

17. Levelling Means

Refer to FAA TCDS A2NM

18. Minimum Flight Crew

Two (2): Pilot and Co-pilot

19. Maximum Seating Capacity

Refer to FAA TCDS A2NM

20. Baggage/ Cargo Compartment

See Weight & Balance Manual

21. Wheels and Tyres

See appropriate Airplane Flight Manual and FAA TCDS A2NM for details

IV. Operating and Service Instructions

1. Airplane Flight Manual (AFM)
Boeing Document No. D631N002 is the basic FAA-Approved Flight Manual for Model 757-200PF airplanes powered by Pratt &Whitney PW2037 and PW2040 engines.
Boeing Document No. D631N005 is the basic FAA-Approved Flight Manual for Model 757-200PF powered by RB211-535E4-37 engines.
2. Instructions for Continued Airworthiness and Airworthiness Limitations
Boeing Document No. D332N402, Maintenance Planning Document
3. Weight and Balance Manual (WBM)
Boeing Document No. D043N302



SECTION 2: 757-200PF – continued

V. Operational Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Aviation Safety Agency under the EASA Type Certificate [original TC number] as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014.

1. Master Minimum Equipment List

No EASA MMEL available (not required per COMMISSION REGULATION (EU) No 69/2014 of 27 January 2014).

2. Flight Crew Data

- a. The Flight Crew data D6-85798, Revision New, as per the defined Operational Suitability Data Certification Basis recorded in document D6-85798, or later recorded CRI A-FCD.
- b. Required for entry into service by EU operator.
- c. Pilot Type Rating: "B757/767".

Note: These data cover the models B757-300 and -300 series and the B767-200, -300, -300F and -400ER series aircraft. Differences are addressed in D6-85798.

3. Cabin Crew Data

No CCD available (not required per COMMISSION REGULATION (EU) No 69/2014 of 27 January 2014).

VI. Notes

Refer to FAA TCDS A2NM for applicable notes



SECTION 3: 757-300

I. General

1. Type/Model/Variant

Type: 757
Model: 300

2. Performance Class A

3. Certifying Authority Federal Aviation Authority (FAA) USA
Seattle Aircraft Certification Office
1601 Lind Avenue S.W.
Seattle, Washington 98055-4056
USA

4. Manufacturer The Boeing Company
P.O. Box 3707
Seattle, Washington 98124-2207
USA

5. FAA Certification Application Date 21 February 1996

6. EASA Validation Application Date In accordance with Regulation (EC) 1702/2003

7. FAA Type Certificate Date 22 January 1999

8. EASA Type Certification Date 25 January 1999

II. Certification Basis

1. Reference Date for determining the applicable requirements

21 February 1996

2. FAA Type Certification Data Sheet No.

Refer to FAA TCDS A2NM

3. FAA Certification Basis



SECTION 3: 757-300 – continued

Refer to FAA TCDS A2NM

4. EASA Airworthiness Requirements

In accordance with Regulation (EC) 1702/2003.

JAA Airworthiness Requirements

JAR 25 Change 14, effective 27 May 1994

JAR AWO Change 2

The following NPA's have been applied:

- NPA 25C-199 Interaction of Systems and Structure
- NPA 25B-215 Stall and Stall Warning Speeds and Manoeuvre Capability
- NPA 25BCD-236 Vibration, Buffet and Aeroelastic Stability
- NPA 25-240 Landing in Abnormal Configuration
- NPA 25BDG-244 Accelerate Stop Distances and Related Performance
- NPA 25B-261 Control Forces, Manoeuvre Stability, Minimum Control Speeds and Stalling
- NPA 25C-260 Loads – General
- NPA 25C-276 Brake Roll Condition
- NPA 25C-279 Shock Absorption Tests
- NPA 25 FD-243 Autopilot

The following reversions from the defined certification basis have been applied:

- Reversion from JAR 25.571, Damage Tolerance and Fatigue Evaluation.
- Reversion from JAR 25.901(b)(1)(ii) 25.901(c), Engine Controls, Electronic.
- Reversion from JAR 25.783, Doors
- Reversion from JAR 25.562(c)(5),(c)(6) Emergency Landing Conditions
- Reversion from JAR 25.365(e)(2), Pressurised Compartment Loads-Equipment Bays
- Reversion from JAR 25X519(b), Static Ground Load Conditions – Jacking
- Reversion from JAR 25.1419, Ice Protection Flight Deck Indication
- Reversion from JAR 25.901(c) 25A901(c), Engine, APU, Fuel Systems
- Reversion from JAR 25.775, Windshield and Windows
- Reversion from JAR 25.773(b)(2), Pilot Compartment View
- Reversion from JAR 25.1438, ECS Compartment Proof and Burst Test Pressure
- Reversion from JAR 25.1309, Equipment, Systems and Installation
- Reversion from JAR 25.963(g)(1), Fuel Tank Access Cover
- Reversion from JAR 25X745(d), Nose Wheel Steering
- Reversion from JAR 25.729(f), Tyre and Wheel Threat
- Reversion from JAR 25.903(d)(1), Uncontained Engine Rotor Failures



SECTION 3: 757-300 – continued

5. Special Conditions

SC H-01 Enhanced Airworthiness Programme for Aeroplane Systems - ICA on EWIS

JAA Special Conditions

The following Special Conditions have been applied:

- JAA/757-300/ND/CRI F-08 MMR Qualification and Installation
- JAA/757-300/ND/CRI F-11 EGPWS
- JAA/757-300/ND/CRI F-15 FANS-1
- JAA/757-300/SC/CRI D-02 Worn Brakes
- JAA/757-300/SC/CRI D-20 Towbarless Towing, Nose Wheel Steering
- JAA/757-300/SC/CRI E-02 Engine Type Certification
- JAA/757-300/SC/CRI F-01 Protection from the effects of HIRF
- JAA/757-300/SC/CRI F-02 Lightning Protection - Directs Effects
- JAA/757-300/SC/CRI F-03 Lightning Protection - Indirect Effects
- JAA/757-300/SC/CRI G-01 Computerised AFM
- JAA/757-300/SC/CRI G-02 Aeroplane Flight Manual

Adopted FAA Special Conditions see FAA TCDS A2NM

6. Exemptions

The following exemptions have been granted:

- JAA/757-300/EX/CRI D-12 Partial Exemption from JAR 25.1435(b)(1)
- JAA/757-300/EX/CRI E-06 Exemption from JAR 25.961(a)(5), JAR25.1521

Adopted FAA Exemptions see FAA TCDS A2NM

7. Deviations

Adopted FAA Deviations see FAA TCDS A2NM

8. Equivalent Safety Findings

JAA Equivalent Safety Findings

The following Equivalent Safety findings have been granted:

- JAA/757-300/ES/CRI B-04 Equivalent Safety with JAR 25.1303(c)
- JAA/757-300/ES/CRI D-05 Equivalent Safety with JAR 25.791 & 853
- JAA/757-300/ES/CRI D-06 Equivalent Safety with JAR 25.807 & 813
- JAA/757-300/ES/CRI D-07 Equivalent Safety with JAR 25.807 & 809



SECTION 3: 757-300 – continued

- JAA/757-300/ES/CRI D-08 Equivalent Safety with JAR 25.810
- JAA/757-300/ES/CRI D-10 Equivalent Safety with JAR 25.812
- JAA/757-300/ES/CRI D-16 Equivalent Safety with JAR 25.810(a)(1)(iii)
- JAA/757-300/ES/CRI D-17 Equivalent Safety with JAR 25X1436
- JAA/757-300/ES/CRI D-19 Equivalent Safety with JAR 25.811(f)
- JAA/757-300/ES/CRI E-01 Equivalent Safety with JAR 25.933(a)
- JAA/757-300/ES/CRI F-10 Equivalent Safety with JAR 25.1389(b)(3)
- JAA/757-300/ES/CRI J-01 Equivalent Safety with JAR Subpart J as required by JAR 25.A901(b)(1)

Adopted FAA Equivalent Safety Findings see FAA TCDS A2NM

9. Environmental Protection

Noise: ICAO Annex 16, Volume I

Fuel Venting & Emissions: ICAO Annex 16, Volume II

III. Technical Characteristics and Operational Limitations

1. Type Design Definition

Refer to FAA TCDS A2NM

2. Description

Low wing jet transport with a conventional tail unit configuration, powered by two high bypass turbofan engines mounted on pylons beneath the wings

3. Equipment

Refer to FAA TCDS A2NM

4. Dimensions

Length	54.4 m	(178 ft 7 ins)
Wing Span	38.02 m	(124 ft 10 ins)
Height	13.6 m	(45 ft 1 ins)

5. Engines



SECTION 3: 757-300 – continued

2 Rolls-Royce RB211-535E4-37 or 2 Rolls-Royce RB211-535E4-B-37 or 2 Rolls-Royce RB211-535E4-C-37

Engine data sheet: FAA TCDS E12EU

Or

2 Pratt & Whitney PW2037, PW2040 or PW2043

Engine data sheet: FAA TCDS E17NE

Refer to FAA-Approved Airplane Flight Manual for aircraft engine intermix eligibility

6. Auxiliary Power Unit

Garrett GTCP 331-200A or Garrett GTCP 331-200ER

Limitations: Refer to the APU TCDS / TSO

Allied Signal Model 331-200

Limitations: Refer to the APU TCDS / TSO

7. Propellers

Reserved

8. Fluids (Fuel, Oil, Additives, Hydraulics)

Refer to applicable approved manuals and FAA TCDS A2NM

9. Fluid Capacities

Refer to applicable approved manuals and FAA TCDS A2NM

10. Airspeed Limits

For airspeed limits see the FAA TCDS A2NM and appropriate FAA Approved Airplane Flight Manual.

11. Flight Envelope

12,800 m (42,000 ft) pressure altitude

12. Operating Limitations

12.1 Approved Operations

See the appropriate FAA Approved Airplane Flight Manual and FAA TCDS A2NM



SECTION 3: 757-300 – continued

12.2 Other Limitations

See the appropriate FAA Approved Airplane Flight Manual and FAA TCDS A2NM

13. Maximum Certified Masses

	<u>Kilograms</u>	<u>Pounds</u>
MTW	124057	273500
MTOW	123830	273000
MLW	101605	224000
MZFW	95254	210000

Refer to the Weight & Balance Manual for eligible serial numbers and restrictions

14. Centre of Gravity Range

See the appropriate FAA Approved Airplane Flight Manual and Weight and Balance Manual

15. Datum

Refer to FAA TCDS A2NM

16. Mean Aerodynamic Chord (MAC)

Refer to FAA TCDS A2NM

17. Levelling Means

Refer to FAA TCDS A2NM

18. Minimum Flight Crew

Two (2): Pilot and Co-pilot

19. Maximum Seating Capacity

Refer to FAA TCDS A2NM

20. Baggage/ Cargo Compartment



SECTION 3: 757-300 – continued

See Weight & Balance Manual

21. Wheels and Tyres

See appropriate Airplane Flight Manual and FAA TCDS A2NM for details

IV. Operating and Service Instructions

1. Airplane Flight Manual (AFM)

Boeing Document No. D631N007.F00 is the basic FAA-Approved Flight Manual for Model 757-300 airplanes powered by RB211-535E4-37, RB211-535E4-B-37, or RB211-535E4-C-37 engines.

Boeing Document No. D631N007.F01 is the basic FAA-Approved Flight Manual for Model 757-300 airplanes powered by PW2037, PW2040 or PW2043 engines.

2. Instructions for Continued Airworthiness and Airworthiness Limitations

Boeing Document No. D332N402, Maintenance Planning Document.

3. Weight and Balance Manual (WBM)

See Weight and Balance Manual Boeing Document No. D043N302

V. Operational Suitability Data (OSD)

The Operational Suitability Data elements listed below are approved by the European Aviation Safety Agency under the EASA Type Certificate [original TC number] as per Commission Regulation (EU) 748/2012 as amended by Commission Regulation (EU) No 69/2014.

1. Master Minimum Equipment List

No EASA MMEL available (not required per COMMISSION REGULATION (EU) No 69/2014 of 27 January 2014).

2. Flight Crew Data



SECTION 3: 757-300 – continued

- a. The Flight Crew data D6-85798, Revision New, as per the defined Operational Suitability Data Certification Basis recorded in document D6-85798, or later recorded CRI A-FCD.
- b. Required for entry into service by EU operator.
- c. Pilot Type Rating: “B757/767”.

Note: These data cover the models B757-300 and -300 series and the B767-200, -300, -300F and -400ER series aircraft. Differences are addressed in D6-85798.

3. Cabin Crew Data

No CCD available (not required per COMMISSION REGULATION (EU) No 69/2014 of 27 January 2014).

VI. Notes

Refer to FAA TCDS A2NM for applicable notes



SECTION: ADMINISTRATIVE

I. Acronyms and Abbreviations

APU:	Auxiliary Power Unit
AWO:	All Weather Operation
CRI:	Certification Review Item
CS:	Certification Specification
EASA:	European Aviation Safety Agency
ESF:	Equivalent Safety Finding
FAA:	Federal Aviation Administration
ICAO:	International Civil Aviation Organization
JAR:	Joint Aviation Requirement
MMEL:	Master Minimum Equipment List
MEL:	Minimum Equipment List
NPA:	Notice of Proposed Amendment
INT/POL:	JAA Interim Policy
RVSM:	Reduced Vertical Separation Minima
SB:	Cessna Service Bulletin
SC:	Special Condition
S/N:	Serial Number
TCDS:	Type Certificate Data Sheet
TCDSN:	Type Certificate Data Sheet for Noise

II. Type Certificate Holder Record

The Boeing Company
P.O. Box 3707
Seattle, Washington 98124-2207
United States of America

III. Change Record

Issue	Date	Changes
Issue 01	23 January 2012	Initial Issue
Issue 02	30 April 2012	Addition of SC H-01 ICA on EWIS (Sections 1.II.5, 2.II.5, 3.II.5)
Issue 03	17 December 2015	Introduction of new Chapters 'V. Operational Suitability Data (OSD)' and renumbering of 'VI. Notes' to Sections I, II and III.

-END-

