
TYPE-CERTIFICATE DATA SHEET

UK.TC.P.00041

For Propeller

Type 5D3 series propellers

Type Certificate Holder

Hartzell Propeller Inc.

One Propeller Place

Piqua

OH 45356-2634

USA

Model(s): 5D3-N338A1
5D3-NK366()
5D31-NK366()
Issue: 01
Date of issue: 26 August 2022

TABLE OF CONTENTS

| | | |
|-----------|--|----|
| Section 1 | Type 5D3 | 5 |
| I. | General | 5 |
| 1. | Type / Variant or Model | 5 |
| 2. | Type Certificate Holder | 5 |
| 3. | Manufacturer | 5 |
| 4. | Date of Application | 5 |
| 5. | UK- CAA Certification Reference Date | 5 |
| 6. | CAA Type Certification Date | 5 |
| II. | Certification Basis | 5 |
| 1. | State of Design Authority Certification Basis | 5 |
| 2. | Reference Date for determining the applicable airworthiness requirements | 5 |
| 3. | UK CAA Certification Basis | 5 |
| III. | Technical Characteristic | 6 |
| 1. | Type Design Definition | 6 |
| 2. | Description | 6 |
| 3. | Equipment | 6 |
| 4. | Dimensions | 6 |
| 5. | Weight | 6 |
| 6. | Hub / Blade Combinations | 6 |
| 7. | Control System | 6 |
| 8. | Adaptation to Engine | 6 |
| 9. | Direction of Rotation | 6 |
| IV. | Operating Limitations | 7 |
| 1. | Approved Installations | 7 |
| 2. | Maximum Take Off Power and Speed | 7 |
| 3. | Maximum Continuous Power and Speed | 7 |
| 4. | Propeller Pitch Angle | 7 |
| V. | Operating and Service Instructions | 8 |
| VI. | Notes | 9 |
| 1. | Hub Model Designation | 9 |
| 2. | Blade Model Designation: | 10 |
| 3. | Pitch Control: (weight of pitch control extra) (See Notes 4 and 10) | 10 |
| 4. | Feathering: | 10 |
| | Reversing: | 10 |
| 5. | Left-Hand Models: (See Notes 1 and 2) | 10 |
| 6. | Interchangeability: | 11 |
| 7. | Accessories: | 11 |

| | | |
|-------------------------------|--|----|
| 8. | Shank Fairings: | 11 |
| 9. | Special Limits: | 11 |
| 10. | The suitability of a propeller for a certain aircraft/engine combination must be demonstrated within the scope of the type certification of the aircraft..... | 11 |
| 11. | Retirement Time:..... | 11 |
| 12. | Special Notes: | 11 |
| 13. | The approved Airworthiness Limitations Section of the Instructions for Continued Airworthiness is published in the applicable Propeller Owner's Manual, chapter 5 "Airworthiness Limitations"..... | 11 |
| Section 2 Administrative..... | | 12 |
| I. | Acronyms and Abbreviations | 12 |
| II. | Type Certificate Holder Record..... | 12 |
| | TCH Record | 12 |
| III. | Amendment Record | 12 |

TCDS No.: UK.TC.P.00041

Date: 26 August 2022

AW-DAW-TP-004

Copies of this document are not controlled.

Issue: 01

Page4 of 12

Section 1 Type 5D3

I. General

1. Type / Variant or Model

5D3-N338(), 5D3-NK366(), 5D31-NK366()

2. Type Certificate Holder

Hartzell Propeller Inc.

One Propeller Place

Piqua,

OH 45356-2634

USA

3. Manufacturer

Hartzell Propeller Inc.

4. Date of Application

5 May 2022

5. UK- CAA Certification Reference Date

24 November 2021

6. CAA Type Certification Date

18 August 2022

II. Certification Basis

1. State of Design Authority Certification Basis

Refer to FAA TCDS no. P00015CH.

2. Reference Date for determining the applicable airworthiness requirements

10 February 2015 for 5D3-N388A1

19 February 2019 for 5D3-NK366B1 and 5D31-NK366B1

20 February 2019 for 5D3-NK366A1.

3. UK CAA Certification Basis

1. Airworthiness Standards

5D3-N338A1, 5D3-NK366() and 5D31-NK366():

CS-P Amendment 1 dated 16 November 2006 as issued by EASA Decision No 2006/09/R, except the requirements of Subpart D as allowed by CS-P 10(b) (See Note 10a).

2. Special Conditions (SC)

None.

3. Equivalent Safety Findings (ESF)

None.

4. Deviations

None.

III. **Technical Characteristic**

1. **Type Design Definition**

The propeller type is defined by a propeller assembly drawing including a parts list (or later approved revisions).

5D3-N338A1: Drawing 106178, rev 0, dated 11 December 2015

5D3-NK366A1: Drawing 107479, rev A, dated 05 October 2019

5D3-NK366B1: Drawing 107701, dated 12 April 2021

5D31-NK366B1: Drawing 107447, rev. B, dated 7 May 2021.

2. **Description**

The 5D(3,31) models of this propeller type all have 5 blades and a hydraulically operated variable pitch control with constant speed.

The model incorporates reversing, feathering, and unfeathering features (See Notes 3 and 4).

The hub is milled out of aluminium alloy. The 5D(3,31)-() has a two-piece aluminium hub and a single acting hydraulic control system. The pitch change mechanism uses a slotted fork to move the pitch change knob and rotate the blade. The blade material is carbon composite.

The only difference is the 5D31 has a different beta ring designed for use with an electronic system and the cylinder is bigger.

Optional equipment includes spinner and ice protection.

3. **Equipment**

Spinner: See Note 7

Governor: See Note 3

Propeller deicing: See Note 7

4. **Dimensions**

Diameters from 243,8 cm to 194,3 cm. (See Table of Section IV)

5. **Weight**

Depending on Propeller-Design Configuration. (See Table of Section IV)

6. **Hub / Blade Combinations**

Details are mentioned within Table of Section IV.

7. **Control System**

Propeller governor. (See Note 3)

8. **Adaptation to Engine**

Special flange. (See Note 1)

9. **Direction of Rotation**

Direction of rotation (viewed in flight direction) as identified by a letter-code in the propeller designation.(See Note 5)

IV. Operating Limitations

| Blades (see Note 2) | Maximum Continuous | | Take Off | | Diameter Limits (cm) (see Note 2) | Approx. Max Wt. Complete (kg) (see Notes 3 and 7) | Blade Construction |
|------------------------------------|-----------------------|-----------------------------|----------|-----------------------------|---|---|-----------------------|
| | kW | RPM (min ⁻¹) | kW | RPM (min ⁻¹) | | | |
| <u>5D3-N338()</u> | | | | | | | |
| 78D01-0 to 78D01-6 | 633.8 | 2000 | 633.8 | 2000 | 209.6 to 194.3 (-0 to -6) | 59.87 | Carbon Composite |
| <u>5D3-NK366(), 5D31-NK366()</u> | | | | | | | |
| 86DB01-0 TO 86DB01-10 | 708.4 | 2000 | 708.4 | 2000 | 231.1 to 205.7 (-0 to -10) | 60.78 | Carbon Composite |
| <u>5D3-NK366()</u> | | | | | | | |
| 91D15-0 To 91D15-7 | 633.8 | 2000 | 633.8 | 2000 | 243.8 to 226.1 (-0 top -7) | 66.68 | Carbon Composite |

1. **Approved Installations**

The 5D3-N338A1 propeller is initially intended for use on a new version of the Piper Meridian aircraft.

The 5D3-NK366A1 propeller is initially intended for use on a King Air 250 aircraft modified by Raisbeck.

The 5D3-NK366B1 propeller has currently no specific intended customer. Hartzell chose to include the version of the propeller in case a customer will arise.

The 5D31-NK366B1 propeller is initially intended for use on Daher aircraft model TBM700N(Variant TBM 960).

(See Note 10)

2. **Maximum Take Off Power and Speed**

Details are mentioned within Table of Section IV.

3. **Maximum Continuous Power and Speed**

Details are mentioned within Table of Section IV.

4. **Propeller Pitch Angle**

The propeller has variable pitch capability. Pitch control is provided by a governor.

(See Note 3)

V. Operating and Service Instructions

Instruction for continued airworthiness (ICA):

| | |
|--|--------------------------|
| Propeller Owner's Manual and Logbook for Raptor Turbine Series (incl. Airworthiness Limitations, if any) | Hartzell Manual 486 (*) |
| Hartzell propeller Owner's Manual – Composite blades | Hartzell Manual 147 (*) |
| Five Blade Raptor Series Turbine Propeller Overhaul Manual | Hartzell Manual 496 (*) |
| Composite Blade Overhaul Manual | Hartzell Manual 135F (*) |
| Standard Practices manual | Hartzell Manual 202A (*) |
| Metal Spinner Maintenance Manual | Hartzell Manual 127 (*) |

(*): or later approved revision

Instruction for propeller installation and operation:


| | |
|------------------------------|-------------------------|
| Propeller Integration Manual | Hartzell Manual 190 (*) |
| Service Bulletins | |

(*): or later approved revision

VI. Notes


1. Hub Model Designation

(see Note 4 and 5)



2. Blade Model Designation:

(See Notes 5 and 6)



*: Diameter limits are nominal diameters of the assembled propeller. They do not include the + or – 0,32 cm (1/8 inch) manufacturing tolerance the FAA allows for propeller with a basic diameter of less than 426,7 cm (14 feet).

3. Pitch Control: (weight of pitch control extra) (See Notes 4 and 10)

- Maximum output pressure:
 - 5D3()-N()A models 3447.38 kPa (500 psig)
 - 5D3()-N()B models 4826.33 kPa (700 psig)
- All propeller models have counterweighted blades and use governor oil to decrease pitch.
- All governors and propeller control systems must be approved as part of the aircraft installation regardless of manufacturer.
- Hartzell propeller model 5D31-() is controlled by an integrated electronic system which is part of the engine type design. Propeller model 5D31-() complies with the propeller airworthiness requirements when used with the engine(s) listed in Hartzell Type Design Data (Manual 159).

Any change to the engine, including its control system, which affects or may affect the propeller approval must be substantiated to demonstrate that the propeller as integrated with the changed engine, including its control system, still complies with the propeller certification basis. Also, any change to the engine resulting from a change to the propeller must be substantiated to demonstrate that the changed engine still complies with the engine certification basis

4. Feathering:

- The 5D3 and 5D31 models incorporate feathering and unfeathering features.

Reversing:

- The 5D3 and 5D31 models are approved for installation as reversing propellers with appropriate reversing controls.

5. Left-Hand Models: (See Notes 1 and 2)

The left-hand version of an approved propeller model is approved at the same rating and diameter as listed for the right-hand model.

6. Interchangeability:

(a) Refer to Hartzell Service Letter HC-SL-30-260 for ice protection system component interchangeability.

7. Accessories:

(a) Propeller spinner. (weight of spinner extra)

(1) Approved with Hartzell and other manufacturers' spinners when listed on Hartzell type design data.

(2) All propeller spinners must be approved as part of the aircraft installation regardless of manufacturer. (See NOTE 10)

(b) Propeller deicing (weight of deicing equipment extra)

(1) Propeller models listed in this data sheet are approved for use with propeller ice protection equipment listed in Hartzell Manual 159() or in other Hartzell type design data.

(2) All propeller ice protection equipment must be approved as part of the aircraft installation regardless of manufacturer. (See NOTE 10)

8. Shank Fairings:

Not applicable.

9. Special Limits:

Not applicable.

10. The suitability of a propeller for a certain aircraft/engine combination must be demonstrated within the scope of the type certification of the aircraft.

Propeller models listed herein consist of basic hub and blade models. Most propeller models include additional characters to denote minor changes and specific features as explained in Notes 1 and 2.

10a. This propeller has been certificated in accordance with CS-P subparts A, B and C. Compliance with the requirements of Subpart D, which is specific to each aircraft installation, has not yet been demonstrated

11. Retirement Time:

(a) Life Limits and Mandatory Inspections

(1) Airworthiness limitations, if any, are specified in Hartzell Manual 486.

(2) The propeller CMACO (FAA) must evaluate the propeller installation for each new aircraft installation to assess possible changes in the airworthiness limitations.

12. Special Notes:

(a) Refer to Hartzell Manual no. 202() for overspeed and overtorque limits.

(b) Refer to Hartzell Service Letter HC-SL-61-61() for overhaul periods.

13. The approved Airworthiness Limitations Section of the Instructions for Continued Airworthiness is published in the applicable Propeller Owner's Manual, chapter 5 "Airworthiness Limitations".

End of Notes

Section 2 Administrative

I. Acronyms and Abbreviations

| Acronym / Abbreviation | Definition |
|-------------------------------|---------------------------------------|
| CAA | Civil Aviation Authority |
| EASA | European Union Aviation Safety Agency |
| TC | Type Certificate |
| TCDS | Type Certificate Data Sheet |
| TCH | Type Certificate Holder |

II. Type Certificate Holder Record

| TCH Record | Period |
|---|----------------------|
| Hartzell Propeller Inc. OH 45356-2634 One Propeller Place Piqua USA | Present. No changes. |

III. Amendment Record

| Issue | Date | Amendment-Change | TC issue |
|----------|----------------|---|----------------|
| Issue 01 | 18 August 2022 | Initial Issue: The content of the initial issue of this UK CAA TCDS was taken from EASA TCDS No. EASA.IM.P.136 Issue 02 dated 27 January 2020 which was the version of the TCDS for the Hartzell Propellor 5D3 Series, accepted by the UK under Article 15 of Annex 30 of the UK-EU Trade and Cooperation Agreement. Introduction of blade 86DB01 for propellor models- 5D3 and 5D31 as FAA TCDS P00015CH, Rev.7 for installation on aircraft, Daher TBM700N(TBM960 variant). | 18 August 2022 |
| | | | |
| | | | |
| | | | |