

---

## **TYPE-CERTIFICATE DATA SHEET**

**UK.TC.R.00065**

for

SA 330 / AS 332 / EC 225

**Type Certificate Holder**

Airbus Helicopters

Aéroport International Marseille – Provence

13725 Marignane CEDEX

France

Model(s): SA 330 J  
AS 332 C, AS 332 L, AS 332 C1, AS 332 L1, AS 332 L2  
EC 225 LP

Issue: 1

Date of issue: 14 May 2024

## TABLE OF CONTENTS

Type Certificate Holder .....	1
Section 1 : SA 330 J .....	3
i. General .....	3
ii. Certification Basis .....	3
iii. Technical Characteristic and Operating Limitations .....	4
iv. Operating and Service Instructions.....	7
v. Operational Suitability Data .....	7
vi. Notes.....	7
Section 2 : AS 332 C, C1, L, L1 .....	8
i. General .....	8
ii. Certification Basis .....	8
iii. Technical Characteristic and Operating Limitations .....	10
iv. Operating and Service Instructions.....	15
v. Operational Suitability Data .....	16
vi. Notes.....	16
Section 3 AS 332 L2 .....	19
i. General .....	19
ii. Certification Basis .....	19
iii. Technical Characteristic and Operating Limitations .....	20
iv. Operating and Service Instructions.....	23
v. Operational Suitability Data .....	24
vi. Notes.....	24
Section 4 EC 225 LP.....	25
i. General .....	25
ii. Certification Basis .....	25
iii. Technical Characteristic and Operating Limitations .....	27
iv. Operating and Service Instructions.....	31
v. Operational Suitability Data .....	31
vi. Notes.....	32
Section 5 : Administration .....	33
i. Acronyms and Abbreviations .....	33
ii. Type Certificate Holder Record .....	33
iii. Amendment Record .....	34

Note: In this TCDS, references to EU regulations are to those regulations as retained and amended in UK domestic law under the European Union (Withdrawal) Act 2018 and are referenced as “UK Regulation (EU) year/number or UK Regulation (EU) No. number/year”

**Section 1 : SA 330 J**

<b>i.</b>	<b>General</b>	
<b>1.</b>	<b>Type / Variant / Model</b>	
1.1	Type	SA 330
1.2	Model	SA 330 J (for memory of SA 330 F and SA 330 G, see Note 5)
1.3	Variant	-
<b>2.</b>	<b>Airworthiness Category</b>	Large Rotorcraft, Category A and B
<b>3.</b>	<b>Type Certificate Holder</b>	Airbus Helicopters Aéroport International Marseille – Provence 13725 Marignane CEDEX France See Section 5ii.
<b>4.</b>	<b>Manufacturer</b>	See Section 5ii.
<b>5.</b>	<b>Type Certification Application Date to DGAC FR</b>	Not recorded
<b>6.</b>	<b>State of Design Authority</b>	EASA (pre-EASA: DGAC FR, France)
<b>7.</b>	<b>Type Certification Date by DGAC FR</b>	29 April 1976
<b>8.</b>	<b>Type Certificate n° by DGAC FR</b>	56
<b>9.</b>	<b>Type Certificate Data Sheet n° by DGAC FR</b>	127 issue 9 dated September 1994
<b>10.</b>	<b>EASA Type Certification Date</b>	28 September 2003, in accordance with CR (EU) 1702/2003, Article 2, 3., (a), (i), 2nd bullet, 1st indented bullet.
<b>ii.</b>	<b>Certification Basis</b>	
<b>1.</b>	<b>Reference Date for determining the applicable requirements</b>	Not recorded
<b>2.</b>	<b>Airworthiness Requirements</b>	According to DGAC letter 02827 SFACT/TC, dated 30 March 1978:  FAR 29, Amdts. 29-1 to 29-9 inclusive and the addition of FAR 29.951 (c), 29.1183, 29.1305 (a)(16) of Amdt. 29-10 for SA 330 J equipped with white anti-collision light.
<b>3.</b>	<b>Special Conditions</b>	DGAC-F CS n°1 – Icing; DGAC-F CS n°2 – Lightning

<b>4.</b>	<b>Deviations</b>	For SA 330 J fitted with red anti-collision light FAR 29 Amdt. 29-7 is excluded.
<b>5.</b>	<b>Equivalent Safety Findings</b>	None
<b>6.</b>	<b>Environmental Protection Requirements</b>	
6.1	Noise Requirements	see TCDSN UK.TC.R.00065
6.2	Emissions Requirements	n/a
<b>7.</b>	<b>Operational Suitability Data (OSD)</b>	Not required for rotorcraft that are no longer in production. CR (EU) 748/2012, as amended by UK (EU) 69/2014 does not require OSD elements for this model (see Article 7a, 1.).
<b>iii.</b>	<b>Technical Characteristic and Operating Limitations</b>	
<b>1.</b>	<b>Type Design Definition</b>	SA 330 J definition is obtained by applying modifications mentioned in note 330A.05.0065 to the definition of former SA 330 G model, which consisted itself of SA 330 F previous model with design changes as listed in note 330A.05.0060 (see also Note 5).
<b>2.</b>	<b>Description</b>	Large twin-engine helicopter; SA 330 J model is a derivative design of former SA 330 G, which is originally derived from SA 330 F model (see also Note 5).
<b>3.</b>	<b>Equipment</b>	As per compliance with applicable FAR 29 airworthiness requirements and referenced in approved RFM.
<b>4.</b>	<b>Dimensions</b>	
4.1	Fuselage	Length: 14.82 m Width: 3.00 m Height: 5.14 m
4.2	Main Rotor	Diameter 15.09 m (4 blades)
4.3	Tail Rotor	Diameter: 3.04 m (5 blades)
<b>5.</b>	<b>Engine</b>	
5.1	Model	Safran Helicopter Engines (former: Turbomeca) 2 x Model TURMO IV C
5.2	Type Certificate	DGAC FR n°: M8 EASA TC/TCDS n°: EASA.E.074
5.3	Limitations	
5.3.1	Installed Engine Limitations	Refer to approved RFM
5.3.2	Transmission Torque Limits	Refer to approved RFM

- 6. Fluids**
- 6.1 Fuel Refer to approved RFM
- 6.2 Oil Refer to approved RFM
- 6.3 Additives Refer to approved RFM
- 7. Fluid capacities**
- 7.1 Fuel Fuel tank capacity: 1 565 litres (413 US gal)  
Usable fuel: 1 544 litres (408 US gal)
- 7.2 Oil Engines: 2 x 12 litres  
MGB: 22 litres  
IGB: 0.75 litre  
TGB: 1.4 litre
- 7.3 Coolant System Capacity n/a
- 8. Air Speed Limitations**  $V_{NE PWR ON}$ : 310 km/h (167 KIAS) at ISA sea level for 4 000kg.  
See RFM for other approved airspeed limits.
- 9. Rotor Speed Limitations**
- Power on:  
Nominal governed 265 rpm  $\pm$  7 rpm  
Minimum transient 220 rpm  
Power off:  
Maximum 310 rpm  
Minimum (< 108 KIAS) 220 rpm  
(> 108 KIAS) 240 rpm
- 10. Maximum Operating Altitude and Temperature**
- 10.1 Altitude TKOF/LDG: -1 650 ft to +13 000 ft PA  
Enroute: +16 500 ft PA
- 10.2 Temperature - 40°C to + 50°C
- 11. Operating Limitations** VFR day and night, IFR, Non-icing conditions
- 12. Maximum Mass** TKOF/LDG: 7 400 kg (16 314 lb)
- 13. Centre of Gravity Range** Refer to approved RFM
- 14. Datum** Longitudinal:  
STA 0: 4.700 m (185.04 in) forward of main rotor centreline  
Lateral: aircraft symmetry plane
- 15. Levelling Means** Levelling plate on right side of the fuselage and graduated plate for plumb line on cabin floor (left side door)

<b>16. Minimum Flight Crew</b>	VFR: 1 pilot in Category B 1 pilot + 1 crew member in Category A IFR: 2 pilots in Categories A and B
<b>17. Maximum Passenger Seating Capacity</b>	19
<b>18. Passenger Emergency Exit</b>	Refer to approved RFM
<b>19. Maximum Baggage/ Cargo Loads</b>	The cabin floor (from +2.48 m to +7.63 m) is provided with the structural strength required for a load of 800 kg/m <sup>2</sup> evenly distributed in cargo configuration
<b>20. Rotor Blade Control Movement</b>	For rigging information refer to AMM
<b>21. Auxiliary Power Unit (APU)</b>	n/a
<b>22. Life-limited Parts</b>	Refer to approved Airworthiness Limitations Section
<b>23. Wheels and Tyres</b>	Wheels: NLG Messier Bugatti C20525000 (two) MLG Messier Bugatti C20525000 (two each side) Tyres: NLG 7.00-6 (two) MLG 7.00-6 (two each side)

- iv. Operating and Service Instructions**
1. **Flight Manual**

SA 330 J Flight Manual approved on 29 April 1976 by DGAC FR(\*), or subsequent approved revisions.

(\* there are other Flight Manuals, which resulted from various European type certifications, e.g. Flight Manual with identification code E (CAA UK).
  2. **Maintenance Manual**

SA 330 Maintenance Manual including:

    - Maintenance programme as Maintenance Servicing Recommendations (PRE);
    - Airworthiness Limitations Section as PRE Chapter 05.99, approved by DGAC FR or EASA;

SA 330 FREM (Transmission assembly overhaul booklets).
  3. **Structural Repair Manual**

SA 330 Structural Repair Manual.
  4. **Weight and Balance Manual**

Refer to approved RFM.
  5. **Illustrated Parts Catalogue**

Not recorded
  6. **Service Letters and Service Bulletins**

As published by Aérospatiale, Eurocopter or Airbus Helicopters
  7. **Required Equipment**
    - As per compliance with applicable FAR 29 requirements and in accordance with the original Type Design standard, refer also to the approved RFM;
    - Approved equipment items are covered by document No 330A.04.1155 dated 17 September 1970 updated to issue J on 26 March 1981;
    - Approved equipment items required for the flight in icing conditions are covered by document 330A.04.1483
- v. Operational Suitability Data** See Section 1, ii., Item 7.
- vi. Notes**
1. Manufacturer's serial numbers:
 

S/N 1371, and subsequent of model SA 330 J are eligible.
  2. The certified "optional" installations are each approved independently of the basic helicopter and an approved Flight Manual Supplement is associated to each optional installation if necessary.
  3. Cabin Interior and Seating Configurations must be approved.
  4. Commercial designation: PUMA
  5. Upon Eurocopter request for its surrender, the Type Certificate of both models SA 330 G and SA 330 F has been revoked by EASA as of 12 November 2009 (see EASA Certification Information No. 2009-17, dated 16 November 2009).

**Section 2 : AS 332 C, C1, L, L1****i. General****1. Type / Variant / Model**

- |     |         |  |
|-----|---------|--|
| 1.1 | Type    | AS 332                                   |
| 1.2 | Model   | AS 332 C, AS 332 C1, AS 332 L, AS 332 L1 |
| 1.3 | Variant | -  |

**2. Airworthiness Category**

Large Rotorcraft, Category A and B

**3. Type Certificate Holder**

Airbus Helicopters  
 Aéroport International Marseille – Provence  
 13725 Marignane CEDEX  
 France  
 See Section 5ii.

**4. Manufacturer**

See Section 5ii.

**5. Type Certification Application Date to DGAC FR**

AS 332 C: 4 April 1978  
 AS 332 L: 16 July 1980  
 AS 332 C1 and L1: 18 June 1984

**6. State of Design Authority**

EASA (pre-EASA: DGAC FR, France)

**7. Type Certification Date by DGAC FR**

AS 332 C: 24 April 1981  
 AS 332 L: 2 December 1981  
 AS 332 C1 and L1: 14 March 1985

**8. Type Certificate n° by DGAC FR**

56

**9. Type Certificate Data Sheet n° by DGAC FR**

127 issue 9 dated September 1994

**10. EASA Type Certification Date**

28 September 2003, in accordance with CR (EU) 1702/2003, Article 2, 3., (a), (i), 2nd bullet, 1st indented bullet.

**ii. Certification Basis****1. Reference Date for determining the applicable requirements**

For Airworthiness and Environmental Protection:  
 not recorded  
 for OSD elements:  
 17 February 2014 (grandfathering date)

**2. Airworthiness Requirements**

For AS 332 C, C1, L, L1 (\*):

FAR 29 with Amdts. 29-1 to 29-16 including. (\*) according to DGAC letter 53.904, dated 18 August 1980 and document 'Airworthiness Criteria for Helicopter Instrument Flight', dated 15 December 1978 for IFR flight. For AS 332 C1 and L1 equipped with AHCAS (commercial reference AS 332 C1e and AS 332 L1e):

according to CRI A-01, see Note 8.

For AS 332 C, C1, L, L1 equipped with a Full Flow Magnetic Plug (FFMP) (MOD 07.53061):

FAR 29.1309(b)(2) Amdt. 24 and FAR 29.1309(d) Amdt. 24 are applicable (see CRI A-01) for the areas affected by the design change.

For AS 332 C1 and L1 equipped with AHCAS (commercial reference AS 322 C1e and AS 332 L1e):

see Note 8

**3. Special Conditions**

For AS 332 C, C1, L, L1 (\*):

- DGAC-F CS n°1 (Icing) and DGAC-F CS n°2 (Lightning) as applicable to previous SA 330 J model and notified by DGAC-F letter 02827 SFACT/TC, dated 30 March 1978.

- DGAC-F CS n°20.2, dated 11 May 1982 for category II, IFR flight.

For AS 332 C1 and L1 equipped with AHCAS (commercial reference AS 332 C1e and AS 332 L1e) see Note 8:

- Minimum in-flight experience (B-01).

- Search and Rescue system (B-02).

- Protection from the effects of High Intensity Radiated Fields (HIRF) (F-02).

For AS 332 C1 and L1: Non-rechargeable Lithium Battery Installations (F-09).

**4. Deviations**

None

**5. Equivalent Safety Findings**

For AS 332 C, C1, L, L1 (\*):

- Endurance Tests of redesigned Tail Rotor Hub pitch change control assembly (MOD 07.66205) (E-01).

For AS 332 C1 and L1 equipped with AHCAS (commercial reference AS 332 C1e and AS 332 L1e), see Note 8:

- IFR Static Longitudinal Stability – Airspeed Stability (B-04).

- V<sub>NE</sub> aural warning (F-01).

- Airspeed indicator markings (G-01).

- Powerplant instrument markings (G-02).

**6. Environmental Protection Requirements**

6.1 Noise Requirements see TCDSN UK.TC.R.00065

6.2 Emissions Requirements n/a

**7. Operational Suitability Data (OSD)**

7.1 Master Minimum Equipment List (MMEL) JAR-MMEL/MEL Section 1, Subpart A and B, Amdt. 1, dated 1 August 2005

7.2 Flight Crew Data (FCD) CS-FCD Initial Issue, dated 31 January 2014 (elect to comply as per EASA approval 10060827)

7.3 Simulation Data (SIMD) Reserved

7.4 Maintenance Certifying Staff Data (MCSD) Reserved

7.5 Cabin Crew Data (CCD) Reserved

**iii. Technical Characteristic and Operating Limitations****1. Type Design Definition**

For AS 332 C:

as per document 332A04.0009 and modifications list in doc. 332A04.3269 for 8 350 kg

For AS 332 L:

as per doc. 332A04.0010 for 8 350 kg

For AS 332 C, L:

as per doc. 332A04.3300 for 8 600 kg

For AS 332 C1, L1:

as per doc. 332A04.3305 for 8 600 kg

For AS 332 C1 and L1 equipped with AHCAS (commercial reference AS 332 C1e and AS 332 L1e): see Note 8

**2. Description**

Large twin-engine helicopter; derivative design of former type certified SA 330 models, featuring:

- two fuselage length configurations (standard for AS 332 C, C1; extended for AS 332 L, L1),

- two engines configurations (MAKILA 1A for AS 332 C, L; MAKILA 1A1 for AS 332 C1, L1)

**3. Equipment**

As per compliance with applicable FAR 29 airworthiness requirements and referenced in approved RFM.

**4. Dimensions**

4.1	Fuselage	for AS 332 C, C1: Length: 15.53 m Width stabiliser: 3.79 m Height: 4.94 m for AS 332 L, L1: Length: 16.29 m Width stabiliser: 3.79 m Height: 4.95 m
4.2	Main Rotor	Diameter 15.60 m (4 blades)
4.3	Tail Rotor	Diameter: 3.05 m (5 blades)

**5. Engine**

5.1	Model	Safran Helicopter Engines (former: Turbomeca) for AS 332 C, L: 2 x Model MAKILA 1A for AS 332 C1, L1: 2 x Model MAKILA 1A1
5.2	Type Certificate	EASA TC/TCDS n°: EASA.E.072
5.3	Limitations	
5.3.1	Installed Engine Limitations	Refer to approved RFM
5.3.2	Transmission Torque Limits	Refer to approved RFM

**6. Fluids**

6.1	Fuel	Refer to approved RFM
6.2	Oil	Refer to approved RFM
6.3	Additives	Refer to approved RFM

**7. Fluid capacities****7.1 Fuel**

For AS 332 C, C1:

Standard configuration: 1 556 litres (411 US gal)  
 with optional internal 6th tank 324 litres (86 US gal)  
 with optional sponson tanks 650 litres (172 US gal)  
 Total available fuel: 2 530 litres (669 US gal)

For AS 332 L, L1:

Standard configuration: 2 043 litres (540 US gal)  
 with optional internal 7th tank 324 litres (86 US gal)  
 with optional sponson tanks 650 litres (172 US gal)  
 Total available fuel: 3 017 litres (798 US gal)

Note to all models: see RFM for other approved optional fuel tanks configurations and for unusable fuel quantities.

**7.2 Oil**

Engines: 2 x 7.6 litres  
 MGB: 19.6 litres  
 IGB: 0.62 litre  
 TGB: 1.44 litre

**7.3 Coolant System Capacity**

n/a

**8. Air Speed Limitations**

At ISA sea level for mass  $\leq$  8 350 kg (18 409 lb):

$V_{NE\ PWR\ ON}$ : 310 km/h (167 KIAS)

$V_{NE\ PWR\ OFF}$ : 278 km/h (150 KIAS)

At ISA sea level for mass  $>$  8 350 kg (18 409 lb):

$V_{NE\ PWR\ ON}$ : 278 km/h (150 KIAS)

$V_{NE\ PWR\ OFF}$ : 268 km/h (145 KIAS)

**9. Rotor Speed Limitations**

Power on:

Maximum 275 rpm

Nominal 265 rpm

Minimum 245 rpm

Minimum transient 220 rpm

Power off:

Maximum transient (20 sec) 310 rpm

Maximum 290 rpm

Minimum ( $>$  100 KIAS) 245 rpm

Minimum ( $<$  100 KIAS) 220 rpm

**10. Maximum Operating Altitude and Temperature**

- 10.1 Altitude
- For AS 332 C, L:  
 TKOF/LDG: 15 000 ft PA for mass  $\leq$  8 350 kg (18 409 lb)  
                   6 000 ft PA for mass  $>$  8 350 kg (18 409 lb)  
 Enroute: 20 000 ft PA
- For AS 332 C1, L1:  
 TKOF/LDG: -1 640 ft PA / +15 000 ft DA  
 Enroute: -1 640 ft/+25 000 ft PA  
                   for mass  $\leq$  8 350 kg (18 409 lb)  
                   -1 640 ft/+9 500 ft PA  
                   for mass  $>$  8 350 kg (18 409 lb)
- 10.2 Temperature
- 30°C to ISA +35°C, limited to 50°C.  
 See relevant RFMS for colder operation down to -45°C.

**11. Operating Limitations**

VFR day and night, IFR, Non-icing conditions

Flight in full icing conditions is permitted on AS 332 C, L and L1 models only when equipment items listed in relevant flight manual supplement are installed.

Flight in limited icing conditions is permitted on AS 332 L and L1 models only when equipment items listed in relevant approved RFMS are installed (see Note 6).

**12. Maximum Mass**

TKOF/LDG for AS 332 C, L:  
 8 350 kg (18 409 lb), prior SB 01.03 embodiment  
 8 600 kg (18 960 lb), after SB 01.03 embodiment

TKOF/LDG for AS 332 C1, L1:  
 8 600 kg (18 960 lb)

**13. Centre of Gravity Range**

Refer to approved RFM

**14. Datum**

Longitudinal:  
 STA 0: 4.670 m (183.86 in) forward of main rotor centreline

Lateral: aircraft symmetry plane

**15. Levelling Means**

Levelling plate on right side of the fuselage and graduated plate for plumb line on cabin floor (left side door)

- 16. Minimum Flight Crew**
- For AS 332 C, L:  
VFR: 1 pilot + 1 qualified crew member (\*)  
IFR: 2 pilots
- For AS 332 C1, L1:  
VFR: < 20 000 ft, 1 pilot + 1 qualified crew member (\*)  
> 20 000 ft, 2 pilots  
IFR: 2 pilots
- (\*) the qualified crew member is not required if, at least, one lane of each AP channel is in operation.
- AS 332 C1 and L1 equipped with AHCAS (commercial reference AS 332 C1e and AS 332 L1e):  
VFR: 1 pilot  
IFR: 2 pilots
- 17. Maximum Passenger Seating Capacity** For AS 332 C, C1: 19  
For AS 332 L, L1: 24
- 18. Passenger Emergency Exit** Refer to approved RFM
- 19. Maximum Baggage/ Cargo Loads** The cabin floor (from +2.48 m to +7.63 m) is provided with the structural strength required for a load of 800 kg/m<sup>2</sup> evenly distributed in cargo configuration
- 20. Rotor Blade Control Movement** For rigging information refer to AMM
- 21. Auxiliary Power Unit (APU)** n/a
- 22. Life-limited Parts** Refer to approved Airworthiness Limitations Section
- 23. Wheels and Tyres**
- Wheels:  
NLG Messier Bugatti C20525000 (two)  
MLG Messier Bugatti C20147200 (one each side)
- Tyres:  
NLG 7.00-6 (two)  
MLG 615 x 225-10 (one each side)

**iv. Operating and Service Instructions**

- |   |  |
|---|--|
| <b>1. Flight Manual</b>                         | <p>AS 332 C:<br/>Flight Manual approved on 24 April 1981 by DGAC-F (*), or subsequent approved revisions.</p> <p>AS 332 L:<br/>Flight Manual approved on 2 December 1981 by DGAC-F (*), or subsequent approved revisions.</p> <p>AS 332 C1:<br/>Flight Manual approved on 14 March 1985 by DGAC-F (*), or subsequent approved revisions.</p> <p>AS 332 L1:<br/>Flight Manual approved on 14 March 1985 by DGAC-F (*), or subsequent approved revisions.</p> <p>AS 332 L1 equipped with AHCAS (commercial reference AS 332 L1e):<br/>Flight Manual approved on 14 June 2012 by EASA or subsequent.</p> <p>AS 332 C1 equipped with AHCAS (commercial reference AS 332 C1e):<br/>Flight Manual approved on 13 November 2013 by EASA or subsequent.</p> <p>(*), there are other RFM, which resulted from various European type certifications, e.g., RFM with identification code E (CAA UK), code D (LBA) or code F (ENAC).</p> |
| <b>2. Maintenance Manual</b>                    | <p>Maintenance Programme:</p> <ul style="list-style-type: none"> <li>- AS 332 C, C1, L, L1 Maintenance Servicing Recommendations (PRE),</li> <li>- AS 332 C, C1, L, L1 Aircraft Maintenance Manual (AMM)</li> <li>- AS 332 C, C1, L, L1 Overhaul Manual.</li> </ul> <p>Airworthiness Limitations:<br/>AS 332 C, C1, L, L1 Maintenance Servicing Recommendations, Chapter 05.99 (or newly Chapter 04 approved by EASA), edition 2003.01.03, Rev.000, DGAC-F approved on 6 May 2003, or subsequent approved revisions.</p>   |
| <b>3. Structural repair Manual</b>              | AS 332 C, C1, L, L1 Repair Manual  |
| <b>4. Weight and Balance Manual</b>             | Refer to approved RFM.   |
| <b>5. Illustrated Parts Catalogue</b>           | AS 332 C, C1, L, L1 Illustrated Part Catalogue   |
| <b>6. Service Letters and Service Bulletins</b> | As published by Aérospatiale, Eurocopter or Airbus Helicopters   |

**7. Required Equipment**

- As per compliance with applicable FAR 29 requirements and in accordance with the original Type Design standard
- Approved equipment items are covered by document No 332A.04.3254, dated 14 May 1981
- Refer to approved Flight Manual, MMEL and also to Note 7 below.

**v. Operational Suitability Data**

1.1	Master Minimum Equipment List (MMEL)	<p>For AS 332 C, L, C1, L1:</p> <p>MMEL AS 332 C-C1-L-L1 Normal Revision 3, Issue 2, Date Code 13-04, dated 13 June 2013, or later approved revisions.</p> <p>For AS 332 C1, L1 equipped with AHCAS (commercial reference AS 332 C1e and AS 332 L1e):</p> <p>MMEL Supplement AS 332 C1-L1</p> <p>Post MOD 07 26640 to 07 22650</p> <p>Normal Revision 0 Issue 1 Date-Code 14-02, dated 27 January 2014, or later approved revisions.</p>
1.2	Flight Crew Data (FCD)	OSD-FCD Super Puma Fleet RN 2 Date Code 16-50, or later approved revision.
1.3	Simulation Data (SIMD)	Reserved
1.4	Maintenance Certifying Staff Data (MCSD)	Reserved
1.5	Cabin Crew Data (CCD)	Reserved

**vi. Notes**

## 1. Manufacturer's serial numbers:

- AS 332 C: s/n 2001, and subsequent;
  - AS 332 C1: see Note 2 for eligible serial numbers;
  - AS 332 L: s/n 2004; and subsequent;
  - AS 332 L1: s/n 2132, and subsequent;
- are eligible.

## 2. Conversion from AS 332 C, L models to AS 332 C1, L1 models possible through SB 01.00.26.

## 3. The certified 'optional' installations are each approved independently of the basic helicopter and an approved Flight Manual Supplement is associated to each optional installation, if necessary.

## 4. Cabin Interior and Seating Configurations must be approved.

## 5. Commercial designation 'SUPER PUMA Mk I' corresponds to AS 332 C, C1, L and L1 models. Commercial references AS 332 C1e and AS 332 L1e are used for AS 332 C1 and AS 332 L1 equipped with AHCAS system and modifications listed below in Note 8.

Since 1 Jan 2016, H215 is the new commercial designation for AS 332 C1e and AS 332 L1e, the two versions being respectively differentiated as H215 short version / H215 long version.

## 6. Flight in "icing conditions of limited severity":

- permitted on AS 332 L and L1 models only, with relevant Flight Manual Supplement, formerly approved under code E (CAA-UK) at normal revision RNO, or subsequent DGAC-F or EASA approved issues.

- such code E (CAA-UK) Flight Manual Supplement does not constitute operational approval and operations must be conducted in accordance with applicable operational regulation.
- 7. AS 332 C, L and L1 helicopters without MGB fire detection system are those modified by AMS 07-21653, design change resulting from CAA-UK's original type certification.
- 8. For AS 332 C1, L1 aircraft with the following Eurocopter modifications installed (commercial reference AS 332 C1e, AS 332 L1e), the design change was classified as 'significant' per 21.A.101 and the certification basis is listed below:
  - MOD 07.26640 - Hydraulic and flight control adaptation for AFCS integration;
  - MOD 07.26641 - VMS installation;
  - MOD 07.26642 - AFCS installation;
  - MOD 07.26643 - FDS installation;
  - MOD 07.26644 - Primary references installation;
  - MOD 07.26645 - Cockpit adaptation for AHCAS installation;
  - MOD 07.26646 - Cockpit lighting;
  - MOD 07.26647 - Electrical wiring and connections adaptation;
  - MOD 07.26648 - Electrical power distribution modification;
  - MOD 07.26649 - Warnings/Cautions and ancillaries adaptation;
  - MOD 07.26650 - Equipment installation structure adaptation.

#### Affected Area

The affected area (primary design change) is aircraft avionics referring to the integration of the avionic systems on cockpit instrument panel: AFCS, VMS, MFD, ISIS, ADU and AHRS.

Installation of the avionic equipment includes the display of the information (vehicle parameters, engine parameters and piloting parameters, AFCS modes and upper modes as an option) through:

- MFD on instrument panel (part of the FDS integration);
- EID on instrument panel (part of the VMS integration);
- ISIS on instrument panel (part of the sensors integration).

For this affected area, CS-29 Amdt. 2, dated 17 November 2008, is applicable and the requirements impacted by are listed below (see reference A-01):

- CS 29.0771 Pilot compartment
- CS 29.0773 Pilot compartment view
- CS 29.0777 Cockpit controls
- CS 29.1301 Function and installation
- CS 29.1303 Flight and navigation instruments
- CS 29.1305 Power plant instruments
- CS 29.1309 Equipment, systems, and installations
- CS 29.1321 Arrangement and visibility
- CS 29.1327 Magnetic direction indicator
- CS 29.1329 Automatic pilot system
- CS 29.1333 Instrument systems
- CS 29.1335 Flight director systems
- CS 29.1543 Instrument markings: general
- CS 29.1545 Airspeed indicator
- CS 29.1547 Magnetic direction indicator
- CS 29.1549 Power plant instruments

#### Appendix B Airworthiness Criteria For Helicopter Instrument Flight

## Special Condition:

- Minimum in flight experience (B-01).
- Search and Rescue system (B-02).
- Protection from the effects of High Intensity Radiated Fields (HIRF) (F-02).

## Equivalent Safety Finding:

- IFR Static Longitudinal Stability – Airspeed Stability (B-04).
- VNE aural warning (F-01).
- Airspeed indicator markings (G-01).
- Powerplant instrument markings (G-02).

## Secondary Change

To integrate these systems on Super Puma MK1 AS 332 C1, L1, some secondary changes have to be applied:

- Electrical integration of the avionic systems,
- Mechanical integration of the avionic systems,
- Adaptation of hydraulic and flight controls systems,
- AFCS modifications,
- Cockpit lighting modifications,
- Other structural modifications of the airframe,
- Warnings and cautions modifications.

For these secondary changes, the certification basis to be applied is the existing certification basis for the AS 332 C1, L1.

Nevertheless, Eurocopter elected to comply with the requirements of affected area, completed by the ones of CS-29 Amdt. 2 listed below.

## Requirements elected to comply:

- CS 29.0161 Trim control
- CS 29.0671 General
- CS 29.0672 Stability augmentation, automatic, and power-operated systems
- CS 29.1322 Warning, caution, and advisory lights
- CS 29.1381 Instrument lights
- CS 29.1523 Minimum flight crew
- CS 29.1525 Kinds of operation

## Unaffected Area

The existing certification basis (FAR 29 Amdt. 16 and DGAC special conditions) as listed in TCDS EASA.R.002, is applicable, except for helicopters equipped with a Full Flow Magnetic Plug (FFMP) (MOD 07.53061) where FAR 29.1309(b)(2) Amdt. 24 and FAR 29.1309(d) Amdt. 24 are applicable (A-01) for the areas affected by the design change.

**Section 3 AS 332 L2**

<b>i. General</b>	
<b>1. Type / Variant / Model</b>	
1.1	Type AS 332
1.2	Model AS 332 L2
1.3	Variant -
<b>2. Airworthiness Category</b>	Large Rotorcraft, Category A and B
<b>3. Type Certificate Holder</b>	Airbus Helicopters Aéroport International Marseille – Provence 13725 Marignane CEDEX France See Section 5ii.
<b>4. Manufacturer</b>	See Section 5ii.
<b>5. Type Certification Application Date to DGAC FR</b>	3 March 1986
<b>6. State of Design Authority</b>	EASA (pre-EASA: DGAC FR, France)
<b>7. Type Certification Date by DGAC FR</b>	12 June 1991
<b>8. Type Certificate n° by DGAC FR</b>	56
<b>9. Type Certificate Data Sheet n° by DGAC FR</b>	127 issue 9 dated September 1994
<b>10. EASA Type Certification Date</b>	28 September 2003, in accordance with CR (EU) 1702/2003, Article 2, 3., (a), (i), 2nd bullet, 1st indented bullet.
<b>ii. Certification Basis</b>	
<b>1. Reference Date for determining the applicable requirements</b>	For Airworthiness and Environmental Protection: 3 March 1986 for OSD elements: 17 February 2014 (grandfathering date)
<b>2. Airworthiness Requirements</b>	FAR 29 with Amdts. 29-1 to 29-24 inclusive According to DGAC letters 53445/SFACT/TC, dated 27 April 1989, and 53610/SFACT/N.HE, dated June 1991

<b>3. Special Conditions</b>	<ul style="list-style-type: none"> <li>- Flight Endurance</li> <li>- Bird and Foreign Object strikes</li> <li>- Protection against external electro-magnetic disturbances</li> <li>- 30 Sec and 2 Min contingency ratings</li> <li>- Maintenance assistance system (not applicable to basic type design definition)</li> </ul>
<b>4. Deviations</b>	<ul style="list-style-type: none"> <li>- reversion to FAR 29 original requirements for 29.1, 29.605, 29.671 and 29.1323</li> <li>- reversion to FAR 29 Amdt. 12 for 29.603</li> <li>- reversion to FAR 29 Amdt. 14 for 29.1303</li> <li>- reversion to FAR 29 Amdt. 14 for 29.1309 regarding equipment used on previous AS 332 version</li> </ul>
<b>5. Equivalent Safety Findings</b>	None
<b>6. Environmental Protection Requirements</b>	
6.1 Noise Requirements	see TCDSN UK.TC.R.00065
6.2 Emissions Requirements	n/a
<b>7. Operational Suitability Data (OSD)</b>	
7.1 Master Minimum Equipment List (MMEL)	JAR-MMEL/MEL Section 1, Subpart A and B, Amdt. 1, dated 1 August 2005
7.2 Flight Crew Data (FCD)	CS-FCD Initial Issue, dated 31 January 2014 (elect to comply as per EASA approval 10060827)
7.3 Simulation Data (SIMD)	Reserved
7.4 Maintenance Certifying Staff Data (MCSD)	Reserved
7.5 Cabin Crew Data (CCD)	Reserved
<b>iii. Technical Characteristic and Operating Limitations</b>	
<b>1. Type Design Definition</b>	Documents ref. 332 A 89 1031 and 332 A 89 1046.
<b>2. Description</b>	Large twin-engine helicopter; derivative design of former type certified AS 332 models.
<b>3. Equipment</b>	As per compliance with applicable FAR 29 airworthiness requirements and referenced in approved RFM.

**4. Dimensions**

4.1	Fuselage	Length:	16.49 m
		Width stabiliser:	3.38 m
		Height:	4.97 m
4.2	Main Rotor	Diameter:	16.20 m (4 blades)
4.3	Tail Rotor	Diameter:	3.15 m (4 blades)

**5. Engine**

5.1	Model	Safran Helicopter Engines (former: Turbomeca) 2 x Model MAKILA 1A2	
5.2	Type Certificate	EASA TC/TCDS n°:	EASA.E.072
5.3	Limitations		
5.3.1	Installed Engine Limitations	Refer to approved RFM	
5.3.2	Transmission Torque Limits	Refer to approved RFM	

**6. Fluids**

6.1	Fuel	Refer to approved RFM
6.2	Oil	Refer to approved RFM
6.3	Additives	Refer to approved RFM

**7. Fluid capacities**

7.1	Fuel	Standard configuration: 2 043 litres (540 US gal) with optional internal 6th tank 324 litres (86 US gal) with optional sponson tanks 600 litres (158 US gal) Total available fuel: 2 967 litres (784 US gal) Note: see RFM for other approved optional fuel tanks configurations and for unusable fuel quantities.
7.2	Oil	Engines: 2 x 4.9 litres MGB: 24.0 litres IGB: 0.75 litre TGB: 1.50 litre
7.3	Coolant System Capacity	n/a

**8. Air Speed Limitations**

$V_{NE\ PWR\ ON}$ :	315 km/h (170 KIAS)
$V_{NE\ PWR\ OFF}$ :	278 km/h (150 KIAS)
Refer to RFM for other approved airspeed limits.	

<b>9.</b>	<b>Rotor Speed Limitations</b>	Power on: Maximum 275 rpm Nominal 265 rpm Minimum 245 rpm Minimum transient 220 rpm Power off: Maximum transient (20 sec) 310 rpm Maximum 290 rpm Minimum (> 100 KIAS) 245 rpm Minimum (< 100 KIAS) 220 rpm
<b>10.</b>	<b>Maximum Operating Altitude and Temperature</b>	
10.1	Altitude	TKOF/LDG: -2 000 ft to +7 200 ft PA Enroute: -2 000 ft to +20 000 ft PA
10.2	Temperature	-30°C to ISA +35°C, limited to 50°C
<b>11.</b>	<b>Operating Limitations</b>	VFR day and night, IFR, Non-icing conditions Flight in limited icing conditions is permitted when equipment items listed in relevant approved Flight Manual supplements are installed (see Note 5)
<b>12.</b>	<b>Maximum Mass</b>	TKOF/LDG: 9 300 kg (20 503 lb)
<b>13.</b>	<b>Centre of Gravity Range</b>	Refer to approved RFM
<b>14.</b>	<b>Datum</b>	Longitudinal: STA 0: 4.670 m (183.86 in) forward of main rotor centreline Lateral: aircraft symmetry plane
<b>15.</b>	<b>Levelling Means</b>	Levelling plate on right side of the fuselage and graduated plate for plumb line on cabin floor (left side door)
<b>16.</b>	<b>Minimum Flight Crew</b>	VFR: 1 pilot IFR: 2 pilots
<b>17.</b>	<b>Maximum Passenger Seating Capacity</b>	25
<b>18.</b>	<b>Passenger Emergency Exit</b>	Refer to approved RFM
<b>19.</b>	<b>Maximum Baggage/ Cargo Loads</b>	The cabin floor (from +2.48 m to +7.63 m) is provided with the structural strength required for a load of 800 kg/m <sup>2</sup> evenly distributed in cargo configuration
<b>20.</b>	<b>Rotor Blade Control Movement</b>	For rigging information refer to AMM

21. **Auxiliary Power Unit (APU)** Optional; to be used on ground only.  
Refer to approved RFMS.
22. **Life-limited Parts** Refer to approved Airworthiness Limitations Section
23. **Wheels and Tyres**  
Wheels:  
NLG Messier Bugatti C20525000 (two)  
MLG Messier Bugatti C20147200 (one each side)  
Tyres:  
NLG 7.00-6 (two)  
MLG 615 x 225-10 (one each side)
- iv. Operating and Service Instructions**
1. **Flight Manual** AS 332 L2 Flight Manual, DGAC-F (\*) approved on 2 April 1992, or subsequent approved revisions.  
(\* ) there are other RFM, which resulted from various European type certifications, e.g., RFM with identification code E (CAA UK), code D (LBA) or code F (ENAC).
2. **Maintenance Manual** Maintenance Programme:  
- AS 332 L2 Maintenance Servicing Recommendations (PRE),  
- AS 332 L2 Aircraft Maintenance Manual (AMM)  
- AS 332 L2 Overhaul Manual  
Airworthiness Limitations:  
AS 332 L2 Maintenance Servicing Recommendations, Chapter 05.99 (or newly Chapter 04 approved by EASA), edition 2003.04.24, Rev.000, DGAC-F approved on 25 June 2003, or subsequent approved revisions
3. **Structural repair Manual** AS 332 L2 Structural Repair Manual.
4. **Weight and Balance Manual** Refer to approved RFM.
5. **Illustrated Parts Catalogue** AS 332 L2 Illustrated Part Catalogue
6. **Service Letters and Service Bulletins** As published by Aérospatiale, Eurocopter or Airbus Helicopters
7. **Required Equipment**  
- As per compliance with applicable FAR 29 requirements and in accordance with the original Type Design standard;  
- Refer to approved Flight Manual, MMEL and also to Note 6 below.

**v. Operational Suitability Data**

1.1	Master Minimum Equipment List (MMEL)	MMEL AS 332 L2 Normal Revision 1, Issue 2, Date Code 10-10, dated 20 October 2010, or later approved revisions.
1.2	Flight Crew Data (FCD)	OSD-FCD Super Puma Fleet RN 2 Date Code 16-50, or later approved revision.
1.3	Simulation Data (SIMD)	Reserved
1.4	Maintenance Certifying Staff Data (MCSD)	Reserved
1.5	Cabin Crew Data (CCD)	Reserved

**vi. Notes**

1. Manufacturer's serial numbers:

S/N 2338, and subsequent of AS 332 L2 model are eligible.

2. The certified "optional" installations are each approved independently of the basic helicopter and an approved Flight Manual Supplement is associated to each optional installation if necessary.

3. Cabin Interior and Seating Configurations must be approved.

4. Commercial designation 'SUPER PUMA Mk II' corresponds to AS 332 L2 version.

5. Flight in 'icing conditions of limited severity':

- permitted with relevant Flight Manual Supplement, formerly approved under code E (CAA-UK) at normal revision RN0, or subsequent EASA approved issues;

- such code E (CAA-UK) Flight Manual Supplement does not constitute operational approval and operations must be conducted in accordance with applicable operational regulation.

6. The AS 332 L2 helicopters without MGB fire detection system are those modified by AMS 07-25208, design change resulting from CAA-UK's original type certification.

**Section 4 EC 225 LP****i. General****1. Type / Variant / Model**

1.1 Type EC 225

1.2 Model EC 225 LP

1.3 Variant -

**2. Airworthiness Category**

Large Rotorcraft, Category A and B (see Note 6)

**3. Type Certificate Holder**

Airbus Helicopters

Aéroport International Marseille – Provence

13725 Marignane CEDEX

France

See Section 5ii.

**4. Manufacturer**

See Section 5ii.

**5. Type Certification Application Date to DGAC FR**

7 November 2000

**6. State of Design Authority**

EASA

**7. EASA Type Certification Date**

27 July 2004

**ii. Certification Basis****1. Reference Date for determining the applicable requirements**

For Airworthiness and Environmental Protection:

7 November 2000,

for OSD elements:

17 February 2014 (grandfathering date).

**2. Airworthiness Requirements**

JAR 29, Change 1 effective 1 December 1999

CS 29.1465 Amdt.3 - Vibration Health Monitoring for Airworthiness Credit (F-09), see Note 7

For helicopters equipped with MOD 07-53048, see Note 8.

**3. Special Conditions**

- Minimum in flight experience (B-01).

- SAR (Search and Rescue) system (B-02).

- Water Bombing System (B-05).

- External loads, JAR 29.865 Amdt. 2 (D-06).

- Protection from the effects of High Intensity Radiated Field (HIRF) (F-02).

- Non-rechargeable Lithium Battery Installations (F-13).

- Helicopter limited icing approval (O-01).

**4. Exemptions**

- JAR 29.562 Emergency dynamic landing conditions (C-02).
- JAR 29.952(a)(c)(d)(e)(f)(g) Fuel system crash resistance (E-01).
- JAR 29.955(b) Fuel transfer (E-05).
- partial exemption: JAR 29.963(b) Fuel tanks: general; Puncture resistance (E-02).

**5. Deviations**

- ADS-B Out Extended Squitter & EHS Installation with Transponder TDR-94D equipment (MOD 332P690408.05) (F-11).
- Reversion to FAR 29, Amdt. 24 as follows:
  - FAR 29.561 (b)(3) Emergency landing conditions-general (C-01).
- Partial reversions to FAR 29, Amdt. 24 as follows:
  - FAR 29.571 Fatigue evaluation of structure (C-03).
  - FAR 29.785 Seat, berth, safety belts, and harnesses (D-01).
- JAR 29.785 (a), Installation of side-facing seats (D-09).
- JAR 29.562 (a), Installation of side-facing seats (D-09).

**6. Equivalent Safety Findings**

- JAR 29.173, .175 Static longitudinal Stability (B-03).
- JAR 29 App B §IV IFR Static longitudinal Stability – Airspeed stability (B 04).
- JAR 29.571 Fatigue evaluation of structure for changed metallic PSE (C-04).
- JAR 29.807 (c)(1) Passenger emergency exits other than side-of-fuselage (D-02).
- JAR 29.813 (a), 29.815 Emergency exit access - Main aisle width (D-03).
- JAR 29. 807 (d)(2) Ditching emergency exits for passengers (D-07).
- JAR 29.601, 29.603, 29.605, 29.865 Hoist installation (D-10)
- JAR 29.923 (a)(2) Rotor drive system and control mechanism tests (E-03).
- JAR 29.1303 (j) VNE aural warning (F-01).
- JAR 29.1545 (b)(4) Airspeed indicators markings (G-01).
- JAR 29.1549 (b) Powerplant instruments markings (G-02).
- CS 29.923 and 29.927 Amdt. 4 (E-09), for helicopters equipped with MOD 07-53048.

**7. Environmental Protection Requirements**

- |     |                        |  |
|-----|------------------------|--|
| 7.1 | Noise Requirements     | see TCDSN UK.TC.R.00065                                |
| 7.2 | Emissions Requirements | Compliant with ICAO Annex 16 Volume 2 - Fuel Discharge |

**8. Operational Suitability Data (OSD)**

- |     |  |   |
|-----|--|---|
| 8.1 | Master Minimum Equipment List (MMEL)     | JAR-MMEL/MEL Section 1, Subpart A and B, Amdt. 1, dated 1 August 2005                       |
| 8.2 | Flight Crew Data (FCD)                   | CS-FCD Initial Issue, dated 31 January 2014 (elect to comply as per EASA approval 10060827) |
| 8.3 | Simulation Data (SIMD)                   | Reserved  |
| 8.4 | Maintenance Certifying Staff Data (MCSD) | Reserved  |
| 8.5 | Cabin Crew Data (CCD)                    | Reserved  |

**iii. Technical Characteristic and Operating Limitations****1. Type Design Definition**

For EC 225 LP Standard:  
Documents ref. 332 A 89 2120

For EC 225 LP MPAI (\*) equipped:  
when standard definition is completed with design change ref. AMS OP 23554

Note: (\*) MPAI means Multi-Purpose Air Intakes

**2. Description**

Large twin-engine helicopter: derivative design of former type certified AS 332 L2 model

Standard configuration consists of grid-type engine air intakes installation, while MPAI configuration is optional and consists of Multi-Purpose Air Intakes

**3. Equipment**

As required by JAR 29 and referenced in approved RFM

**4. Dimensions**

- |     |            |                              |                          |                |
|-----|------------|------------------------------|--------------------------|----------------|
| 4.1 | Fuselage   | Length: 16.49 m              | Width stabiliser: 3.96 m | Height: 4.97 m |
| 4.2 | Main Rotor | Diameter: 16.20 m (5 blades) |                          |                |
| 4.3 | Tail Rotor | Diameter: 3.15 m (4 blades)  |                          |                |

**5. Engine**

5.1	Model	Safran Helicopter Engines (former: Turbomeca) 2 x Model MAKILA 2A, or, 2 x Model MAKILA 2A1
5.2	Type Certificate	EASA TC/TCDS n°: EASA.E.006
5.3	Limitations	
5.3.1	Installed Engine Limitations	Refer to approved RFM
5.3.2	Transmission Torque Limits	Refer to approved RFM

**6. Fluids**

6.1	Fuel	Refer to approved RFM
6.2	Oil	Refer to approved RFM
6.3	Additives	Refer to approved RFM

**7. Fluid capacities**

7.1	Fuel	Standard configuration: 2 588 litres (682 US gal) with optional internal 6th tank: 320 litres (84 US gal) Total available fuel: 2 908 litres (766 US gal) Note: see RFM for other approved optional fuel tanks configurations and for unusable fuel quantities.
7.2	Oil	Engines: 2 x 4.92 litres MGB: 27.0 litres IGB: 0.62 litre TGB: 1.50 litre
7.3	Coolant System Capacity	n/a

**8. Air Speed Limitations**

$V_{NE PWR ON}$ : 175 KIAS below 5 000 ft DA and  
above 5 000 ft: -3 KIAS/1000 ft.

$V_{NE PWR OFF}$ : 150 KIAS

Refer to RFM for other approved airspeed limits.

**9. Rotor Speed Limitations**

Power on:	
Maximum	275 rpm
Minimum	246 rpm
Minimum transient	220 rpm
Power off:	
Maximum transient (20 sec)	310 rpm
Maximum	290 rpm
Minimum (> 100 KIAS)	246 rpm
Minimum (< 100 KIAS)	220 rpm

**10. Maximum Operating Altitude and Temperature**

- 10.1 Altitude
- TKOF/LDG for EC 225 LP Standard:  
 OAT from -45°C to -12°C:  
 -6 000 ft DA to +7 400 ft DA  
 OAT from -12°C to ISA +40°C (without exceeding +50°C):  
 -2 000 ft PA to +7 400 ft DA  
 TKOF/LDG for EC 225 LP MPAL equipped:  
 OAT from -45°C to -12°C:  
 -6 000 ft DA to +11 000 ft DA  
 OAT from -12°C to ISA +40°C (without exceeding +50°C):  
 -2 000 ft PA to +11 000 ft DA  
 Enroute for EC 225 LP Standard/MPAL equipped:  
 OAT from -45°C to -12°C:  
 -6 000 ft DA to +20 000 ft PA  
 OAT from -12°C to ISA +40°C (without exceeding +50°C):  
 -2 000 ft PA to +20 000 ft PA
- 10.2 Temperature
- 30°C to ISA +40°C, limited to 50°C  
 See RFMS SUPP 2 for lower temperature operation down to -45°C.
- 11. Operating Limitations**
- VFR day and night, IFR, non-icing conditions  
 Flight in full icing conditions is permitted only when other equipment items as listed in relevant approved RFMS are installed.  
 Flight in limited icing conditions is permitted only when equipment items listed in relevant approved RFMS are installed (see Note 5).
- 12. Maximum Mass**
- TKOF/LDG: 11 000 kg (24 251 lb)  
 For helicopters equipped with MAKILA 2A1 engine and MOD 07.28724:  
 TKOF/LDG: 11 160 kg (24 604 lb)
- 13. Centre of Gravity Range**
- Refer to approved RFM
- 14. Datum**
- Longitudinal:  
 STA 0: 4.670 m (183.86 in) forward of main rotor centreline  
 Lateral: aircraft symmetry plane
- 15. Levelling Means**
- Levelling plate on right side of the fuselage and graduated plate for plumb line on cabin floor (left side door)

- 16. Minimum Flight Crew** VFR: 1 pilot  
IFR: 2 pilots  
Note: Pilot and suitably trained crew member in day VFR for fire-fighting operations.
- 17. Maximum Passenger Seating Capacity** 25
- 18. Passenger Emergency Exit** one (1) door, the dimensions of which exceed those of Type II exit + two (2) Type IV exits on each side
- 19. Maximum Baggage/ Cargo Loads** The cabin floor (from +2.48 m to +7.63 m) is provided with the structural strength required for a load of 800 kg/m<sup>2</sup> evenly distributed in cargo configuration
- 20. Rotor Blade Control Movement** For rigging information refer to AMM
- 21. Auxiliary Power Unit (APU)** Optional; to be used on ground only.  
Refer to approved RFMS.
- 22. Life-limited Parts** Refer to approved Airworthiness Limitations Section
- 23. Wheels and Tyres** Wheels:  
NLG Messier Bugatti C 20525 000 (two)  
MLG Messier Bugatti C 20147 200 (one each side)  
Tyres:  
NLG 466 x 173-10 (two)  
MLG 615 x 225-10 (one each side)

- iv. Operating and Service Instructions**
- 1. Flight Manual**
- For EC 225 LP Standard:  
 EC 225 LP Flight Manual, normal revision RN0 (04-20),  
 EASA approved 27 July 2004, or subsequent approved revisions.
- EC 225 LP MPAI equipped:  
 EC 225LP MPAI Flight Manual, normal revision RN2 (04-44), EASA approved 21 December 2004, or subsequent approved revisions
- 2. Maintenance Manual**
- Maintenance Programme:  
 - EC 225 LP Maintenance Servicing Recommendations (PRE),  
 - EC 225 LP Aircraft Maintenance Manual (AMM)
- Airworthiness Limitations:  
 EC 225 LP Maintenance Servicing Recommendations, Chapter 05.99 (or newly Chapter 04 approved by EASA), edition 2004.05.31, Rev. 000, EASA approved on 27 July 2004, or subsequent approved revisions
- 3. Structural repair Manual**
- EC 225 LP Structural Repair Manual
- 4. Weight and Balance Manual**
- Refer to approved RFM.
- 5. Illustrated Parts Catalogue**
- Not recorded
- 6. Service Letters and Service Bulletins**
- As published by Eurocopter or Airbus Helicopters
- 7. Required Equipment**
- As per compliance with applicable JAR 29 requirements and in accordance with the original Type Design standard.  
 - Refer to approved Flight Manual and MMEL.
- v. Operational Suitability Data**
- 1.1 Master Minimum Equipment List (MMEL) MMEL EC 225 LP Normal Revision 4, Issue 2, Date Code 13-25, dated 24 October 2013, or later approved revisions.
- 1.2 Flight Crew Data (FCD) OSD-FCD Super Puma Fleet RN 2 Date Code 16-50, or later approved revision.
- 1.3 Simulation Data (SIMD) Reserved
- 1.4 Maintenance Certifying Staff Data (MCSD) Reserved
- 1.5 Cabin Crew Data (CCD) Reserved

**vi. Notes**

1. Manufacturer's eligible serial numbers:

s/n 2600, and subsequent of EC 225 LP model are eligible.

2. The certified "optional" installations are each approved independently of the basic helicopter and an approved Flight Manual Supplement is associated to each optional installation if necessary (some optional installations are specific to the EC 225 LP equipped with MPAI and the relevant RFMS are approved for that particular EC 225 LP type design definition only).

3. Cabin Interior and Seating Configurations must be approved; passenger transport is not permitted in both operational and non-operational configurations of the Water Bombing System; except while performing Water Bombing operations, the EC 225 LP is not approved for the carriage of cargo only in the cabin.

4. Commercial designation 'SUPER PUMA Mk II+' or 'LP' corresponds to EC 225 LP model.

Since 1 Jan 2016, H225 is the new commercial designation for EC 225 LP model.

5. Flight in limited icing conditions and fire-fighting operations:

The relevant approved Flight Manual Supplements do not constitute operational clearance approvals and operations must be conducted in accordance with applicable operational regulation.

6. The EC 225 LP is certified as Category A rotorcraft with operating limitations as defined in the relevant approved RFMS.

7. For EC 225 LP helicopters equipped with M'ARMS (optional Vibration Health Monitoring system), the associated mandatory design change MOD 0726978 / 0726994 (defined as 'M'ARMS MOD45 monitoring') is certified in compliance with CS 29.1465 of CS 29 Amdt. 3 – see above 'II.7. Requirement elected to comply'.

8. For EC 225 LP helicopters equipped with MOD 07-53048, the design change is certified in compliance with the following with CS 29 Amdt. 4 paragraphs and subparagraphs, elected to comply: 29.29, 29.301(a), 29.303, 29.305, 29.307, 29.361, 29.547 (d)(2), 29.561, 29.571, 29.601 (a), 29.601 (b), 29.602, 29.603, 29.605, 29.607, 29.609, 29.611, 29.613, 29.619, 29.623, 29.625, 29.917 (a), 29.917 (b), 29.917 (c), 29.923, 29.927 (a), 29.927 (b)(1), 29.927 (c), 29.927 (d), 29.927 (e), 29.927 (f), 29.1027, 29.1041 (b), 29.1041 (c), 29.1301, 29.1305 (a)(23), 29.1309 (b)(2)(i), 29.1309 (b)(2)(ii), 29.1309 (d)(1), 29.1309 (d)(2), 29.1309 (d)(3), 29.1309 (d)(4), 29.1529.

## Section 5 : Administration

### i. Acronyms and Abbreviations

Acronym / Abbreviation	Definition
Amdt.	Amendment
AMM	Aircraft Maintenance Manual
AMS	Aircraft Modification system
APU	Auxiliary Power Unit
C.G.	Centre of Gravity
DA	Density Altitude
DGAC FR	Direction Générale de l'Aviation Civile - France
HIRF	High Intensity Radiated Field
ICAO	International Civil Aviation Organisation
IFR	Instrument Flight Rules
IPC	Illustrated Parts Catalogue
JAR	Joint Airworthiness Requirements
KIAS	Knots Indicated Air Speed
M'ARMS	EC225's Vibration Health Monitoring
M MEL	Master Minimum Equipment List
MPAI	Multi-Purpose Air Intakes
OSD	Operational Suitability Data
P/N	Part number
PA	Pressure Altitude
RFM	Rotorcraft Flight Manual
s/n	Serial Number
SIM	Simulator
VFR	Visual Flight Rules
VNE	Never Exceed Speed

### ii. Type Certificate Holder Record

Type Certificate Holder and Manufacturer	Period
Aérospatiale 37, Boulevard de Montmorency 75781 Paris CEDEX 16, France	From 29 April 1976 until 31 December 1991
Eurocopter France Aéroport International Marseille – Provence 13725 Marignane CEDEX, France	From 1 January 1992 until 30 May 1997
Eurocopter Aéroport International Marseille – Provence 13725 Marignane CEDEX, France	From 1 June 1997 until 6 January 2014
Airbus Helicopters Aéroport International Marseille – Provence 13725 Marignane CEDEX, France	Since 7 January 2014

## iii. Amendment Record

TCDS Issue No.	TCDS Issue Date	Changes	TC Issue and Date
1	14 May 2024	<p>The content of the initial issue of this UK CAA TCDS was taken from EASA TCDS No. EASA.R.002 Issue 16 dated 26 July 2017 which was the current EASA version on 31 December 2020 and therefore the version accepted by the UK under Article 15 of Annex 30 of the UK-EU Trade and Cooperation Agreement. Other changes introduced are as follows:</p> <p>Section 1 (SA 330 J) amended:</p> <ul style="list-style-type: none"> <li>- III.12.: lb value corrected.</li> </ul> <p>Section 2 (AS 332 C, C1, L, L1) amended:</p> <ul style="list-style-type: none"> <li>- II.1, II.7, OSD: editorial</li> <li>- II.2., II.3., II.6., V.: SC and ESF references amended.</li> <li>- II.2, V.: Elect to Comply for AS 332 C, C1, C1e, L, L1, L1e equipped with a FFMP (MOD 07.53061) added.</li> <li>- II.3: AS 332 C1 and L1 Certification Basis updated to introduce the Special Condition F-09.</li> <li>- III.7.: fuel values correction.</li> <li>- III.8., III.10., III.12.: lb values corrected.</li> <li>- IV.2.: MM original approval date added.</li> <li>- V.5.: new commercial designation added.</li> <li>- V.8.: unaffected area updated</li> </ul> <p>Section 3 (AS 332 L2) amended:</p> <ul style="list-style-type: none"> <li>- II.1, II.7, OSD: editorial.</li> <li>- III.12.: lb value corrected.</li> <li>- IV.2.: MM original approval date added.</li> </ul> <p>Section 4 (EC 225 LP) amended:</p> <ul style="list-style-type: none"> <li>- II.1, II.7, OSD: editorial</li> <li>- II.2.: EC 225 LP Certification Basis updated to introduce the reference to Note 8 for helicopters equipped with MOD 07-53048.</li> <li>- II.3.: EC 225 LP Certification Basis updated to introduce the Special Condition F-13.</li> <li>- II.3., II.4., II.5., II.6., II.7.: SC and ESF references amended.</li> <li>- II.5: EC 225 LP Certification Basis updated to introduce the deviation F-11.</li> <li>- II.6: EC 225 LP Certification Basis updated to introduce ESFs D-10 and E-09.</li> <li>- II.8: noise requirement wording corrected.</li> <li>- III.12: maximum mass updated for helicopters equipped with MAKILA 2A1 engine and MOD 07.28724.</li> <li>- IV.2: typo corrected.</li> <li>- V.4.: new commercial designation added.</li> <li>- V.8.: new Note 8 added.</li> </ul> <p>Section 5: OSD, complete section removed and OSD information moved to specific helicopter model sections:</p> <ul style="list-style-type: none"> <li>- I. deleted/shifted to II. Certification Basis</li> </ul> <p>Section ADMINISTRATIVE amended:</p> <ul style="list-style-type: none"> <li>- II.: table title updated.</li> </ul> <p>Applicable to all Sections:</p> <ul style="list-style-type: none"> <li>- III.8.: speed units clarification.</li> </ul>	Issue 1 14 May 2024

– END –