

UK Air Traffic Management Vocabulary

CAP 1430



© Civil Aviation Authority, 2025

You can copy and use this text but please ensure you always use the most up to date version and use it in context so as not to be misleading, and credit the CAA.

First published 29 September 2016, effective 5 January 2017

Second Edition published 17 August 2017, effective 12 October 2017

Third Edition published 30 July 2021, effective 28 September 2021

Fourth Edition published 17 March 2023, effective 15 June 2023

Fifth Edition published 1 August 2025, effective 30 September 2025

Enquiries regarding the content of this publication should be addressed to:

Airspace, ATM & Aerodrome, Safety and Airspace Regulation Group, Civil Aviation Authority,
Aviation House, Beehive Ring Road, Crawley, West Sussex, RH6 0YR.

The latest version of this document is available at: www.caa.co.uk/CAP1430

List of Effective Pages

Section	Page	Date
Contents	1	30 September 2025
Contents	2	30 September 2025
Foreword	3	30 September 2025
Foreword	4	30 September 2025
Definitions	5	30 September 2025
Definitions	6	30 September 2025
Definitions	7	30 September 2025
Definitions	8	30 September 2025
Definitions	9	30 September 2025
Definitions	10	30 September 2025
Definitions	11	30 September 2025
Definitions	12	30 September 2025
Definitions	13	30 September 2025
Definitions	14	30 September 2025
Definitions	15	30 September 2025
Definitions	16	30 September 2025
Definitions	17	30 September 2025
Definitions	18	30 September 2025
Definitions	19	30 September 2025
Definitions	20	30 September 2025
Definitions	21	30 September 2025
Definitions	22	30 September 2025
Definitions	23	30 September 2025
Definitions	24	30 September 2025
Definitions	25	30 September 2025
Definitions	26	30 September 2025
Definitions	27	30 September 2025
Definitions	28	30 September 2025
Definitions	29	30 September 2025
Definitions	30	30 September 2025
Definitions	31	30 September 2025
Definitions	32	30 September 2025
Definitions	33	30 September 2025

Section	Page	Date
Definitions	34	30 September 2025
Definitions	35	30 September 2025
Definitions	36	30 September 2025
Definitions	37	30 September 2025
Definitions	38	30 September 2025
Definitions	39	30 September 2025
Definitions	40	30 September 2025
Definitions	41	30 September 2025
Definitions	42	30 September 2025
Definitions	43	30 September 2025
Definitions	44	30 September 2025
Definitions	45	30 September 2025
Definitions	46	30 September 2025
Definitions	47	30 September 2025
Definitions	48	30 September 2025
Definitions	49	30 September 2025
Definitions	50	30 September 2025
Definitions	51	30 September 2025
Definitions	52	30 September 2025
Definitions	53	30 September 2025
Definitions	54	30 September 2025
Definitions	55	30 September 2025
Definitions	56	30 September 2025
Definitions	57	30 September 2025
Definitions	58	30 September 2025
Definitions	59	30 September 2025
Definitions	60	30 September 2025
Abbreviations and Acronyms	61	30 September 2025
Abbreviations and Acronyms	62	30 September 2025
Abbreviations and Acronyms	63	30 September 2025
Abbreviations and Acronyms	64	30 September 2025

Section	Page	Date
Abbreviations and Acronyms	65	30 September 2025
Abbreviations and Acronyms	66	30 September 2025
Abbreviations and Acronyms	67	30 September 2025
Abbreviations and Acronyms	68	30 September 2025
Abbreviations and Acronyms	69	30 September 2025
Abbreviations and Acronyms	70	30 September 2025
Abbreviations and Acronyms	71	30 September 2025
Abbreviations and Acronyms	72	30 September 2025
Abbreviations and Acronyms	73	30 September 2025
Abbreviations and Acronyms	74	30 September 2025
Abbreviations and Acronyms	75	30 September 2025

Revision History

The table below is provided as a reference to highlight when major changes were made to the content of CAP 1430. It does not cover editorial changes. As necessary, an update will be added to the table at each amendment.

Fifth Edition

Section	Subject	Source
Foreword	<p>Provenance: Reference to 'retained' regulation amended to 'assimilated' regulation.</p> <p>Applicability: Updated to include CAP 670 and CAP 1616.</p> <p>Enquiries: Updated</p>	CAA
Definitions	<p>The following definitions have been added:</p> <ul style="list-style-type: none"> - Acts of unlawful interference - Aerodrome Flight Information Service (AFIS) - Aerodrome Reference Point - Aeronautical Data Quality (ADQ) - Aeronautical Information Circular (AIC) - Aeronautical Information Publication Change Request - Aeronautical Information Publication Supplement (AIP SUP) - Aeronautical Information Regulation and Control (AIRAC) cycle - Aeronautical Mobile Station - Airborne collision avoidance system (ACAS) specific definitions - Air Navigation Directions - Air Navigation Guidance - Airspace change portal - Airspace change process - Airspace change proposal (ACP) - Airspace infringement - Airspace Modernisation Strategy (AMS) - Air safety report (ASR) - Airspace structure - Airspace Trial - Air Traffic Management safety questionnaire 	ICAO, Eurocontrol & CAA

Section	Subject	Source
	<ul style="list-style-type: none"> - Applicability and Policy Alignment Check (APAC) - Approved Procedure Design Organisation (APDO) - ATS Message Handling System (AMHS) - Aurora Data Originators Portal - Communications, navigation and surveillance (CNS) infrastructure - Continuous climb (or descent) operations (CCO/CDO) - Defence Airspace and Air Traffic Management (DAATM) - Disruptive passenger - Electronic Conspicuity - Filed flight plan (FPL) - Flight behaviours - Flight procedures - Flight rules - Hazard - Instrument flight procedure (IFP) - Instrument Flight Rules (IFR) - International Airport - International Civil Aviation Organization standards and recommended practices (ICAO SARPs) - Launch Operator - Lower Airspace Radar Service (LARS) - Manual of Air Traffic Services - Manual of Air Traffic Services Part 1 - Manual of Air Traffic Services Part 2 - National Air Traffic Management Advisory Committee (NATMAC) - NATS - Navigation aid - Network Manager - Non-standard Planning Zone (NPZ) - Noise abatement procedures - Noise preferential route (NPR) - Non-instrument runway - Notified - Notified airspace design - Offshore Aeronautical Service (OAS) - Offshore Communication Service (OCS) - Operational Control 	

Section	Subject	Source
	<ul style="list-style-type: none"> - Order - Point in space (PinS) - Remotely Piloted Aircraft System (RPAS) - Safety Management System (SMS) - Spaceport - Statement of Need - Supplementary Instruction (SI) - Temporary Operating Instruction (TOI) - Transport Act 2000 - Unruly passengers - Visual Reference Point (VRP) <p>The following definitions have been amended:</p> <ul style="list-style-type: none"> - General Air Traffic - Special Use Airspace (SUA) - Temporary Reserved Area (TRA) - Temporary Segregated Area (TSA) - UK Standardised European Rules of the Air ((UK) SERA) <p>The following definitions have been removed:</p> <ul style="list-style-type: none"> - Managed Danger Area (MDA) 	
Abbreviations and Acronyms	<p>The following abbreviations and acronyms have been added:</p> <ul style="list-style-type: none"> - AAA - ADC - ADQ - ADS - AFPEx - AIPCR - AIP SUP - AIRAC cycle - AltMOC - AMC - AMHS - AMS - ANG - AOC - APAC - APC - APDO - ARP - ASL - ASR 	ICAO, Eurocontrol & CAA

Section	Subject	Source
	<ul style="list-style-type: none"> - ATM - CCO - CDO - CNS - D-ATIS - DOC - DVOR - EASA - ECCAIRS - FID - GM - HLA - ICAO SARPs - IFP - IN - Infringement - INS - km/h - LARS - MATS Pt 1 - MATS Pt 2 - MoU - NGO - NPR - OAS - OCS - PinS - RAG - RNP - RO - RPAS - SERA - SI - SMS - TOI - UK FIS - VRP - VTOL <p>The following abbreviations and acronyms have been amended:</p> <ul style="list-style-type: none"> - NPZ - QNE 	

Section	Subject	Source
	<ul style="list-style-type: none"> - R of A changed to RoTA <p>The following abbreviations and acronyms have been deleted:</p> <ul style="list-style-type: none"> - NOTAM - MDA (Managed Danger Area) 	

Fourth Edition

Section	Subject	Source
Foreword	No change.	CAA
Definitions	<p>The following definitions have been amended:</p> <ul style="list-style-type: none"> - Air Traffic Management (ATM) - note added. - Ground effect (Rotary-wing) - Level Bust - Special Use Airspace (SUA) - Unmanned aircraft system (UAS) <p>The following definition have been added:</p> <ul style="list-style-type: none"> - Beyond Visual Line Of Sight (BVLOS). - Segregated airspace - Unmanned aircraft system Traffic Management - Visual Line Of Sight (VLOS) 	ICAO, Eurocontrol & CAA
Abbreviations and Acronyms	<p>The following abbreviations have been added:</p> <ul style="list-style-type: none"> - BVLOS - Beyond Visual Line Of Sight. - UTM – Unmanned aircraft system Traffic Management - VLOS – Visual Line Of Sight. 	ICAO, Eurocontrol & CAA

Third Edition

Section	Subject	Source
Foreword	Provenance section updated to reflect changes in regulation references and contact address amended within the enquiries section.	CAA
Definitions	<p>The following definitions have been amended:</p> <ul style="list-style-type: none"> - Dependent parallel approaches. - Independent parallel approaches. - Normal operation zone. - Standard European Rules of the Air changed to UK Standard European Rules of the Air. <p>The following definition have been added:</p>	ICAO, Eurocontrol & CAA

Section	Subject	Source
	<ul style="list-style-type: none"> - CPDLC message. - CPDLC message set. - Data convention. - Data link initiation capability. - Data processing. - Flight plan Buffer Zone (FBZ). - Free Route Airspace (FRA). - FRA Arrival Connecting Point (A). - FRA Departure Connecting Point (D). - FRA Horizontal Entry Point (E). - FRA Intermediate Point (I). - FRA Horizontal Exit Point (X). - Free text message element. - ITP aircraft. - ITP distance. - Logon address. - Meteorological information. - Meteorological office. - Meteorological report. - No Planning Zone (NPZ). - Performance-based communication (PBC). - Performance-based navigation (PBN). - Performance-based surveillance (PBS). - Recognised air traffic environment. - Required communication performance (RCP) specification. - Required surveillance performance (RSP) specification. - Standard message element. - Time difference of arrival (TDOA). - Total estimated elapsed time. - Visual surveillance system. 	
Abbreviations	<p>The following abbreviation have been amended:</p> <ul style="list-style-type: none"> - MTOM changed to MCTOM. - NOTAM changed from Notice to Airmen to Notice to Aviation. - SERA changed to (UK) SERA. <p>The following abbreviation have been added:</p> <ul style="list-style-type: none"> - DLIC – Data link initiation capability. - EGPWS – Enhanced Ground Proximity Warning System - FBZ – Flight plan Buffer Zone. - FRA – Free Route Airspace. 	ICAO, Eurocontrol & CAA

Section	Subject	Source
	<ul style="list-style-type: none"> - FRA(A) – FRA Arrival Connecting Point. - FRA(D) – FRA Departure Connection Point. - FRA(E) – FRA Horizontal Entry Point. - FRA(I) – FRA Intermediate Point. - FRA(X) – FRA Horizontal Exit Point. - GCAS – Ground Collision Avoidance System - NPZ – No Planning Zone. - PBC – Performance-based communication. - PBN – Performance-based navigation. - PBS – Performance-based surveillance. - RCP – Required communication performance. - RSP – Required surveillance performance. - SFN – Special Flight Notification. - PLOC – Prolonged Loss of Communications. - TAWS – Terrain Awareness and Warning System. - TDOA – Time difference of arrival. 	

Second Edition

Section	Subject	Source
All	Implement Reg (EU) No 1185/2016 Standardised European Rules of the Air Part C and adopt ICAO Doc 4444 PANS-ATM Sixteenth Edition.	EASA & ICAO

Contents

List of Effective Pages	i
Revision History	iii
Contents	1
Foreword	3
Introduction	3
Provenance	3
Applicability	4
Enquiries	4
Definitions	5
A	5
B	20
C	21
D	24
E	26
F	27
G	30
H	31
I	32
K	36
L	37
M	38
N	40
O	42
P	44
R	47
S	50
T	53
U	56

V	58
W	60
Abbreviations and Acronyms	61
A	61
B	64
C	64
D	65
E	65
F	66
G	67
H	67
I	68
J	68
K	68
L	69
M	69
N	70
O	71
P	71
Q	72
R	72
S	73
T	73
U	74
V	75

Foreword

Introduction

This document provides the authoritative reference for all terms and abbreviations used within specific CAA Civil Aviation Publications (CAPs).

Provenance

Two strands of UK aviation related legislation now exist. That made under the Air Navigation Order (and including the Rules of the Air Regulations), and that made under The Basic Regulation (UK Reg (EU) 2018/1139 as assimilated (and amended in UK domestic law) under the European Union (Withdrawal) Act 2018) and its Implementing Rules.

The terms and abbreviations contained within this document are sourced, primarily, from assimilated European Union (EU) Regulations, as amended by various UK Statutory Instruments (made under the European Union (Withdrawal) Act 2018). For example, Regulation (EU) No 923/2012 Standardised European Rules of the Air (SERA) as assimilated (and amended in UK domestic law) under the European Union (Withdrawal) Act 2018 ("UK Reg (EU) No 923/2012").

References to the 'Cover Regulation' are cited as either UK Reg (EU) No XXX/YYYY followed by the appropriate Article, or UK Reg (EU) YYYY/XXX; where 'X' is the number of the Regulation and 'YYYY' is the year of publication.

Where terms and abbreviations are not defined within such assimilated EU Regulations, additional material has been sourced from:

- a) Annexes to the Convention on International Civil Aviation and, where appropriate, to ICAO documents such as PANS-ATM (Doc 4444) and PANS-OPS (Doc 8168);
- b) The UK Air Navigation Order and supporting UK policy documentation; and,
- c) The EUROCONTROL European Route Network Improvement Plan Part 1: Airspace Design Methodology Guidelines.
- d) The EUROCONTROL European Route Network Improvement Plan Part 3: Airspace Management Handbook – Guidelines for Airspace Management. Hereafter referred to as the EUROCONTROL ASM Handbook.

Exceptionally, where the UK has filed a Difference to an ICAO Standard, the term defined within the UK Air Navigation Order or instrument made under it will have effect. In this instance, such variations or Differences will be highlighted with an asterisk (*) next to the document reference as follows: (* ANO 2016 Schedule 1)

Applicability

The terms and abbreviations contained within this document are applicable to the following CAA publications:

- a) Manual of Air Traffic Services (MATS) Part 1 (CAP 493);
- b) Flight Information Service Officer (FISO) Manual (CAP 797);
- c) UK Flight Information Services (FIS) (CAP 774);
- d) Radiotelephony Manual (CAP 413);
- e) UK Airspace Management Policy (CAP 740);
- f) Air Traffic Services Safety Requirements (CAP 670);
- g) The Process for Changing the Notified Airspace Design (CAP 1616).

The terms contained herein have been defined to remove any doubt about the meaning of instructions in the text of the documents listed above and are referenced to their source document.

Enquiries

Any enquiries concerning the content of this document should be marked for the attention of the Editor of CAP 1430 - ATM Vocabulary, and sent to: ats.enquiries@caa.co.uk

Definitions

A

Accepting unit/controller Air traffic control unit/air traffic controller next to take control of an aircraft.

Note: See definition of “transferring unit/controller”. (ICAO PANS-ATM (Doc 4444))

Accuracy A degree of conformance between the estimated or measured value and the true value. (UK Reg (EU) No 923/2012 Article 2(1))

Acts of unlawful interference Acts or attempted acts such as to jeopardize the safety of civil aviation, including but not limited to:

- unlawful seizure of aircraft,
- destruction of an aircraft in service,
- hostage-taking on board aircraft or on aerodromes,
- forcible intrusion on board an aircraft, at an airport or on the premises of an aeronautical facility,
- introduction on board an aircraft or at an airport of a weapon or hazardous device or material intended for criminal purposes,
- use of an aircraft in service for the purpose of causing death, serious bodily injury, or serious damage to property or the environment,
- communication of false information such as to jeopardize the safety of an aircraft in flight or on the ground, of passengers, crew, ground personnel or the general public, at an airport or on the premises of a civil aviation facility. (ICAO Annex 17)

Advisory airspace An airspace of defined dimensions, or designated route, within which air traffic advisory service is available. (UK Reg (EU) No 923/2012 Article 2(3))

Advisory route A designated route along which air traffic advisory service is available. (UK Reg (EU) No 923/2012 Article 2(4))

Aerial work An aircraft operation in which an aircraft is used for specialised services such as agriculture, construction, photography, surveying, observation and patrol, search and rescue, aerial advertisement, etc. (UK Reg (EU) No 923/2012 Article 2(12))

Aerobatic flight Manoeuvres intentionally performed by an aircraft involving an abrupt change in its attitude, an abnormal attitude, or an abnormal variation in speed, not necessary for normal flight or for instruction for licenses or ratings other than aerobatic rating. (UK Reg (EU) No 923/2012 Article 2(5))

Aerodrome A defined area (including any buildings, installations and equipment) on land or water or on a fixed, fixed off-shore or floating structure intended to be used either wholly or in part for the arrival, departure and surface movement of aircraft. (UK Reg (EU) No 923/2012 Article 2(6))

Aerodrome control service Air traffic control service for aerodrome traffic. (UK Reg (EU) No 923/2012 Article 2(7))

Aerodrome control tower A unit established to provide air traffic control service to aerodrome traffic. (UK Reg (EU) No 923/2012 Article 2(8))

Aerodrome Flight Information Service (AFIS) A flight information service for aerodrome traffic provided by a designated air traffic services provider. (Eurocontrol European Route Network Improvement Plan Part 1)

Aerodrome Operating Minima In relation to the operation of an aircraft at an aerodrome means the cloud ceiling and runway visual range for take-off, and the decision height or minimum descent height, runway visual range and visual reference for landing, which are the minimum for the operation of that aircraft at that aerodrome. (* ANO 2016 Schedule 1)

Aerodrome reference point The geographical location of the aerodrome and the centre of its traffic zone where an ATZ is established. (CAP 168)

Aerodrome traffic All traffic on the manoeuvring area of an aerodrome and all aircraft flying in the vicinity of an aerodrome. An aircraft operating in the vicinity of an aerodrome includes but is not limited to aircraft entering or leaving an aerodrome traffic circuit. (UK Reg (EU) No 923/2012 Article 2(9))

Aerodrome traffic circuit The specified path to be flown by aircraft operating in the vicinity of an aerodrome. (UK Reg (EU) No 923/2012 Article 2(10))

Aerodrome Traffic Monitor (ATM) An electronic display indicating the position and distance from touchdown of arriving aircraft relative to the extended centreline of the runway in use. It may also be used for other purposes. It is also known as the Distance From Touchdown Indicator (DFTI). (CAA)

Aerodrome Traffic Zone (ATZ) Airspace of defined dimensions established around an aerodrome for the protection of aerodrome traffic. (UK Reg (EU) No 923/2012 Article 2(11))

Aeronautical Data Quality (ADQ) Data quality requirements for the provision of aeronautical data and aeronautical information. (CAA)

Aeronautical Fixed Service (AFS) A telecommunication service between specified fixed points provided primarily for the safety of air navigation and for the regular, efficient and economical operation of air services. (ICAO Annex 11)

Aeronautical Ground Light[ing] (AGL) Any light specifically provided as an aid to air navigation, other than a light displayed on an aircraft. (ICAO Annex 14)

Aeronautical Information Circular (AIC) A notice containing information that does not qualify for the origination of a NOTAM or for inclusion in the AIP, but which relates to flight safety, air navigation, technical, administrative or legislative matters. (ICAO Annex 15)

Aeronautical Information Publication (AIP) A publication issued by or with the authority of a State and containing aeronautical information of a lasting character essential to air navigation. (UK Reg (EU) No 923/2012 Article 2(13))

Aeronautical Information Publication Change Request A process which allows authorised users to raise proposals to change data and information in the UK Aeronautical Information Publication for which they are responsible. (UK AIS)

Aeronautical Information Publication Supplement (AIP SUP) AIP SUPs will normally contain items of a temporary nature only. To be included in an AIP SUP, changes must be of operational significance and include comprehensive text and/or graphics (e.g., major air exercises or aerodrome work) that preclude 'complete' promulgation by NOTAM. They are to remain in the AIP for as long as all or some of their contents remain valid. (UK AIS)

Aeronautical Information Regulation and Control (AIRAC) cycle A 28 day cycle of common effective dates regulating when significant changes to the Aeronautical Information Publication can be made. Information is published either 28 days in advance (single AIRAC) or 56 days in advance (double AIRAC) in order to enable users of the aeronautical data to update their systems on the AIRAC cycle date of change, i.e. providers of aircraft flight management systems used to navigate along the flight plan route. (ICAO Annex 15)

Aeronautical Information Service (AIS) A service established within the defined area of coverage responsible for the provision of aeronautical information and data necessary for the safety, regularity, and efficiency of air navigation. (UK Reg (EC) No 549/2004 Article 2 (3))

Aeronautical Mobile Service A mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate; emergency position-indicating radio beacon stations may also participate in this service on designated distress and emergency frequencies. (UK Reg (EU) No 923/2012 Article 2(14))

Aeronautical Mobile Station A Station in the Aeronautical Mobile Service, other than an Aircraft Station, intended to be used while in motion or during halts at unspecified points. (ICAO Annex 10, Volume II)

Aeronautical Radio Station A radio station on the surface, which transmits or receives signals for the purpose of assisting aircraft. (ANO 2016 Schedule 1)

Aeronautical Station A land station in the Aeronautical Mobile Service. In certain instances, an aeronautical station may be located, for example, on board ship or on a platform at sea. (UK Reg (EU) No 923/2012 Article 2(15))

Aeroplane A power-driven heavier-than-air aircraft, deriving its lift in flight chiefly from aerodynamic reactions on surfaces which remain fixed under given conditions of flight. (UK Reg (EU) No 923/2012 Article 2(16))

Airborne collision avoidance system (ACAS) An aircraft system based on secondary surveillance radar (SSR) transponder signals which operates independently of ground based equipment to provide advice to the pilot on potential conflicting aircraft that are equipped with SSR transponders. (UK Reg (EU) No 923/2012 Article 2(17))

Airborne collision avoidance system (ACAS) specific definitions (ICAO Annex 10, Volume IV):

ACAS I An ACAS which provides information as an aid to “see and avoid” action but does not include the capability for generating resolution advisories (RAs).

Note: ACAS I is not intended for international implementation and standardisation by ICAO. Therefore, only ACAS I characteristics required to ensure compatible operation with other ACAS configurations and interference limiting are defined within ICAO Annex 10 Volume IV, paragraph 4.2.

ACAS II An ACAS which provides vertical resolution advisories (RAs) in addition to traffic advisories (TAs).

ACAS III An ACAS which provides vertical and horizontal resolution advisories (RAs) in addition to traffic advisories (TAs).

ACAS broadcast A long Mode S air-air surveillance interrogation (UF = 16) with the broadcast address.

Active RAC An resolution advisory complement is active if it currently constrains the selection of the RA. RACs that have been received within the last six seconds and have not been explicitly cancelled are active.

Altitude crossing RA A resolution advisory is altitude crossing if own ACAS aircraft is currently at least 30 m (100 ft) below or above the threat aircraft for upward or downward sense advisories, respectively.

Climb RA A positive RA recommending a climb but not an increased climb.

Closest approach The occurrence of minimum range between own ACAS aircraft and the intruder. Thus range at closest approach is the smallest range between the two aircraft and time of closest approach is the time at which this occurs.

Coordination The process by which two ACAS-equipped aircraft select compatible resolution advisories (RAs) by the exchange of resolution advisory complements (RACs).

Coordination interrogation A Mode S interrogation (uplink transmission) radiated by ACAS II or III and containing a resolution message.

Coordination reply A Mode S reply (downlink transmission) acknowledging the receipt of a coordination interrogation by the Mode S transponder that is part of an ACAS II or III installation.

Corrective RA A resolution advisory that advises the pilot to deviate from the current flight path.

Cycle The term “cycle” used in this chapter refers to one complete pass through the sequence of functions executed by ACAS II or ACAS III, nominally once a second.

Descend RA A positive RA recommending a descent but not an increased descent.

Established track A track generated by ACAS air-air surveillance that is treated as the track of an actual aircraft.

Increased rate RA A resolution advisory with a strength that recommends increasing the altitude rate to a value exceeding that recommended by a previous climb or descend RA.

Intruder An aircraft for which ACAS has an established track.

Own aircraft The aircraft fitted with the ACAS that is the subject of the discourse, which ACAS is to protect against possible collisions, and which may enter a manoeuvre in response to an ACAS indication.

Positive RA A resolution advisory that advises the pilot either to climb or to descend (applies to ACAS II).

Potential threat An intruder deserving special attention either because of its close proximity to own aircraft or because successive range and altitude measurements indicate that it could be on a collision or near-collision course with own aircraft. The warning time provided against a potential threat is sufficiently small that a traffic advisory (TA) is justified but not so small that a resolution advisory (RA) would be justified.

Preventive RA A resolution advisory that advises the pilot to avoid certain deviations from the current flight path but does not require any change in the current flight path.

RA sense The sense of an ACAS II RA is “upward” if it requires climb or limitation of descent rate and “downward” if it requires descent or limitation of climb rate. It can be both upward and downward simultaneously if it requires limitation of the vertical rate to a specified range.

Note: The RA sense may be both upward and downward when, having several simultaneous threats, ACAS generates an RA aimed at ensuring adequate separation below some threat(s) and above some other threat(s).

Resolution advisory (RA) An indication given to the flight crew recommending:

- a) a manoeuvre intended to provide separation from all threats; or
- b) a manoeuvre restriction intended to maintain existing separation.

Resolution advisory complement (RAC) Information provided by one ACAS to another via a Mode S interrogation in order to ensure complementary manoeuvres by restricting the choice of manoeuvres available to the ACAS receiving the RAC.

Resolution advisory complements record (RAC record) A composite of all currently active vertical RACs (VRCs) and horizontal RACs (HRCs) that have been received by ACAS. This information is provided by one ACAS to another ACAS or to a Mode S ground station via a Mode S reply.

Resolution advisory strength The magnitude of the manoeuvre indicated by the RA. An RA may take on several successive strengths before being cancelled. Once a new RA strength is issued, the previous one automatically becomes void.

Resolution message The message containing the resolution advisory complement (RAC).

Reversed sense RA A resolution advisory that has had its sense reversed.

Sensitivity level (S) An integer defining a set of parameters used by the traffic advisory (TA) and collision avoidance algorithms to control the warning time provided by the potential threat and threat detection logic, as well as the values of parameters relevant to the RA selection logic.

Note: For TA and RA selection, sensitivity level is not used in ACAS X-compliant systems.

Threat An intruder deserving special attention either because of its close proximity to own aircraft or because successive range and altitude measurements indicate that it could be on a collision or near-collision course with own aircraft. The warning time provided against a threat is sufficiently small that an RA is justified.

Track A sequence of measurements representing positions that could reasonably have been occupied by an aircraft.

Traffic advisory (TA) An indication given to the flight crew that a certain intruder is a potential threat.

Vertical speed limit (VSL) RA A resolution advisory advising the pilot to avoid a given range of altitude rates. A VSL RA can be either corrective or preventive.

Warning time The time interval between potential threat or threat detection and closest approach when neither aircraft accelerates.

Aircraft Any machine that can derive support in the atmosphere from the reactions of the air other than the reactions of the air against the earth's surface. (UK Reg (EU) No 923/2012 Article 2(18))

Aircraft address A unique combination of 24 bits available for assignment to an aircraft for the purpose of air-ground communications, navigation and surveillance. (UK Reg (EU) No 923/2012 Article 2(19))

Aircraft observation The evaluation of one or more meteorological elements made from an aircraft in flight. (UK Reg (EU) No 923/2012 Article 2(20))

Aircraft proximity (AIRPROX) A situation in which, in the opinion of a pilot or air traffic services personnel, the distance between aircraft as well as their relative positions and speed have been such that the safety of the aircraft involved may have been compromised. An aircraft proximity is classified as follows:

Risk of collision. The risk classification of an aircraft proximity in which serious risk of collision has existed.

Safety not assured. The risk classification of an aircraft proximity in which the safety of the aircraft may have been compromised.

No risk of collision. The risk classification of an aircraft proximity in which no risk of collision has existed.

Risk not determined. The risk classification of an aircraft proximity in which insufficient information was available to determine the risk involved, or inconclusive or conflicting evidence precluded such determination. (ICAO PANS-ATM (Doc 4444))

Air-ground communication Two way communication between aircraft and stations or locations on the surface of the earth. (UK Reg (EU) No 923/2012 Article 2(22))

Air-Ground Communications Service (AGCS) A service provided from an aerodrome to aerodrome traffic by means of radio signals and 'air/ground communications service unit' is to be construed accordingly. (ANO 2016 Schedule 1)

Air-ground control radio station An aeronautical telecommunication station having primary responsibility for handling communications pertaining to the operation and control of aircraft in a given area. (UK Reg (EU) No 923/2012 Article 2(23))

AIRMET Information Information issued by a meteorological watch office concerning the occurrence or expected occurrence of specified en-route weather phenomena which may affect the safety of low-level aircraft operations and which was not already included in the forecast issued for low-level flights in the flight information region concerned or sub-area thereof. (UK Reg (EU) No 923/2012 Article 2(21))

Air Navigation Directions Directions issued by the Secretary of State for Transport which set out the CAA's air navigation duties. (CAA)

Air Navigation Guidance Guidance issued by the Secretary of State for Transport to the CAA on its environmental objectives when carrying out its air navigation functions, and to the CAA and wider industry on airspace and noise management. The CAA is required to take account of this guidance from the Secretary of State when considering airspace change proposals. (CAA)

Air Navigation Services (ANS) Air traffic services; communication, navigation and surveillance services; meteorological services for air navigation; and aeronautical information services. (UK Reg (EC) No 549/2004 Article 2 (4))

Air Navigation Service Provider (ANSP) Any public or private entity providing ANS for general air traffic, including an organisation having applied for a certificate to provide such services. (UK Reg (EU) No 1035/2011 Article 2(15))

Airspace change portal The CAA's online portal containing details of all current and previous airspace changes. (<https://airspacechange.caa.co.uk>) (CAA)

Airspace change process The seven stage process an airspace change sponsor follows to submit an airspace change to the CAA for a decision. (CAA)

Airspace change proposal (ACP) A request, usually from an airport or air navigation service provider, for a change to the design of UK airspace. (CAA)

Airspace Infringement The unauthorised entry of an aircraft into notified airspace. (CAA)

Airspace Management A planning function with the primary objective of maximising the utilisation of available airspace by dynamic time-sharing and, at times, the segregation of airspace among various categories of airspace users on the basis of short-term needs. (UK Reg (EC) No 549/2004 Article 2(7))

Airspace Management Cell (AMC) A joint civil/military cell responsible for the day-to-day management and temporary allocation of national or sub-regional airspace under the jurisdiction of one or more European Civil Aviation Conference (ECAC) State(s). (EUROCONTROL Airspace Management (ASM) Handbook)

Airspace Modernisation Strategy (AMS) A co-ordinated strategy and plan for the use of UK airspace for air navigation up to 2040, including for the modernisation of the use of such airspace, prepared and maintained by the CAA, incorporating the previous Future Airspace Strategy. It is a requirement of the Air Navigation Directions 2017. (CAA)

Air Report A report from an aircraft in flight prepared in conformity with requirements for position, and operational and/or meteorological reporting. (UK Reg (EU) No 923/2012 Article 2(24))

Air safety report (ASR) A report raised internally within an airline/operator whereby flight crew can report safety-related concerns. (CAA)

Airspace structure A specific volume of airspace designed to ensure the safe and optimal operation of aircraft. (Eurocontrol: European Route Network Improvement Plan Part 1)

Airspace Trial Changes to airspace design, or ATC operational procedures (which if subsequently made permanent would constitute a relevant PPR), of a temporary nature for the purposes of—

- (a) investigating the feasibility of, or validating proposals for, innovative airspace design, technology or ATC operational procedures, or
- (b) assessing its performance and effect, or
- (c) supporting the development and integration of new airspace user groups into UK airspace. (Civil Aviation Authority (Air Navigation) Directions 2023)

Air-taxiing Movement of a helicopter/vertical take-off and landing (VTOL) above the surface of an aerodrome, normally in ground effect and at a ground speed normally less than 37 km/h (20 kt). (UK Reg (EU) No 923/2012 Article 2(25))

Note. The actual height during air-taxiing may vary, and some helicopters may require air-taxiing above 8 m (25 ft) AGL to reduce ground effect turbulence or provide clearance for cargo sling loads. (UK Reg (EU) No 923/2012 Article 2(25) GM1)

Air Traffic All aircraft in flight or operating on the manoeuvring area of an aerodrome. (UK Reg (EU) No 923/2012 Article 2(26))

Air traffic advisory service A service provided within advisory airspace to ensure separation, in so far as practical, between aircraft which are operating on instrument flight rules (IFR) flight plans. (UK Reg (EU) No 923/2012 Article 2(27))

Note.

- (a) Air traffic advisory service does not afford the degree of safety and cannot assume the same responsibilities as air traffic control (ATC) service in respect of the avoidance of collisions, since the information regarding the disposition of traffic in the area concerned available to the unit providing air traffic advisory service may be incomplete.
- (b) Aircraft wishing to conduct IFR flights within advisory airspace, but not electing to use the air traffic advisory service, are nevertheless to submit a flight plan, and notify changes made thereto to the unit providing that service.
- (c) ATS units providing air traffic advisory service:
 - (1) *advise* the aircraft to depart at the time specified and to cruise at the levels indicated in the flight plan if it does not foresee any conflict with other known traffic;

- (2) *suggest* to aircraft a course of action by which a potential hazard may be avoided, giving priority to an aircraft already in advisory airspace over other aircraft desiring to enter such advisory airspace; and
- (3) *pass* to aircraft traffic information comprising the same information as that prescribed for area control service. (UK Reg (EU) No 923/2012 Article 2(27) GM1)

Air traffic control (ATC) clearance Authorisation for an aircraft to proceed under conditions specified by an air traffic control unit. (UK Reg (EU) No 923/2012 Article 2(28))

Note.

- (a) For convenience, the term ‘air traffic control clearance’ is frequently abbreviated to ‘clearance’ when used in appropriate contexts.
- (b) The abbreviated term ‘clearance’ may be prefixed by the words ‘taxi’, ‘take-off’, ‘departure’, ‘en route’, ‘approach’ or ‘landing’ to indicate the particular portion of flight to which the air traffic control clearance relates. (UK Reg (EU) No 923/2012 Article 2(28) GM1)

Air traffic control instruction Directives issued by air traffic control for the purpose of requiring a pilot to take a specific action. (UK Reg (EU) No 923/2012 Article 2(29))

Air traffic control service A service provided for the purpose of preventing collisions between aircraft, and on the manoeuvring area between aircraft and obstructions; and expediting and maintaining an orderly flow of traffic. (UK Reg (EU) No 923/2012 Article 2(30))

Air traffic control unit A generic term meaning variously, area control centre, approach control unit or aerodrome control tower. (UK Reg (EU) No 923/2012 Article 2(31))

Air traffic flow management A function established with the objective of contributing to a safe, orderly and expeditious flow of air traffic by ensuring that ATC capacity is utilised to the maximum extent possible, and that the traffic volume is compatible with the capacities declared by the appropriate ATS providers. (UK Reg (EC) No 549/2004 Article 2(9))

Air traffic management (ATM) The aggregation of the airborne and ground-based functions (air traffic services, airspace management and air traffic flow management) required to ensure the safe and efficient movement of aircraft during all phases of operations. (UK Reg (EC) No 549/2004 Article 2(10))

Note. The use of the term ‘aircraft’ above includes UAS/RPAS; thus ATM includes the management of these aircraft which has been referred to as ‘UAS traffic management (UTM)’. See the definition of UTM.

Air Traffic Management safety questionnaire A questionnaire that is required to be completed by airspace change sponsors making applications for the provision of required navigational performance instrument approach procedures without an approach control

service, designed to give the CAA a clear picture of the environment in which the IAP is proposed to be employed and the likely safety mitigations a sponsor may need to consider utilising in their safety argument. (CAA)

Air traffic service (ATS) A generic term meaning variously, flight information service, alerting service, air traffic advisory service, air traffic control service (area control service, approach control service or aerodrome control service). (UK Reg (EU) No 923/2012 Article 2(32))

Air traffic service equipment Ground based equipment, including an aeronautical radio station, used or intended to be used in connection with the provision of a service to an aircraft in flight or on the ground which equipment is not otherwise approved by or under [the ANO] but excluding:

- (a) any public electronic communications network; and
- (b) any equipment concerning which the CAA has made a direction that it is not air traffic service equipment for the purposes of Articles 205 and 206. (ANO 2016 Schedule 1)

Air traffic services (ATS) airspaces Airspaces of defined dimensions, alphabetically designated, within which specific types of flights may operate and for which air traffic services and rules of operation are specified. (UK Reg (EU) No 923/2012 Article 2(33))

Air traffic services (ATS) reporting office (ARO) A unit established for the purpose of receiving reports concerning air traffic services and flight plans submitted before departure. (UK Reg (EU) No 923/2012 Article 2(34))

Note. An air traffic services reporting office may be established as a separate unit or combined with an existing unit, such as another air traffic services unit, or a unit of the aeronautical information service. (UK Reg (EU) No 923/2012 Article 2(34) GM1)

Air traffic services (ATS) surveillance service A service provided directly by means of an ATS surveillance system. (UK Reg (EU) No 923/2012 Article 2(34a))

Air traffic services (ATS) unit A generic term meaning, variously, air traffic control unit, flight information centre, aerodrome flight information service unit or air traffic services reporting office. (UK Reg (EU) No 923/2012 Article 2(35))

Airway A control area or portion thereof established in the form of a corridor. (UK Reg (EU) No 923/2012 Article 2(36))

ALERFA The code word used to designate an alert phase. (ICAO PANS-ATM (Doc 4444))

Alert phase A situation wherein apprehension exists as to the safety of an aircraft and its occupants. (ICAO PANS-ATM (Doc 4444))

Alerting service A service provided to notify appropriate organisations regarding aircraft in need of search and rescue aid, and assist such organisations as required. (UK Reg (EU) No 923/2012 Article 2(37))

Alternate aerodrome An aerodrome to which an aircraft may proceed when it becomes either impossible or inadvisable to proceed to or to land at the aerodrome of intended landing, where the necessary services and facilities are available, where aircraft performance requirements can be met and which is operational at the expected time of use. Alternate aerodromes include the following:

- (a) take-off alternate: an alternate aerodrome at which an aircraft would be able to land should this become necessary shortly after take-off and it is not possible to use the aerodrome of departure;
- (b) en-route alternate: an alternate aerodrome at which an aircraft would be able to land in the event that a diversion becomes necessary while en route;
- (c) destination alternate: an alternate aerodrome at which an aircraft would be able to land should it become either impossible or inadvisable to land at the aerodrome of intended landing. (UK Reg (EU) No 923/2012 Article 2(38))

Note. The aerodrome from which a flight departs may also be an en-route or a destination alternate aerodrome for that flight. (UK Reg (EU) No 923/2012 Article 2(38) GM1)

Altitude The vertical distance of a level, a point or object considered as a point, measured from mean sea level. (UK Reg (EU) No 923/2012 Article 2(39))

Note.

- (a) A pressure type altimeter calibrated in accordance with the Standard Atmosphere when set to a QNH altimeter setting will indicate altitude (above the mean sea level).
- (b) The term 'altitude' indicates altimetric rather than geometric altitude. (UK Reg (EU) No 923/2012 Article 2(39) GM1)

AMC Managed Area (AMA) A volume of airspace that is routinely managed by the Airspace Management Cell (AMC). (CAP 740)

Applicability and Policy Alignment Check (APAC) The process for checking with the CAA whether a proposed change to the UK Aeronautical Information Publication is administrative in nature and can be progressed by submitting an aeronautical information publication change request directly to the UK Aeronautical Information Service. (CAA)

Approach and Landing Operations With Vertical Guidance An instrument approach and landing which utilises lateral and vertical guidance but does not meet the requirements established for precision approach and landing operations. (ICAO Annex 6 Vol I)

Approach control service Air traffic control service for arriving or departing controlled flights. (UK Reg (EU) No 923/2012 Article 2(40))

Approach control unit A unit established to provide air traffic control service to controlled flights arriving at, or departing from, one or more aerodromes. (UK Reg (EU) No 923/2012 Article 2(41))

Note. The purpose of the definition is to describe the specific services associated to approach control unit. This does not preclude the possibility for an approach control unit to provide air traffic control service to flights other than those arriving or departing. (UK Reg (EU) No 923/2012 Article 2(41) GM1)

Approach sequence The order in which two or more aircraft are cleared to approach to land at the aerodrome. (ICAO PANS-ATM (Doc 4444))

Approval request A request for clearance made by an ACC when an aircraft will be entering the controlled or advisory airspace of an adjacent ACC in less than 15 minutes, and the first designated reporting point is in the adjacent area. (CAA)

Approved departure time An allocated take-off time calculated from the elapsed flight time between the aerodrome of departure and the point at which the regulated flow is effective. (CAA)

Approved Procedure Design Organisation (APDO) An Instrument Flight Procedure (IFP) Design Service Provider approved in the UK for the provision of IFP Design Service. (CAP 785A)

Apron A defined area, intended to accommodate aircraft for purposes of loading or unloading passengers, mail or cargo, fuelling, parking or maintenance. (UK Reg (EU) No 923/2012 Article 2(42))

Apron Management Service A service provided to regulate the activities and the movement of aircraft and vehicles on an apron. (ICAO PANS-ATM (Doc 4444))

Area control centre (ACC) An Air Traffic Control unit established to provide an air traffic control service to controlled flights in control areas under its jurisdiction. (UK Reg (EU) No 923/2012 Article 2(43))

Area control service An Air Traffic Control service for controlled flights in control areas. (UK Reg (EU) No 923/2012 Article 2(44))

Area navigation (RNAV) A method of navigation which permits aircraft operation on any desired flight path within the coverage of station-referenced navigation aids or within the limits of the capability of self-contained aids, or a combination of these. (UK Reg (EU) No 923/2012 Article 2(45))

Note. Area navigation includes performance-based navigation as well as other operations that do not meet the definition of performance-based navigation. (UK Reg (EU) No 923/2012 Article 2(45) GM1)

Arrival routes Routes identified in an instrument approach procedure by which aircraft may proceed from the En-route phase of flight to an initial approach fix. (ICAO Annex 4)

ATC unit terrain safe level The applicable level as published in ATC unit procedures, that ensures IFR terrain clearance requirements.

Note. This may include: ATC Surveillance Minimum Altitude Areas, Radar Vector Charts, ADR levels, en-route ATC safety altitudes or sector safety altitudes. (CAP 774)

ATS Message Handling System (AMHS) The set of computing and communication resources implemented by ATS organisations to provide the ATS message handling service. (ICAO Annex 10 Vol 3)

ATS route A specified route designed for channelling the flow of traffic as necessary for the provision of air traffic services. (UK Reg (EU) No 923/2012 Article 2(46))

Note.

- (a) Includes airways, advisory routes, controlled or uncontrolled route, arrival or departure route, etc.
- (b) An ATS route is defined by route specifications which include an ATS route designator, the track to or from significant points (waypoints), distance between significant points, reporting requirements, and as determined by the competent authority, the lowest safe altitude. (UK Reg (EU) No 923/2012 Article 2(46) GM1)

ATS surveillance system A generic term meaning variously, ADS-B, PSR, SSR or any comparable ground-based system that enables the identification of aircraft.

Note. A comparable ground-based system is one that has been demonstrated, by comparative assessment or other methodology, to have a level of safety and performance equal to or better than monopulse SSR. (ICAO PANS-ATM (Doc 4444))

Aurora Data Originators Portal Part of the Aeronautical Information Management System used by NATS that allows authorised users to raise proposals to change data and information in the UK Aeronautical Information Publication for which they are responsible. (NATS AIS)

Automatic dependent surveillance – broadcast (ADS-B) A means by which aircraft, aerodrome vehicles and other objects can automatically transmit and/or receive data such as identification, position and additional data, as appropriate, in a broadcast mode via a data link. (UK Reg (EU) No 923/2012 Article 2(47))

Automatic dependent surveillance – contract (ADS-C) A means by which the terms of an ADS-C agreement will be exchanged between the ground system and the aircraft, via a data link, specifying under what conditions ADS-C reports would be initiated, and what data would be contained in the reports. (UK Reg (EU) No 923/2012 Article 2(48))

Note. The abbreviated term ‘ADS-C’ is commonly used to refer to ADS event contract, ADS demand contract, ADS periodic contract, or an emergency mode. (UK Reg (EU) No 923/2012 Article 2(48) GM1)

Automatic dependent surveillance – contract (ADS-C) agreement A reporting plan which establishes the conditions of ADS-C data reporting (i.e. data required by the air traffic services unit and frequency of ADS-C reports which have to be agreed to, prior to using ADS-C in the provision of air traffic services). (UK Reg (EU) No 923/2012 Article 2(48a))

Automatic terminal information service (ATIS) The automatic provision of current, routine information to arriving and departing aircraft throughout 24 hours or a specified portion thereof:

- (1) Data link-automatic terminal information service (D-ATIS) means the provision of ATIS via data link
- (2) Voice-automatic terminal information service (Voice-ATIS) means the provision of ATIS by means of continuous and repetitive voice broadcasts. (UK Reg (EU) No 923/2012 Article 2(49))

B

Backtrack To taxi on a runway-in-use, in the opposite direction to the aircraft's take-off or landing direction. (CAA)

Base Turn A turn executed by the aircraft during the initial approach between the end of the outbound track and the beginning of the intermediate or final approach track. These tracks are not reciprocal. (ICAO Annex 11)

Basic Service A Basic Service is an ATS provided for the purpose of giving advice and information useful for the safe and efficient conduct of flights. This may include weather information, changes of serviceability of facilities, conditions at aerodromes, general airspace activity information, and any other information likely to affect safety. The avoidance of other traffic is solely the pilot's responsibility. (CAP 774)

Beyond visual line of sight operation Means a type of UAS operation which is not conducted in VLOS (UK Reg (EU) 2019/947 Article 2(8))

Blind Transmission A transmission from one station to another station in circumstances where two-way communication cannot be established but where it is believed that the called station is able to receive the transmission. (ICAO Annex 10 Vol II)

Broadcast A transmission of information relating to air navigation that is not addressed to a specific station or stations. (ICAO Annex 10 Vol II)

C

Ceiling The height above the ground or water of the base of the lowest layer of cloud below 6 000 m (20 000 ft) covering more than half the sky. (UK Reg (EU) No 923/2012 Article 2(50))

Change-over point The point at which an aircraft navigating on an ATS route segment defined by reference to very high frequency omnidirectional radio ranges is expected to transfer its primary navigational reference from the facility behind the aircraft to the next facility ahead of the aircraft. (UK Reg (EU) No 923/2012 Article 2(51))

Note. Change-over points are established to provide the optimum balance in respect of signal strength and quality between ground facilities at all levels to be used and to ensure a common source of azimuth guidance for all aircraft operating along the same portion of a route segment. (UK Reg (EU) No 923/2012 Article 2(51) GM1)

Circling approach An extension of an instrument approach procedure which provides for visual circling of the aerodrome prior to landing. (ICAO PANS-OPS Vol I (Doc 8168))

Clearance limit The point to which an aircraft is granted an air traffic control clearance. (UK Reg (EU) No 923/2012 Article 2(52))

Clearway A defined rectangular area on the ground or water under the control of the appropriate authority, selected or prepared as a suitable area over which an aircraft may make a portion of its initial climb to a specified height. (ICAO Annex 4)

Cloud of operational significance A cloud with the height of cloud base below 1 500 m (5 000 ft) or below the highest minimum sector altitude, whichever is greater, or a cumulonimbus cloud or a towering cumulus cloud at any height. (UK Reg (EU) No 923/2012 Article 2(53))

Code (SSR) The number assigned to a particular multiple pulse reply signal transmitted by a transponder in Mode A or Mode C. (UK Reg (EU) No 923/2012 Article 2(54))

Communications, navigation and surveillance (CNS) infrastructure Technological infrastructure supporting air traffic service provision. (CAA)

Competent authority The authority designated by the Member State as competent to ensure compliance with the requirements of this Regulation. (UK Reg (EU) No 923/2012 Article 2(55))

Conditional route (CDR) An ATS route that is only available for flight planning and use under specified conditions. (EUROCONTROL Airspace Management (ASM) Handbook)

Note. A CDR may have more than one category, and those categories may change at specified times.

Contact point The position, time or level at which an arriving aircraft is to establish communication with approach control. (CAA)

Continuous climb (or descent) operations (CCO/CDO) Allow departing or arriving aircraft to climb or descend continuously, to the greatest extent possible, in order to deliver environmental and economic benefits. (CAA)

Control area (CTA) Controlled airspace extending upwards from a specified limit above the earth. (UK Reg (EU) No 923/2012 Article 2(56))

Control zone (CTR) Controlled airspace extending upwards from the surface of the earth to a specified upper limit. (UK Reg (EU) No 923/2012 Article 2(61))

Controlled aerodrome An aerodrome at which air traffic control service is provided to aerodrome traffic regardless whether or not a control zone exists. (UK Reg (EU) No 923/2012 Article 2(57))

Controlled airspace (CAS) Airspace of defined dimensions within which air traffic control service is provided in accordance with the airspace classification. (UK Reg (EU) No 923/2012 Article 2(58))

Note. Controlled airspace is a generic term which covers ATS airspace Classes A, B, C, D and E. (UK Reg (EU) No 923/2012 Article 2(58) GM1)

Controlled flight Any flight which is subject to an air traffic control clearance. (UK Reg (EU) No 923/2012 Article 2(59))

Controller A generic term encompassing: civil and MOD air traffic controllers, ASACS weapons controllers, and any other military personnel who are trained, authorised and certified to provide some or all of the suite of services that comprise UK FIS. (CAP 774)

Controller overload An ATC situation during which a controller considers they experienced excessive workload to the point where the safety of aircraft under their control was, or could have been, compromised. (CAA)

Controller-pilot data link communications (CPDLC) A means of communication between controller and pilot, using data link for ATC communications. (UK Reg (EU) No 923/2012 Article 2(60))

Co-ordination The act of negotiation between two or more parties each vested with the authority to make executive decisions appropriate to the task being discharged. (CAP 493)

CPDLC message Information exchanged between an airborne system and its ground counterpart. A CPDLC message consists of a single message element or a combination of message elements conveyed in a single transmission by the initiator. (ICAO PANS-ATM (Doc 4444))

CPDLC message set A list of standard message elements and free text message elements. (ICAO PANS-ATM (Doc 4444))

Cross border area (CBA) An airspace restriction or reservation established over international borders for specific operational requirements. This may take the form of a Temporary Segregated Area (TSA) or a Temporary Reserved Area (TRA). (EUROCONTROL Airspace Management (ASM) Handbook)

Cruise climb An aeroplane cruising technique resulting in a net increase in altitude as the aeroplane mass decreases. (UK Reg (EU) No 923/2012 Article 2(62))

Cruising level A level maintained during a significant portion of a flight. (UK Reg (EU) No 923/2012 Article 2(63))

Current flight plan (CPL) The flight plan, including changes, if any, brought about by subsequent clearances. (UK Reg (EU) No 923/2012 Article 2(64))

D

Danger area Airspace of defined dimensions within which activities dangerous to the flight of aircraft may exist at specified times. (UK Reg (EU) No 923/2012 Article 2(65))

Data convention An agreed set of rules governing the manner or sequence in which a set of data may be combined into a meaningful communication. (ICAO PANS-ATM (Doc 4444))

Data link communications A form of communication intended for the exchange of messages via a data link. (UK Reg (EU) No 923/2012 Article 2(66))

Data link initiation capability (DLIC) A data link application that provides the ability to exchange addresses, names and version numbers necessary to initiate data link applications. (ICAO PANS-ATM (Doc 4444))

Data processing A systematic sequence of operations performed on data. (ICAO PANS-ATM (Doc 4444))

Note.— Examples of operations are the merging, sorting, computing or any other transformation or rearrangement with the object of extracting or revising information, or of altering the representation of information.

Datum Any quantity or set of quantities that may serve as a reference or basis for the calculation of other quantities. (UK Reg (EU) No 923/2012 Article 2(67))

Decision altitude/height In relation to the operation of an aircraft at an aerodrome means the altitude/height in a precision approach at which a missed approach must be initiated if the required visual reference to continue that approach has not been established. (* ANO 2016 Schedule 1)

Declared capacity A measure of the ability of the ATC system or any of its subsystems or operating positions to provide service to aircraft during normal activities. It is expressed as the number of aircraft entering a specified portion of airspace in a given period of time, taking due account of weather, ATC unit configuration, staff and equipment available, and any other factors which may affect the workload of the controller responsible for the airspace. (ICAO Annex 11)

Deconfliction advice Advice issued by a controller to pilots, aimed at achieving notified deconfliction minima from other traffic in Class F/G airspace. (CAP 774)

Deconfliction instruction Instruction issued by a controller to pilots in receipt of a Procedural Service, which if complied with, shall achieve deconfliction minima against other aircraft participating in the Procedural Service. (CAP 774)

Deconfliction minima The defined vertical, lateral or time minima relevant to the provision of UK Flight Information Services. (CAP 774)

Deconfliction Service A Deconfliction Service is a surveillance based ATS where, in addition to the provisions of a Basic Service, the controller provides specific surveillance derived traffic information and issues headings and/or levels aimed at achieving planned deconfliction minima against all observed aircraft in Class F/G airspace, or for positioning and/or sequencing. However, the avoidance of other traffic is ultimately the pilot's responsibility. (CAP 774)

Defence Airspace and Air Traffic Management (DAATM) The DAATM is a pan-Defence organization, which works directly for the RAF Assistant Chief of the Air Staff. The DAATM acts as the MOD representative organization, in close collaboration with the CAA, within Europe. It is responsible for developing and addressing all Ministry of Defence airspace requirements, including developing and coordinating a common Defence position in response to domestic airspace change proposals within the UK. (CAP 740 / RA 3201)

Dependent parallel approaches Simultaneous approaches to parallel or near-parallel instrument runways where ATS surveillance system separation minima between aircraft on adjacent extended runway centre lines are prescribed. (ICAO PANS-ATM (Doc 4444))

DETRESFA The code word used to designate a distress phase. (ICAO PANS-ATM (Doc 4444))

Discrete code A four-digit SSR code with the last two digits not being "00". (ICAO PANS-ATM (Doc 4444))

Disruptive passenger A passenger who fails to respect the rules of conduct at an airport or on board an aircraft or to follow the instructions of the airport staff or crew members and thereby disturbs the good order and discipline at an airport or on board the aircraft. (ICAO Annex 17)

Distress phase A situation wherein there is reasonable certainty that an aircraft and its occupants are threatened by grave and imminent danger or require immediate assistance. (ICAO PANS-ATM (Doc 4444))

Downstream clearance A clearance issued to an aircraft by an air traffic control unit that is not the current controlling authority of that aircraft. (UK Reg (EU) No 923/2012 Article 2(68))

Duty Engineering Officer (DEO) Generic term meaning the person(s) responsible for the specified task, namely engineering/telecommunications/ surveillance systems etc. As appropriate, locally established personnel shall be specified in unit local procedures. (CAA)

E

Electronic Conspicuity An umbrella term for a range of technologies that can help airspace users to be more aware of other aircraft in the same airspace. It includes transponders and radios. (CAP 1391)

Elevation The vertical distance of a point or level on, or affixed to, the surface of the earth measured from mean sea level. (ICAO Annex 3)

Emergency phase A generic term meaning, as the case may be, uncertainty phase, alert phase or distress phase. (ICAO PANS-ATM (Doc 4444))

Entry point The first airways/advisory airspace reporting point over which a flight passes on entering an FIR. (MATS Part 1)

Estimated elapsed time The estimated time required to proceed from one significant point to another. (UK Reg (EU) No 923/2012 Article 2(69))

Estimated off-block time The estimated time at which the aircraft will commence movement associated with departure. (UK Reg (EU) No 923/2012 Article 2(70))

Estimated time of arrival (ETA) For IFR flights, the time at which it is estimated that the aircraft will arrive over that designated point, defined by reference to navigation aids, from which it is intended that an instrument approach procedure will be commenced, or, if no navigation aid is associated with the aerodrome, the time at which the aircraft will arrive over the aerodrome. For visual flight rules (VFR) flights, the time at which it is estimated that the aircraft will arrive over the aerodrome. (UK Reg (EU) No 923/2012 Article 2(71))

Exit Point The last airways/advisory airspace reporting point over which a flight passes before leaving an FIR. (MATS Part 1)

Expected approach time (EAT) The time at which ATC expects that an arriving aircraft, following a delay, will leave the holding fix to complete its approach for a landing. The actual time of leaving the holding fix will depend upon the approach clearance. (UK Reg (EU) No 923/2012 Article 2(72))

F

Filed flight plan (FPL) The flight plan as filed with an ATS unit by the pilot or a designated representative, without any subsequent changes. (UK Reg (EU) No 923/2012 Article 2(73))

Final approach That part of an instrument approach procedure which commences at the specified final approach fix or point, or where such a fix or point is not specified:

- (1) at the end of the last procedure turn, base turn, or inbound turn of a racetrack procedure, if specified, or
- (2) at the point of interception of the last track specified in the approach procedure; and ends at a point in the vicinity of an aerodrome from which:
 - (a) a landing can be made; or
 - (b) a missed approach procedure is initiated. (ICAO Annex 11)

Flexible use of airspace (FUA) Concept Based on the fundamental principle that airspace should not be designated as either pure civil or military airspace, but rather be considered as one continuum in which all user requirements have to be accommodated to the extent possible. (EUROCONTROL ASM Handbook)

Flight behaviours The way that a flight behaves (i.e. profile, track, altitude) in a particular situation or under particular conditions. (CAA)

Flight crew member A licensed crew member charged with duties essential to the operation of an aircraft during a flight duty period. (UK Reg (EU) No 923/2012 Article 2(74))

Flight information centre (FIC) A unit established to provide flight information service and alerting service. (UK Reg (EU) No 923/2012 Article 2(75))

Flight information region (FIR) Airspace of defined dimensions within which flight information service and alerting service are provided. (UK Reg (EU) No 923/2012 Article 2(76))

Flight information service (FIS) A service provided for the purpose of giving advice and information useful for the safe and efficient conduct of flights. (UK Reg (EU) No 923/2012 Article 2(77))

Flight information service officer (FISO) A Flight Information Service Officer at any aerodrome or area control centre. (CAA)

Flight level (FL) A surface of constant atmospheric pressure which is related to a specific pressure datum, 1013.2 hectopascals (hPa), and is separated from other such surfaces by specific pressure intervals. (UK Reg (EU) No 923/2012 Article 2(78))

Note. A pressure type altimeter calibrated in accordance with the Standard Atmosphere, when set to a pressure of 1 013.2 hPa, may be used to indicate flight levels. (UK Reg (EU) No 923/2012 Article 2(78) GM1)

Flight path monitoring The use of ATS surveillance systems for the purpose of providing aircraft with information and advice relative to significant deviations from nominal flight path, including deviations from the terms of their ATC clearance. (ICAO PANS ATM (Doc 4444))

Flight plan Specified information provided to ATSUs relative to an intended flight or portion of a flight of an aircraft. (UK Reg (EU) No 923/2012 Article 2(79))

Flight plan Buffer Zone (FBZ) An airspace volume, which may be established in association to a reserved/restricted area. The FBZ defines the lateral, vertical and time limits for the purpose of validating submitted IFR FPLs when the associated area is activated or planned to be activated. (Eurocontrol European Route Network Improvement Plan Part 1)

Flight procedures Part of the airspace design. A set of predetermined segments intended to be followed by a pilot when arriving to or departing from an aerodrome. (CAA)

Flight rules Aircraft can operate under Visual Flight Rules (VFR) or Instrument Flight Rules (IFR). There is also an intermediate form, Special Visual Flight Rules (SVFR). (CAA)

Flight visibility The visibility forward from the cockpit of an aircraft in flight. (UK Reg (EU) No 923/2012 Article 2(80))

Forecast A statement of expected meteorological conditions for a specified time or period, and for a specified area or portion of airspace. (UK Reg (EU) No 923/2012 Article 2(81))

FRA Arrival Connecting Point (A) A published significant point to which FRA operations are allowed for arriving traffic to specific aerodromes. (Eurocontrol European Route Network Improvement Plan Part 1)

FRA Departure Connecting Point (D) A published significant point from which FRA operations are allowed for departing traffic from specific aerodromes. (Eurocontrol European Route Network Improvement Plan Part 1)

FRA Horizontal Entry Point (E) A published significant point on the horizontal boundary of the Free Route Airspace from which FRA operations are allowed. (Eurocontrol European Route Network Improvement Plan Part 1)

FRA Horizontal Exit Point (X) A published significant point on the horizontal boundary of the Free Route Airspace to which FRA operations are allowed. (Eurocontrol European Route Network Improvement Plan Part 1)

FRA Intermediate Point (I) A published significant point or unpublished point, defined by geographical coordinates or by bearing and distance via which FRA operations are allowed. (Eurocontrol European Route Network Improvement Plan Part 1)

Free Route Airspace (FRA) A specified airspace within which users may freely plan a route between a defined entry point and a defined exit point, with the possibility to route via intermediate (published or unpublished) significant points, without reference to the ATS route network, subject to airspace availability. Within this airspace, flights remain subject to air traffic control. (Eurocontrol European Route Network Improvement Plan Part 1)

Free text message element Part of a message that does not conform to any standard message element in the PANS-ATM (Doc 4444). (ICAO PANS-ATM (Doc 4444))

G

General air traffic (GAT) Means all movements of civil aircraft, as well as all movements of State aircraft (including military, customs and police aircraft) when these movements are carried out in conformity with the procedures of the ICAO. (UK Reg (EU) No 549/2004 Article 2(26))

Glide path A descent profile determined for vertical guidance during a final approach. (ICAO PANS ATM (Doc 4444))

Global Navigation Satellite System (GNSS) A worldwide position and time determination system that includes one or more satellite constellations, aircraft receivers and system integrity monitoring, augmented as necessary to support the required navigation performance for the intended operation. (CAA)

Ground effect (Rotary-wing) A condition of improved performance (lift) due to the interference of the surface with the airflow pattern of the rotor system when a helicopter or other VTOL aircraft is operating near the ground.

Note. Rotor efficiency is increased by ground effect to a height of about one rotor diameter for most helicopters. (ICAO PANS ATM (Doc 4444))

Ground visibility The visibility at an aerodrome, as reported by an accredited observer or by automatic systems. (UK Reg (EU) No 923/2012 Article 2(82))

H

Hazard Means any condition, event, or circumstance which could induce a harmful effect (UK Regulation (EU) 2017/373 Annex 1(61))

Heading The direction in which the longitudinal axis of an aircraft is pointed, usually expressed in degrees from North (true, magnetic or compass). (UK Reg (EU) No 923/2012 Article 2(83))

Height The vertical distance of a level, a point or an object considered as a point, measured from a specified datum. (UK Reg (EU) No 923/2012 Article 2(84))

Note.

- (a) A pressure type altimeter calibrated in accordance with the Standard Atmosphere, when set to a QFE altimeter setting, will indicate height (above the QFE reference datum).
- (b) The term 'height' indicates altimetric rather than geometric height. (UK Reg (EU) No 923/2012 Article 2(84) GM1)

Helicopter A heavier-than-air aircraft supported in flight chiefly by the reactions of the air on one or more power-driven rotors on substantially vertical axes. (UK Reg (EU) No 923/2012 Article 2(85))

High seas airspace Airspace beyond land territory and territorial seas, as specified in the United Nations Convention on the Law of the Sea (Montego Bay, 1982). (UK Reg (EU) No 923/2012 Article 2(86))

Holding fix A geographical location that serves as a reference for a holding procedure. (ICAO PANS ATM (Doc 4444))

Holding procedure A predetermined manoeuvre which keeps an aircraft within a specified airspace whilst awaiting further clearance. (ICAO Annex 4)

Hot spot A location on an aerodrome movement area with a history or potential risk of collision or runway incursion, and where heightened attention by pilots/drivers is necessary. (ICAO Annex 4)

I

(Radar) Identification The situation which exists when the position indication of a particular aircraft is seen on a situation display and positively identified. (ICAO PANS-ATM (Doc 4444))

IFR The symbol used to designate the instrument flight rules. (UK Reg (EU) No 923/2012 Article 2(87))

IFR flight A flight conducted in accordance with the Instrument Flight Rules. (UK Reg (EU) No 923/2012 Article 2(88))

IMC The symbol used to designate instrument meteorological conditions. (UK Reg (EU) No 923/2012 Article 2(89))

INCERFA The code word used to designate an uncertainty phase. (ICAO PANS-ATM (Doc 4444))

Independent parallel approaches Simultaneous approaches to parallel or near-parallel instrument runways where ATS surveillance system separation minima between aircraft on adjacent extended runway centre lines are not prescribed. (ICAO PANS-ATM (Doc 4444))

Independent parallel departures Simultaneous departures from parallel or near-parallel instrument runways. (ICAO PANS-ATM (Doc 4444))

Initial approach segment That segment of an instrument approach procedure between the initial approach fix and the intermediate approach fix or, where applicable, the final approach fix or point. (ICAO PANS-ATM (Doc 4444))

Instrument approach operation An approach and landing using instruments for navigation guidance based on an instrument approach procedure. There are two methods for executing instrument approach operations:

- (a) a two-dimensional (2D) instrument approach operation, using lateral navigation guidance only; and
- (b) a three-dimensional (3D) instrument approach operation, using both lateral and vertical navigation guidance. (UK Reg (EU) No 923/2012 Article 2(89a))

Note. Lateral and vertical guidance utilised in an instrument approach procedure refers to the guidance provided either by:

- (a) a ground-based navigation aid; or
- (b) computer-generated navigation data from ground-based, space-based, self-contained navigation aids or a combination of these. (UK Reg (EU) No 923/2012 Article 2(89a) GM1)

Instrument approach procedure (IAP) A series of predetermined manoeuvres by reference to flight instruments with specified protection from obstacles from the initial

approach fix, or where applicable, from the beginning of a defined arrival route to a point from which a landing can be completed and thereafter, if a landing is not completed, to a position at which holding or en-route obstacle clearance criteria apply. Instrument approach procedures are classified as follows:

- (a) Non-precision approach (NPA) procedure. An instrument approach procedure designed for 2D instrument approach operations Type A.
- (b) Approach procedure with vertical guidance (APV). A performance-based navigation (PBN) instrument approach procedure designed for 3D instrument approach operations Type A.
- (c) Precision approach (PA) procedure. An instrument approach procedure based on navigation systems (ILS, MLS, GLS and SBAS Cat I) designed for 3D instrument approach operations Type A or B. (UK Reg (EU) No 923/2012 Article 2(90))

Note. Instrument approach operations are classified based on the designed lowest operating minima below which an approach operation should only be continued with the required visual reference as follows:

- (a) Type A: a minimum descent height or decision height (DH) at or above 75 m (250 ft); and
- (b) Type B: a DH below 75 m (250 ft). Type B instrument approach operations are categorised as:
 - (1) Category I (CAT I): a DH not lower than 60 m (200 ft) and with either a visibility not less than 800 m or a runway visual range (RVR) not less than 550 m;
 - (2) Category II (CAT II): a DH lower than 60 m (200 ft) but not lower than 30 m (100 ft) and an RVR not less than 300 m;
 - (3) Category IIIA (CAT IIIA): a DH lower than 30 m (100 ft) or no DH and an RVR not less than 175 m;
 - (4) Category IIIB (CAT IIIB): a DH lower than 15 m (50 ft) or no DH and an RVR less than 175 m but not less than 50 m; and
 - (5) Category IIIC (CAT IIIC): no DH and no RVR limitations.

Where DH and RVR fall into different categories of operation, the instrument approach operation would be conducted in accordance with the requirements of the most demanding category (e.g. an operation with a DH in the range of CAT IIIA but with an RVR in the range of CAT IIIB would be considered a CAT IIIB operation, or an operation with a DH in the range of CAT II but with an RVR in the range of CAT I would be considered a CAT II operation).

The required visual reference means that section of the visual aids or of the approach area which should have been in view for sufficient time for the pilot to have made an assessment of the aircraft position and rate of change of position, in relation to the desired flight path. In the case of a circling approach operation, the required visual reference is the runway environment. (UK Reg (EU) No 923/2012 Article 2(90) GM1)

Instrument flight procedure (IFP) A standard instrument departure (SID), a standard instrument arrival (STAR), an approach transition, an initial approach procedure or an instrument approach procedure (IAP). (CAP 785A)

Instrument Flight Rules (IFR) The rules under which a pilot can fly and navigate an aircraft, in certain weather conditions where visibility is below the minima for visual flight, primarily through use of on-board instruments. (CAA)

Instrument meteorological conditions (IMC) Meteorological conditions expressed in terms of visibility, distance from cloud, and ceiling, less than the minima specified for Visual Meteorological Conditions (VMC). (UK Reg (EU) No 923/2012 Article 2(91))

Intermediate approach segment That part of an instrument approach procedure between either the intermediate fix and the final approach fix or point, or between the end of a reversal, racetrack or dead reckoning track procedure and the final approach fix or point, as appropriate. (ICAO Annex 4)

Note. In radar approaches, no distinction is made between initial and intermediate approach.

Intermediate holding position A designated position intended for traffic control at which taxiing aircraft and vehicles shall stop and hold until further cleared to proceed, when so instructed by the aerodrome control tower. (ICAO Annex 14 Vol I)

International Airport Any airport designated by the Contracting State in whose territory it is situated as an airport of entry and departure for international air traffic, where the formalities incident to customs, immigration, public health, animal and plant quarantine and similar procedures are carried out. (ICAO)

International Civil Aviation Organisation (ICAO) An agency of the United Nations responsible for international standards for civil aviation which the UK is bound by international treaty to implement. (CAA)

International Civil Aviation Organisation standards and recommended practices (ICAO SARPs) Technical specifications intended to achieve the highest practicable degree of uniformity in regulations, standards, procedures and organisation in relation to aircraft, personnel, airspace and auxiliary services in all matters in which such uniformity will facilitate and improve air navigation. (CAA)

ITP aircraft An aircraft approved by the State of the Operator to conduct in-trail procedure (ITP) . (ICAO PANS-ATM (Doc 4444))

ITP distance The distance between the ITP aircraft and a reference aircraft as defined by:

- a) aircraft on the same track, the difference in distance to an aircraft calculated common point along a projection of each other's track; or
- b) aircraft on parallel tracks, the distance measured along the track of one of the aircraft using its calculated position and the point abeam the calculated position of the other aircraft.

Note. Reference aircraft refers to one or two aircraft with ADS-B data that meet the ITP criteria described in ICAO Doc 4444 PANS-ATM Paragraph 5.4.2.7 and are indicated to ATC by the ITP aircraft as part of the ITP clearance request. (ICAO PANS-ATM (Doc 4444))

K

Known traffic Traffic, the current flight details and intentions of which are known to the controller/FISO. (CAA)

L

Landing area That part of a movement area intended for the landing or take-off of aircraft. (UK Reg (EU) No 923/2012 Article 2(92))

Launch operator The holder of a licence under the Space Industry Act 2018 authorising a person to carry out spaceflight activities. (Space Industry Regulations 2021)

Level A generic term relating to the vertical position of an aircraft in flight and meaning variously height, altitude or flight level. (UK Reg (EU) No 923/2012 Article 2(93))

Level bust Any unauthorised vertical deviation of more than 200 feet from an assigned level. (CAA)

Location indicator A four-letter code group formulated in accordance with rules prescribed by ICAO and assigned to the location of an aeronautical fixed station. (ICAO PANS-ATM (Doc 4444))

Logon address A specified code used for data link logon to an ATS unit. (ICAO PANS-ATM (Doc 4444))

Lower Airspace Radar Service (LARS) A system of participating Air Traffic Service Units which provide an Air Traffic Service to transit traffic at and below FL 95. (CAA: UK Flight Information Service Guidance)

M

Manoeuvring area The part of an aerodrome to be used for the take-off, landing and taxiing of aircraft, excluding aprons. (UK Reg (EU) No 923/2012 Article 2(94))

Manual of Air Traffic Services (MATS) Contains procedures and information for civil air traffic control officers in the provision of air traffic control services. The Manual of Air Traffic Services is comprised of two parts. (CAA)

Manual of Air Traffic Services (MATS) Part 1 Contains procedures and information applicable to the provision of air traffic services within the UK FIR. The MATS Pt 1 is published by the CAA as CAP 493. (www.caa.co.uk/cap493) (CAA)

Manual of Air Traffic Services (MATS) Part 2 The unit specific instructions to controllers produced by the provider of the air traffic control service. (CAA)

Meteorological information Meteorological report, analysis, forecast, and any other statement relating to existing or expected meteorological conditions. (ICAO PANS-ATM (Doc 4444))

Meteorological office An office designated to provide meteorological service for international air navigation. (ICAO PANS-ATM (Doc 4444))

Meteorological report A statement of observed meteorological conditions related to a specified time and location. (ICAO PANS-ATM (Doc 4444))

Microwave approach An approach executed by an aircraft, utilising a Microwave Landing System (MLS) for guidance. (CAA)

Minimum descent altitude/height (MDA/MDH) In relation to the operation of an aircraft at an aerodrome means the altitude/height in a non-precision approach below which descent may not be made without the required visual reference. (* ANO 2016 Schedule 1)

Minimum fuel A term used to describe a situation in which an aircraft's fuel supply has reached a state where the flight is committed to land at a specific aerodrome and no additional delay can be accepted. (UK Reg (EU) No 923/2012 Article 2(94a))

Note. This is not an emergency situation but merely indicates that an emergency situation is possible, should any undue delay occur.

Minimum sector altitude (MSA) The lowest safe altitude for instrument flight within sectors of an aid, facility or aerodrome which is published in the appropriate approach chart. (CAA)

Missed approach point (MAPt) The point in an instrument approach procedure at or before which the prescribed missed approach procedure must be initiated in order to ensure that the minimum obstacle clearance is not infringed. (ICAO Annex 4)

Missed approach procedure The procedure to be followed if the approach cannot be continued. (ICAO Annex 4)

Mode (SSR) The conventional identifier related to specific functions of the interrogation signals transmitted by an SSR interrogator. There are four modes specified in ICAO Annex 10: A, C, S and intermode. (UK Reg (EU) No 923/2012 Article 2(95))

Model aircraft An unmanned aircraft, other than toy aircraft, having an operating mass not exceeding limits prescribed by the competent authority, that is capable of sustained flight in the atmosphere and that is used exclusively for display or recreational activities. (UK Reg (EU) No 923/2012 Article 2(95a))

Mountainous area An area of changing terrain profile where the changes of terrain elevation exceed 900 m (3 000 ft) within a distance of 18,5 km (10,0 NM). (UK Reg (EU) No 923/2012 Article 2(95b))

Movement area That part of an aerodrome to be used for the take-off, landing and taxiing of aircraft, consisting of the manoeuvring area and the apron(s). (UK Reg (EU) No 923/2012 Article 2(96))

Multilateration (MLAT) system A group of equipment configured to provide position derived from the secondary surveillance radar (SSR) transponder signals (replies or squitters) primarily using time difference of arrival (TDOA) techniques. Additional information, including identification, can be extracted from the received signals. (ICAO PANS-ATM (Doc 4444))

N

National Air Traffic Management Advisory Committee (NATMAC) An advisory body chaired by the CAA with representation across the UK aviation community, consulted for advice and views on airspace management and strategy matters. (CAA)

NATS Formerly National Air Traffic Services. Parent company of NERL (NATS (En Route) plc) and NSL (NATS Services Limited). (www.nats.co.uk) (CAA)

Navigation aid Any visual or electronic device airborne or on the surface which provides point-to-point guidance information or position data to aircraft in flight. (Eurocontrol: Skybrary)

Near-parallel runways Non-intersecting runways whose extended centre lines have an angle of convergence/divergence of 15 degrees or less. (ICAO PANS-ATM (Doc 4444))

Network Manager The entity established under Article 6 of REGULATION (EC) No 551/2004 (the Airspace regulation) as amended by Commission Regulation (EU) No 1070/2009 as to perform the duties provided for in that article and in Commission Implementing Regulation (EU) 2019/123 (the ATM Network Functions regulation) laying down detailed rules for the implementation of air traffic management (ATM) network functions and repealing Commission Regulation (EU) No 677/2011. (Eurocontrol: European Route Network Improvement Plan Part 1)

Night The time between half an hour after sunset and half an hour before sunrise (both times inclusive), sunset and sunrise being determined at surface level. (* ANO 2016 Schedule 1)

Non-standard Planning Zone (NPZ) Is a defined airspace volume within which the planning of FRA DCT trajectories is either not allowed or allowed only for exceptions as described. (Eurocontrol European Route Network Improvement Plan Part 1)

Noise abatement procedures Procedures that minimise the overall exposure to aircraft noise on the ground, including: use of noise preferential runways and routes and noise abatement take-off or approach procedures. (CAA)

Noise preferential route (NPR) Set departure routes followed by aircraft departing from certain airports agreed by Government or the Local Authority, with the aim of providing certainty in respect of, and, where possible, minimising, noise impacts on the ground. Noise Preferential Routes are not decided by the CAA nor covered by the airspace change process. (CAA)

Non-AMC managed area (NAM) A volume of airspace that is not routinely managed by the Airspace Management Cell (AMC). (CAP 740)

Non-deviating status (NDS) A flight category which entails priority handling for certain flights within specified classes of controlled airspace by prior arrangement with controlling authorities. (CAA)

Non-instrument runway A runway intended for the operation of aircraft using visual approach procedures or an instrument approach procedure to a point beyond which the approach may continue in visual meteorological conditions. (CAP 168)

Non-precision approach An instrument approach using non-visual aids for guidance in azimuth or elevation but which is not a precision approach. (* ANO 2016 Schedule 1)

Normal operating zone (NOZ) Airspace of defined dimensions extending to either side of an published instrument approach procedure final approach course or track. Only that half of the normal operating zone adjacent to a no transgression zone (NTZ) is taken into account in independent parallel approaches. (ICAO PANS-ATM (Doc 4444))

NOTAM A notice distributed by means of telecommunication containing information concerning the establishment, condition or change in any aeronautical facility, service, procedure or hazard, the timely knowledge of which is essential to personnel concerned with flight operations. (ICAO PANS-ATM (Doc 4444))

Notified means set out with the authority of the CAA in a document published by or under an arrangement entered into with the CAA and entitled “United Kingdom Notam” or “United Kingdom Aeronautical Information Publication” and for the time being in force. (ANO, Schedule 1)

Notified airspace design Details of airspace structure and procedures published in the UK Aeronautical Information Publication. (CAA)

No transgression zone (NTZ) In the context of independent parallel approaches, a corridor of airspace of defined dimensions located centrally between the two extended runway centre lines, where a penetration by an aircraft requires a controller intervention to manoeuvre any threatened aircraft on the adjacent approach. (ICAO PANS-ATM (Doc 4444))

O

Obstacle All fixed (whether temporary or permanent) and mobile objects, or parts thereof, that are located on an area intended for the surface movement of aircraft; or extend above a defined surface intended to protect aircraft in flight; or stand outside those defined surfaces and that have been assessed as being a hazard to air navigation. (UK Reg (EU) No 923/2012 Article 2(98))

Obstacle clearance altitude/height (OCA/OCH) The lowest altitude or the lowest height above the elevation of the relevant runway threshold or the aerodrome elevation as applicable, used in establishing compliance with the appropriate obstacle clearance criteria.

Note 1. Obstacle clearance altitude is referenced to mean sea level and obstacle clearance height is referenced to the threshold elevation or in the case of non-precision approach procedures to the aerodrome elevation or the threshold elevation if that is more than 2 m (7 ft) below the aerodrome elevation. An obstacle clearance height for a circling approach procedure is referenced to the aerodrome elevation.

Note 2. For convenience when both expressions are used they may be written in the form 'obstacle clearance altitude/height' and abbreviated 'OCA/H'. (ICAO Annex 4)

Off-Route Traffic Encompasses all GAT flying outside the published ATS Routes Network. (EUROCONTROL ASM Handbook)

Note. Within the UK, aircraft are considered to be 'off-route' when not complying with the conditions of 'on-route' flight.

Offshore Aeronautical Service (OAS) See Offshore Communication Service.

Offshore Communication Service (OCS) (Also known as an Offshore Aeronautical Service) A service provided from an offshore installation or UK flagged vessel to helicopters through the use of aeronautical radio stations and non-directional radio beacons located on these installations or vessels. (CAA)

Omnidirectional departure A departure procedure that is designed on the basis that an aircraft maintains the runway direction until it reaches such a height that it can make a turn in any direction and maintain the obstacle clearance prescribed by the procedure. (ANO 2016 Schedule 1)

On-Route Traffic Encompasses all GAT flying along the published ATS Routes Network. (EUROCONTROL ASM Handbook)

Note. Within the UK, aircraft are considered to be 'on-route' when flying along the alignment and within 5 NM of the centre-line of published parameters of an Upper ATS Route (UAR) and other areas defined for the application of reduced co-ordination procedures.

Operating site A site selected by the operator or pilot-in-command for landing, take-off and/or hoist operations. (UK Reg (EU) No 923/2012 Article 2(99))

Operational Air Traffic (OAT) Encompasses all flights which do not comply with the provisions stated for GAT and for which rules and procedures have been specified by appropriate national authorities. (EUROCONTROL ASM Handbook)

Note. OAT can include civil flights such as test-flights, which require some deviation from ICAO rules to satisfy their operational requirements.

Operational Control The exercise of authority over the initiation, continuation, diversion or termination of a flight in the interest of the safety of the aircraft and the regularity and efficiency of the flight. (ICAO)

Order Refers to the Air Navigation Order. (CAA)

P

Performance-based communication (PBC) Communication based on performance specifications applied to the provision of air traffic services.

Note. An RCP specification includes communication performance requirements that are allocated to system components in terms of the communication to be provided and associated transaction time, continuity, availability, integrity, safety and functionality needed for the proposed operation in the context of a particular airspace concept. (ICAO Annex 11)

Performance-based navigation (PBN) Area navigation based on performance requirements for aircraft operating along an ATS route, on an instrument approach procedure or in a designated airspace.

Note. Performance requirements are expressed in navigation specifications (RNAV specification, RNP specification) in terms of accuracy, integrity, continuity, availability and functionality needed for the proposed operation in the context of a particular airspace concept. (ICAO Annex 11)

Performance-based surveillance (PBS) Surveillance based on performance specifications applied to the provision of air traffic services.

Note. An RSP specification includes surveillance performance requirements that are allocated to system components in terms of the surveillance to be provided and associated data delivery time, continuity, availability, integrity, accuracy of the surveillance data, safety and functionality needed for the proposed operation in the context of a particular airspace concept. (ICAO Annex 11)

Pilot-in-command (PIC) The pilot designated by the operator, or in the case of general aviation, the owner, as being in command and charged with the safe conduct of a flight. (UK Reg (EU) No 923/2012 Article 2(100))

Point in space (PinS) A Point-in-Space approach is based on GNSS and is an approach procedure designed for helicopters only. It is aligned with a reference point located to permit subsequent flight manoeuvring or approach and landing using visual manoeuvring in adequate visual conditions to see and avoid obstacles. (Eurocontrol)

Position indication The visual indication, in non-symbolic and/or symbolic form, on a situation display, of the position of an aircraft, aerodrome vehicle or other object. (ICAO PANS-ATM (Doc 4444))

Position symbol The visual indication in symbolic form, on a situation display, of the position of an aircraft, aerodrome vehicle or other object obtained after automatic processing of positional data derived from any source. (ICAO PANS-ATM (Doc 4444))

Precision approach An instrument approach using precision lateral and vertical guidance with minima as determined by the category of operation. (ANO 2016 Schedule 1)

Precision approach radar (PAR) Primary radar equipment used to determine the position of an aircraft during final approach, in terms of lateral and vertical deviations relative to a nominal approach path, and in range relative to touchdown.

Note. Precision approach radars are designated to enable pilots of aircraft to be given guidance by radiocommunication during the final stages of the approach to land. (ICAO PANS-ATM (Doc 4444))

Pressure altitude An atmospheric pressure expressed in terms of altitude which corresponds to that pressure in the Standard Atmosphere, as defined in Annex 8, Part 1 to the Chicago Convention. (UK Reg (EU) No 923/2012 Article 2(101))

Prevailing visibility The greatest visibility value, observed in accordance with the definition of “visibility”, which is reached within at least half the horizon circle or within at least half of the surface of the aerodrome. These areas could comprise contiguous or non- contiguous sectors. (CAA CAP 746)

Primary surveillance radar (PSR) A surveillance radar system which uses reflected radio signals. (ICAO PANS-ATM (Doc 4444))

Problematic use of substances The use of one or more psychoactive substances by aviation personnel in a way that constitutes a direct hazard to the user or endangers the lives, health or welfare of others; and/or causes or worsens an occupational, social, mental or physical problem or disorder. (UK Reg (EU) No 923/2012 Article 2(102))

Procedural control Term used to indicate that information derived from an ATS surveillance system is not required for the provision of air traffic control service. (ICAO PANS-ATM (Doc 4444))

Procedural separation The separation used when providing procedural control. (ICAO PANS-ATM (Doc 4444))

Procedural service A Procedural Service is an ATS where, in addition to the provisions of a Basic Service, the controller provides restrictions, instructions, and approach clearances, which if complied with, shall achieve deconfliction minima against other aircraft participating in the Procedural Service. Neither traffic information nor deconfliction advice can be passed with respect to unknown traffic. (CAP 774)

Procedure turn A manoeuvre in which a turn is made away from a designated track followed by a turn in the opposite direction to permit the aircraft to intercept and proceed along the reciprocal of the designated track.

Note 1. Procedure turns are designated “left” or “right” according to the direction of the initial turn.

Note 2. Procedure turns may be designated as being made either in level flight or while descending, according to the circumstances of each individual procedure. (ICAO PANS-ATM (Doc 4444))

Prohibited area Airspace of defined dimensions, above the land areas or territorial waters of a State, within which the flight of aircraft is prohibited. (UK Reg (EU) No 923/2012 Article 2(103))

PSR blip The visual indication, in non-symbolic form, on a situation display of the position of an aircraft obtained by primary radar. (ICAO PANS-ATM (Doc 4444))

Psychoactive substances Term used to mean alcohol, opioids, cannabinoids, sedatives and hypnotics, cocaine, other psychostimulants, hallucinogens, and volatile solvents, whereas caffeine and tobacco are excluded. (UK Reg (EU) No 923/2012 Article 2(104))

R

Racetrack procedure A procedure designed to enable the aircraft to reduce altitude during the initial approach segment and/or establish the aircraft inbound when the entry into a reversal procedure is not practical. (ICAO PANS-OPS Vol I (Doc 8168))

Radar A radio detection device which provides information on range, azimuth and/or elevation of objects. (UK Reg (EU) No 923/2012 Article 2(105))

Radar approach An approach, in which the final approach phase is executed, under the direction of a controller using radar. (ICAO PANS-ATM (Doc 4444))

Radar clutter The visual indication on a situation display of unwanted signals. (ICAO PANS-ATM (Doc 4444))

Radar contact The situation which exists when the radar position of a particular aircraft is seen and identified on a situation display. (ICAO PANS-ATM (Doc 4444))

Radar handover Transfer of responsibility for the control of an aircraft between two controllers using radar, following identification of the aircraft by both controllers.

Radar separation The separation used when aircraft position information is derived from radar sources. (ICAO PANS-ATM (Doc 4444))

Radial A magnetic bearing extending from a VOR/VORTAC/TACAN. (CAA)

Radio mandatory zone (RMZ) Airspace of defined dimensions wherein the carriage and operation of suitable/appropriate radio equipment is mandatory. (UK Reg (EU) No 923/2012 Article 2(106))

Radio navigation service A service providing guidance information or position data for the efficient and safe operation of aircraft supported by one or more radio navigation aids. (UK Reg (EU) No 923/2012 Article 2(106))

Radiotelephony (RTF) A form of radiocommunication primarily intended for the exchange of information in the form of speech. (UK Reg (EU) No 923/2012 Article 2(107))

Receiving unit/controller Air traffic services unit/air traffic controller to which a message is sent.

Note. See definition of “sending unit/controller”. (ICAO PANS-ATM (Doc 4444))

Recognised air traffic environment The situation which results from the deployment of a transponder mandatory zone (TMZ) where all air traffic within a defined volume of airspace is conspicuous to air traffic services through the carriage and operation of a Mode S SSR transponder (unless operating in compliance with alternative provisions prescribed for that particular airspace by the TMZ Controlling authority that will achieve a cooperative electronic conspicuity environment), but where there is no requirement for air traffic to maintain continuous air-ground voice communication watch. (CAA)

Reduced Coordination Airspace A portion of airspace of defined dimensions within which GAT is permitted to fly 'off-route' without requiring controllers of GAT flights to initiate co-ordination with controllers of OAT flights. (EUROCONTROL: Airspace Management (ASM) Handbook)

Note. The definition of this type of airspace formalizes existing UK procedures for off route GAT in periods of low traffic intensity or in specific areas agreed between civil and military units at ACCs.

Reduced Vertical Separation Minimum (RVSM) Any airspace between FL290 and FL410 inclusive which has been notified, prescribed or otherwise designated by the relevant competent authority as being airspace within which a vertical separation minimum of 1000 feet or 300 metres must be applied. (ANO 2016 Schedule 1)

Release point The position, time or level at which an arriving aircraft comes under the jurisdiction of an approach control unit. (CAA)

Remotely Piloted Aircraft System (RPAS) A remotely piloted aircraft, its associated remote pilot stations, the required command and control links and any other components as specified in the type design. (ICAO)

Repetitive flight plan A flight plan related to a series of frequently recurring, regularly operated individual flights with identical basic features, submitted by an operator for retention and repetitive use by ATS units. (UK Reg (EU) No 923/2012 Article 2(109))

Reporting point A specified geographical location in relation to which the position of an aircraft can be reported. (UK Reg (EU) No 923/2012 Article 2(110))

Required communication performance (RCP) specification A set of requirements for air traffic service provision and associated ground equipment, aircraft capability, and operations needed to support performance-based communication. (ICAO PANS-ATM (Doc 4444))

Required surveillance performance (RSP) specification A set of requirements for air traffic service provision and associated ground equipment, aircraft capability, and operations needed to support performance-based surveillance. (ICAO PANS-ATM (Doc 4444))

Restricted area Airspace of defined dimensions, above the land areas or territorial waters of a State, within which the flight of aircraft is restricted in accordance with certain specified conditions. (UK Reg (EU) No 923/2012 Article 2(111))

Reversal procedure A procedure designed to enable an aircraft to reverse direction during the initial approach segment of an instrument approach procedure. The sequence may include procedure turns or base turns. (ICAO Annex 4)

Route segment A route or portion of route usually flown without an intermediate stop. (UK Reg (EU) No 923/2012 Article 2(112))

Runway A defined rectangular area on a land aerodrome prepared for the landing and take-off run of aircraft along its length. (UK Reg (EU) No 923/2012 Article 2(113))

Runway holding position A designated position intended to protect a runway, an obstacle limitation surface, or an instrument landing system (ILS)/microwave landing system (MLS) critical/sensitive area at which taxiing aircraft and vehicles are to stop and hold, unless otherwise authorised by the aerodrome control tower. (UK Reg (EU) No 923/2012 Article 2(114))

Note 1. In radiotelephony phraseology, the term 'holding point' is used to designate the runway holding position. (UK Reg (EU) No 923/2012 Article 2(114) GM1)

Note 2. Runway-holding positions also exist at aerodromes with no ATC. In such circumstances authorisation from an aerodrome control tower is not possible. (UK Reg (EU) No 923/2012 Article 2(114) GM2)

Runway incursion Any occurrence at an aerodrome involving the incorrect presence of an aircraft, vehicle or person on the protected area of a surface designated for the landing and take-off of aircraft. (ICAO PANS-ATM (Doc 4444))

Runway visual range (RVR) The range over which the pilot of an aircraft on the centre line of a runway can see the runway surface markings or the lights delineating the runway or identifying its centre line. (UK Reg (EU) No 923/2012 Article 2(115))

S

Safety Management System (SMS) A systematic and proactive approach to managing safety risks. Risk management activities are at the heart of SMS, including the identification of safety issues, risk assessments and risk mitigation. It is supported by a strong assurance function that monitors compliance and performance as well as managing changes. (CAA)

Safety sensitive personnel Persons who might endanger aviation safety if they perform their duties and functions improperly, including crew members, aircraft maintenance personnel, aerodrome operations personnel, rescue, fire-fighting and maintenance personnel, personnel allowed unescorted access to the movement area and air traffic controllers. (UK Reg (EU) No 923/2012 Article 2(116))

SAFETYCOM A common frequency (135.475 MHz) made available for use at aerodromes where no other frequency is allocated, to enable pilots to broadcast their intentions to other aircraft that may be operating on, or in the vicinity of, the aerodrome.

Note. SAFETYCOM is not an air traffic service and procedures for its use by pilots are notified in the UK AIP. (CAA)

Sailplane A heavier-than-air aircraft which is supported in flight by the dynamic reaction of the air against its fixed lifting surfaces, the free flight of which does not depend on an engine, including also hang gliders, paragliders and other comparable craft. (UK Reg (EU) No 923/2012 Article 2(117))

Secondary surveillance radar (SSR) A surveillance radar system which uses transmitters/receivers (interrogators) and transponders. (UK Reg (EU) No 923/2012 Article 2(118))

Segregated airspace Means airspace of specified dimensions allocated for exclusive use to a specific user(s), with operations that are not able to be safely integrated with other airspace users (ICAO)

Segregated parallel operations Simultaneous operations on parallel or near-parallel instrument runways in which one runway is used exclusively for approaches and the other runway is used exclusively for departures. (ICAO PANS-ATM (Doc 4444))

Note. See definition of “receiving unit/controller”. (ICAO PANS-ATM (Doc 4444))

Semi-circular cruising level Specified cruising levels determined in relation to magnetic track within hemispheres of the compass. (CAA)

Sending unit/controller Air traffic services unit/air traffic controller transmitting a message.

SIGMET information Information issued by a meteorological watch office concerning the occurrence or expected occurrence of specified en-route weather phenomena which may affect the safety of aircraft operations. (UK Reg (EU) No 923/2012 Article 2(119))

Signal area An area on an aerodrome used for the display of ground signals. (UK Reg (EU) No 923/2012 Article 2(120))

Significant point A specified geographical location used in defining an ATS route or the flight path of an aircraft and for other navigation and ATS purposes. (UK Reg (EU) No 923/2012 Article 2(121))

Note. There are three categories of significant points: ground based navigation aid, intersection and waypoint. In the context of this definition, intersection is a significant point expressed as radials, bearings and/or distances from ground-based navigation aids. (UK Reg (EU) No 923/2012 Article 2(121) GM1)

Silent handover A transfer of control without a radar handover, made in accordance with local conditions. (CAA)

Situation display An electronic display depicting the position and movement of aircraft and other information as required. (ICAO PANS-ATM (Doc 4444))

Spaceport A site from which spacecraft or carrier aircraft are launched or (as the case may be) are to be launched, or a site at which controlled and planned landings of spacecraft take place or (as the case may be) are to take place. (Space Industry Act 2018)

Special Use Airspace (SUA) An airspace volume designated for specific operations, such as military training, exercises, and operations, of a nature such that required limitations on airspace access may be imposed on other aircraft not participating in those activities. (CAA)

Special VFR (SVFR) flight A VFR flight cleared by air traffic control to operate within a control zone in meteorological conditions below VMC. (UK Reg (EU) No 923/2012 Article 2(122))

SSR response The visual indication in non-symbolic form, on a situation display, of a response from an SSR transponder in reply to an interrogation. (ICAO PANS-ATM (Doc 4444))

Standard instrument arrival (STAR) A designated instrument flight rule (IFR) arrival route linking a significant point, normally on an ATS route, with a point from which a published instrument approach procedure can be commenced. (ICAO PANS-ATM (Doc 4444))

Standard instrument departure (SID) A designated instrument flight rule (IFR) departure route linking the aerodrome or a specified runway of the aerodrome with a

specified significant point, normally on a designated ATS route, at which the en route phase of a flight commences. (ICAO PANS-ATM (Doc 4444))

Standard message element Part of a message defined in the PANS-ATM (Doc 4444) in terms of display format, intended use and attributes. (ICAO PANS-ATM (Doc 4444))

Statement of Need The means by which a change sponsor initiates the airspace change process by setting out what airspace issue or opportunity it is seeking to address and what outcome it wishes to achieve, without specifying solutions, technical or otherwise. (CAA)

Stepdown fix A defined point on the final approach track indicating that a critical obstacle has been safely overflown and descent to the next specified level may be commenced. (CAA)

Stopway A defined rectangular area on the ground at the end of the take-off run available, prepared as a suitable area in which an aircraft can be stopped in the case of a abandoned take-off. (ICAO Annex 14 Vol I)

Straight ahead When used in departure clearances means: 'track extended runway centreline'. When given in Missed Approach Procedures means: 'continue on Final Approach Track'. (CAA)

Strayed aircraft An aircraft which has deviated significantly from its intended track or which reports that it is lost. (UK Reg (EU) No 923/2012 Article 2(123))

Supplementary Instruction (SI) Supplementary instructions are issued in relation to a specific document and introduce change to information and/or procedures contained within that document. The CAA issues supplementary instructions for the MATS Pt 1, FISO Manual, and the Radiotelephony Manual. ANSPs issue supplementary instructions for their MATS Pt 2. (CAA)

Surface visibility The horizontal visibility as measured at a height of 2 metres above the ground. (CAA)

Surveillance minimum altitude area (SMAA) Defined area in the vicinity of an aerodrome, depicted on a Surveillance Minimum Altitude Chart (SMAC), in which the minimum safe levels allocated by a controller vectoring IFR flights with Primary and/or Secondary Radar equipment have been predetermined. (CAP 777)

Surveillance radar Radar equipment used to determine the position of an aircraft in range and azimuth. (UK Reg (EU) No 923/2012 Article 2(124))

T

Taxiing Movement of an aircraft on the surface of an aerodrome or an operating site under its own power, excluding take-off and landing. (UK Reg (EU) No 923/2012 Article 2(125))

Taxiway A defined path on a land aerodrome established for the taxiing of aircraft and intended to provide a link between one part of the aerodrome and another, including:

- (a) Aircraft stand taxilane means a portion of an apron designated as a taxiway and intended to provide access to aircraft stands only.
- (b) Apron taxiway means a portion of a taxiway system located on an apron and intended to provide a through taxi route across the apron.
- (c) Rapid exit taxiway means a taxiway connected to a runway at an acute angle and designed to allow landing aeroplanes to turn off at higher speeds than are achieved on other exit taxiways thereby minimizing runway occupancy times. (UK Reg (EU) No 923/2012 Article 2(126))

Taxiway holding position A designated position at which taxiing aircraft and vehicles may be required to hold in order to provide adequate clearance from a runway or taxiway.

Note. In radiotelephony phraseologies, the expression 'holding point' is used to designate the runway-holding position or taxiway holding position. (CAA)

Temporary Operating Instruction (TOI) A mandatory air traffic control instruction which constitutes a temporary change to local air traffic control operational procedures or information. The modification in procedures or operating techniques can be short term, for example an airshow or while waiting for an adaptation fix, or a longer-term activity such as a procedures trial. (CAA)

Temporary Reserved Area (TRA) Airspace that is temporarily reserved and allocated for the specific use of a particular user during a determined period of time and through which other traffic may or may not be allowed to transit in accordance with the air traffic management arrangements notified for that volume of airspace. (CAA)

Temporary Segregated Area (TSA) A defined volume of airspace, temporarily segregated and allocated for the exclusive use of a particular user during a determined period of time and through which other traffic will not be allowed to transit. (CAA)

Terminal control area (TMA) A control area normally established at the confluence of ATS routes in the vicinity of one or more major aerodromes. (ICAO Annex 11)

Territory The land areas and territorial waters adjacent thereto under the sovereignty, suzerainty, protection or mandate of a State. (UK Reg (EU) No 923/2012 Article 2(127))

Threshold The beginning of that portion of the runway usable for landing. (UK Reg (EU) No 923/2012 Article 2(128))

Time difference of arrival (TDOA) The difference in relative time that a transponder signal from the same aircraft (or ground vehicle) is received at different receivers. (ICAO PANS-ATM (Doc 4444))

Total elapsed time For IFR flights, the estimated time required from take-off to arrive over that designated point, defined by reference to navigation aids, from which it is intended that an instrument approach procedure will be commenced, or, if no navigation aid is associated with the destination aerodrome, to arrive over the destination aerodrome. For VFR flights, the estimated time required from take-off to arrive over the destination aerodrome. (UK Reg (EU) No 923/2012 Article 2(129))

Total estimated elapsed time. For IFR flights, the estimated time required from take-off to arrive over that designated point, defined by reference to navigation aids, from which it is intended that an instrument approach procedure will be commenced, or, if no navigation aid is associated with the destination aerodrome, to arrive over the destination aerodrome. For VFR flights, the estimated time required from take-off to arrive over the destination aerodrome. (ICAO PANS-ATM (Doc 4444))

Touchdown The point where the nominal glide path intercepts the runway.

Note. “Touchdown” as defined above is only a datum and is not necessarily the actual point at which the aircraft will touch the runway. (ICAO PANS-ATM (Doc 4444))

Toy aircraft An unmanned aircraft designed or intended for use, whether or not exclusively, in play by children under 14 years of age. (UK Reg (EU) No 923/2012 Article 2(129a))

Note. Directive 2009/48/EC (the Toy Safety Directive) requires that toys, including the chemicals they contain, shall not jeopardise the safety or health of users or third parties when they are used as intended or in a foreseeable way, bearing in mind the behaviour of children. The Toy Safety Directive additionally requires that toys made available on the market shall bear the CE marking. The CE marking indicates the conformity of the product with the Union legislation applying to the product and providing for CE marking. (UK Reg (EU) No 923/2012 Article 2(129a) GM1)

Track The projection on the earth’s surface of the path of an aircraft, the direction of which path at any point is usually expressed in degrees from North (true, magnetic or grid). (UK Reg (EU) No 923/2012 Article 2(130))

Traffic avoidance advice Advice provided by an air traffic services unit specifying manoeuvres to assist a pilot to avoid a collision. (UK Reg (EU) No 923/2012 Article 2(131))

Traffic information Information issued by an air traffic services unit to alert a pilot to other known or observed air traffic which may be in proximity to the position or intended

route of flight and to help the pilot avoid a collision. (UK Reg (EU) No 923/2012 Article 2(132))

Note. Traffic information may also be passed between ATS personnel.

Traffic Service A Traffic Service is a surveillance ATS, where in addition to the provisions of a Basic Service, the controller provides specific surveillance derived traffic information to assist the pilot in avoiding other traffic. Controllers may provide headings and/or levels for the purposes of positioning and/or sequencing; however, the controller is not required to achieve deconfliction minima, and the pilot remains responsible for collision avoidance. (CAP 774)

Transfer of control point A defined point located along the flight path of an aircraft, at which the responsibility for providing air traffic control service to the aircraft is transferred from one control unit or control position to the next. (UK Reg (EU) No 923/2012 Article 2(133))

Transferring unit/controller Air traffic control unit/air traffic controller in the process of transferring the responsibility for providing air traffic control service to an aircraft to the next air traffic control unit/air traffic controller along the route of flight.

Note. See definition of “accepting unit/controller”. (ICAO PANS-ATM (Doc 4444))

Transition altitude (TA) The altitude at or below which the vertical position of an aircraft is controlled by reference to altitudes. (UK Reg (EU) No 923/2012 Article 2(134))

Note. Where QFE is used, the vertical position will be with reference to height.

Transition level (TL) The lowest flight level available for use above the transition altitude. (UK Reg (EU) No 923/2012 Article 2(135))

Transponder A receiver/transmitter which will generate a reply signal upon interrogation. (CAA)

Transponder mandatory zone A Transponder Mandatory Zone (TMZ) is airspace of defined dimensions wherein the carriage and operation of pressure-altitude reporting transponders is mandatory. (UK Reg (EU) No 923/2012 Article 2(136))

Transport Act 2000 Primary legislation setting out the CAA’s statutory duties and functions in relation to airspace change. The Transport Act 2000 places the CAA under a general duty when deciding whether to approve airspace change proposals to do so in a way that maintains a high standard of safety in the provision of air traffic services. (CAA)

U

UK Flight Information Services The suite of air traffic services detailed in CAP 774.

UK Reg (EU) No. 923/2012 UK Standardised European Rules of the Air.

UK Standardised European Rules of the Air ((UK) SERA) Annex I to Assimilated Regulation (EU) No. 923/2012 under the European Union (Withdrawal) Act 2018 laying down the common rules of the air and operational provisions regarding services and procedures in air navigation. (CAA)

Uncertainty phase. A situation wherein uncertainty exists as to the safety of an aircraft and its occupants. (ICAO PANS-ATM (Doc 4444))

Unidentified aircraft An aircraft which has been observed or reported to be operating in a given area but whose identity has not been established. (UK Reg (EU) No 923/2012 Article 2(137))

Unknown traffic Traffic, the flight details and intentions of which are not known to the controller/FISO. (CAA)

Unmanned Aircraft System (UAS) Means an unmanned aircraft and the equipment to control it remotely (UK Reg (EU) 2019/947 Article 2(1)).

Unmanned aircraft system Traffic Management (UTM) A specific aspect of air traffic management which manages UAS operations safely, economically and efficiently through the provision of facilities and a seamless set of services in collaboration with all parties and involving airborne and ground-based functions. (CAA)

Unmanned free balloon A non-power-driven, unmanned, lighter-than-air aircraft in free flight. (UK Reg (EU) No 923/2012 Article 2(138))

Note. Unmanned free balloons are classified as heavy, medium or light in accordance with the specifications contained in Appendix 2 to this Regulation. (UK Reg (EU) No 923/2012 Article 2(138) GM1)

Unruly passengers Persons who commit, on board a civil aircraft, from the moment when the aircraft door is closed prior to take-off to the moment when it is reopened after landing, an act of:

- assault, intimidation, menace or wilful recklessness which endangers good order or the safety of property or persons;
- assault, intimidation, menace or interference with a crew member in the performance of duties or which lessens the ability to perform duties;
- wilful recklessness or damage to an aircraft, its equipment, or attendant structures and equipment such as to endanger good order and the safety of the aircraft or its occupants;

- communication of information which is known to be false, thereby endangering the safety of an aircraft in flight; and
- disobedience of lawful commands or instructions for safe, orderly or efficient operations.

V

Vectoring Provision of navigational guidance to aircraft in the form of specific headings, based on the use of an ATS surveillance system. (ICAO PANS-ATM (Doc 4444))

VFR The symbol used to designate the visual flight rules. (UK Reg (EU) No 923/2012 Article 2(139))

VFR flight A flight conducted in accordance with the visual flight rules. (UK Reg (EU) No 923/2012 Article 2(140))

Visibility Visibility for aeronautical purposes is the greater of:

- (a) The greatest distance at which a black object of suitable dimensions, situated near the ground, can be seen and recognised when observed against a bright background;
- (b) The greatest distance at which lights in the vicinity of 1,000 candelas can be seen and identified against an unlit background. (UK Reg (EU) No 923/2012 Article 2(141))

Note.

- (a) The two distances which may be defined by a given visibility have different values in air of a given extinction coefficient. Visibility based on seeing and recognizing an object is represented by the meteorological optical range (MOR) (Article 2(141)(a)). Visibility based on seeing and identifying lights varies with the background illumination (Article 2(141)(b)).
- (b) The definition of visibility applies to the observations of visibility in local routine and special reports, to the observations of prevailing and minimum visibility reported in METAR and SPECI and to the observations of ground visibility. (UK Reg (EU) No 923/2012 Article 2(141) GM1)

Visual approach An approach by an IFR flight when part or all of an instrument approach procedure is not completed and the approach is executed with visual reference to terrain. (ICAO PANS-ATM (Doc 4444))

Visual line of sight operation Means a type of UAS operation in which, the remote pilot is able to maintain continuous unaided visual contact with the unmanned aircraft, allowing the remote pilot to control the flight path of the unmanned aircraft in relation to other aircraft, people and obstacles for the purpose of avoiding collisions (UK Reg (EU) 2019/947 Article 2(7)).

Visual meteorological conditions (VMC) Meteorological conditions expressed in terms of visibility, distance from cloud, and ceiling, equal to or better than specified minima. (UK Reg (EU) No 923/2012 Article 2(142))

Visual Reference Point (VRP) Fixed point on land or sea used by pilots to fix the position of their aircraft in relation to their route. (CAA)

Visual surveillance system An electro-optical system providing an electronic visual presentation of traffic and any other information necessary to maintain situational awareness at an aerodrome and its vicinity. (ICAO PANS-ATM (Doc 4444))

VMC The symbol used to designate visual meteorological conditions. (UK Reg (EU) No 923/2012 Article 2(143))

W

Waypoint A specified geographical location used to define an area navigation route or the flight path of an aircraft employing area navigation. Waypoints are identified as either:

Fly-by waypoint. A waypoint which requires turn anticipation to allow tangential interception of the next segment of a route or procedure, or

Flyover waypoint. A waypoint at which a turn is initiated in order to join the next segment of a route or procedure. (ICAO PANS-ATM (Doc 4444))

Windshear A sudden change in wind speed and/or direction in space, including updrafts and downdrafts.

Note 1. Vertical wind shear is defined as change of horizontal wind direction and/or speed with height, as would be determined by means of two or more anemometers mounted at different heights on a single mast.

Note 2. Horizontal wind shear is defined as change of horizontal wind direction and/or speed with horizontal distance, as would be determined by two or more anemometers mounted at the same height along a runway. (ICAO Doc 9817)

With the surface in sight Means with the flight crew being able to see sufficient surface features or surface illumination to enable the flight crew to maintain the aircraft in a desired attitude without reference to any flight instrument and 'when the surface is not in sight' is to be construed accordingly. (ANO 2016 Schedule 1)

Abbreviations and Acronyms

A

AAA	Airspace, ATM and Aerodromes
AAC	Army Air Corps
AAIB	Air Accidents Investigation Branch
aal	Above Aerodrome Level
AARA	Air to Air Refuelling Area
ACARS	Aircraft Communication Addressing and Reporting System
ACAS	Airborne Collision Avoidance System
ACC	Area Control Centre
ACN	Airspace Co-ordination Notice
ACM	Airspace Capacity Management
ACP	Airspace Change Proposal
ADC	Aerodrome Control
ADF	Automatic Direction-Finding Equipment
ADR	Advisory Route
ADQ	Aeronautical Data Quality
ADS	Automatic Dependent Surveillance
ADS-B	Automatic Dependent Surveillance-Broadcast
ADS-C	Automatic Dependent Surveillance-Contract
ADT	Approved Departure Time
AEW	Airborne Early Warning
AFIS	Aerodrome Flight Information Service
AFISO	Aerodrome Flight Information Service Officer
AFS	Aeronautical fixed service
AFPEX	Assisted Flight Plan Exchange

AFTN	Aeronautical Fixed Telecommunications Network
AGCS	Air/Ground Communications Service
agl	Above Ground Level
AGL	Aerodrome Ground Lighting
AGCS	Air-Ground Communication Service
AIC	Aeronautical Information Circular
AIP	Aeronautical Information Publication
AIPCR	Aeronautical Information Publication Change Request
AIP SUP	Aeronautical Information Publication Supplement
AIRAC	Aeronautical Information Regulation and Control
AIRAC cycle	28-day cycle over which changes to the AIP are made
AIRPROX	Aircraft Proximity
AIS	Aeronautical Information Service
AltMOC	Alternative Means of Compliance
AMA	AMC Managed Area
AMC	Airspace Management Cell
AMC	Acceptable Means of Compliance
AME	Authorised Medical Examiner
AMF	Airspace Management Function
AMHS	ATS Message Handling System
AMS	Airspace Modernisation Strategy
AMSG	Airspace Management Steering Group
AMSL	Above Mean Sea Level
ANG	Air Navigation Guidance
ANO	Air Navigation Order
ANS	Air Navigation Services
ANSP	Air Navigation Service Provider
AO	Aircraft Operator

AOA	Airport Operators' Association
AOC	Air Operator Certificate
APAC	Applicability and Policy Alignment Check
APAPI	Abbreviated Precision Approach Path Indicator
APC	Approach Control
APDO	Approved Procedure Design Organisation
APV	Approach Procedures With Vertical Guidance
AR	Airspace Regulation (of CAA SARG)
ARCC	Aeronautical Rescue Co-ordination Centre
ARP	Aerodrome Reference Point
ASACS	Airborne Surveillance and Control System
ASI	Airspace and Safety Initiative
ASL	Above Sea Level
ASM	Airspace Management
ASR	Altimeter Setting Region
ASR	Air Safety Report
ATA	Actual Time of Arrival
ATAS	Air Traffic Advisory Service
ATC	Air Traffic Control
ATCC	Air Traffic Control Centre
ATCO	Air Traffic Control Officer
ATCU	Air Traffic Control Unit
ATD	Actual Time of Departure
ATFCM	Air Traffic Flow and Capacity Management
ATFM	Air Traffic Flow Management
ATIS	Automatic Terminal Information Service
ATM	Air Traffic Management (ATS & ASM & ATFCM)
ATM	Aerodrome Traffic Monitor

ATM	Air Traffic Movement
ATS	Air Traffic Services
ATSI	Air Traffic Services Investigations
ATSIN	ATS Information Notice
ATSP	Air Traffic Services Provider
ATSU	Air Traffic Services Unit
AT-VASIS	Abbreviated T Visual Approach Slope Indicator System
ATZ	Aerodrome Traffic Zone
AUP	Airspace Use Plan
AU	Airspace Utilisation

B

BVLOS	Beyond visual line of sight operation
-------	---------------------------------------

C

CAA	Civil Aviation Authority
CADF	Central Airspace Data Function
CAM	Civil Airspace Manager
CAP	Civil Aviation Publication
CAS	Controlled Airspace
CAS-T	Temporary class D Controlled Airspace
CAT	Commercial Air Transport
CAVOK	Visibility, cloud and present weather better than prescribed values or conditions
CBA	Cross-Border Areas
CCO	Continuous Climb Operations
CDO	Clearance Delivery Officer
CDO	Continuous Descent Operations
CDR	Conditional Route
CFME	Continuous Friction Measuring Equipment

CIAM	Collaborative Interface Airspace Management
CMATZ	Combined Military Aerodrome Traffic Zone
CPDLC	Controller Pilot Datalink Communications
CPL	Current Flight Plan
CNS	Communication Navigation Service
c/s	Callsign
CTA	Control Area
CTR	Control Zone
CVSM	Conventional Vertical Separation Minimum

D

DAA	Danger Area Authorities
DAAIS	Danger Area Activity Information Service
DAASG	Danger Area Airspace Steering Group
DAATM	Defence Airspace and Air Traffic Management
D&D	RAF Distress and Diversion Cell
DACS	Danger Area Crossing Service
D-ATIS	Data Link Automatic Terminal Information Service
DEO	Duty Engineering Officer
DF	Direction Finding
DfT	Department for Transport
DFTI	Distance from Touchdown Indicator
DLIC	Data link initiation capability
DME	Distance Measuring Equipment
DOC	Designated Operational Coverage
DR	Dead Reckoning
DVOR	Doppler VHF Omni-directional Range

E

EASA	European Aviation Safety Agency
------	---------------------------------

EAT	Expected Approach Time
EC	European Commission
ECCAIRS	European Coordination Centre for Accident and Incident Reporting Systems
ECAC	European Civil Aviation Conference
EGNOS	European Geostationary Navigation Overlay Service
EGPWS	Enhanced Ground Proximity Warning System
EHS	Enhanced Surveillance
ELS	Elementary Surveillance
EOBT	Estimated Off-Block Time
ESSIP	European Single Sky Implementation
ETA	Estimated Time of Arrival
ETD	Estimated Time of Departure
EUCARF	European Centralised Airspace Reservation Facility
ExCo	Executive Committee (CAA)

F

FAB	Functional Airspace Block
FAS	Future Airspace Strategy
FAF	Final Approach Fix
FBZ	Flight plan Buffer Zone
FID	Flight Information Display
FIR	Flight Information Region
FIS	Flight Information Service(s)
FISO	Flight Information Service Officer
FL	Flight Level
FMP	Flow Management Position
FOST	Flag Officer Sea Training
FPL	Flight Plan
FPPS	Flight Plan Processing System

FRA	Free Route Airspace
FRA(A)	FRA Arrival Connection Point
FRA(D)	FRA Departure Connection Point
FRA(E)	FRA Horizontal Entry Point
FRA(I)	FRA Intermediate Point
FRA(X)	FRA Horizontal Exit Point
ft	Foot (feet)
FUA	Flexible Use of Airspace

G

GA	General Aviation
GAT	General Air Traffic
GBAS	Ground-based augmentation system
GCAS	Ground Collision Avoidance System
GLONASS	Global Orbiting Navigation Satellite System
GM	Guidance Material
GMC	Ground Movement Control
GNSS	Global Navigation Satellite System
GPS	Global Positioning System
GPWS	Ground Proximity Warning System
GRAS	Ground-based regional augmentation system

H

H	Hour
H24	Continuous day and night service
HEMS	Helicopter Emergency Medical Service
HF	High Frequency
HJ	Sunrise to Sunset
HLA	High-Level Airspace
HLAPB	High-Level Airspace Policy Body

HN Sunset to Sunrise

hPa Hectopascal

I

IAA Irish Aviation Authority

IAF Initial Approach Fix

IAIP Integrated Aeronautical Information Publication

IAP Instrument Approach Procedure

IAS Indicated Air Speed

ICAO International Civil Aviation Organisation

ICAO SARPs International Civil Aviation Organisation Standards and Recommended Practices

IF Intermediate Approach Fix

IFP Instrument Flight Procedure

IFR Instrument Flight Rules

ILS Instrument Landing System

IMC Instrument Meteorological Conditions

IN CAA Information Notice

Infringement Airspace Infringement

INS Inertial Navigation System

IRVR Instrumented Runway Visual

J

JANSC Joint Air Navigation Services Council

JFADT Joint Future Airspace Development Team

J&I Joint and Integrated

K

kg Kilogramme(s)

kHz Kilohertz

km Kilometre(s)

km/h	Kilometres per hour
KPA	Key Performance Area
KPI	Key Performance Indicator
kt	Knot(s)

L

LARS	Lower Airspace Radar Service
Lat	Latitude
LATCC (Mil)	London Air Traffic Control Centre (Military)
LoA	Letter of Agreement
Long	Longitude
LSSIP	Local Single Sky Implementation

M

m	Metre(s)
MAA	Military Aviation Authority
MABCC	Military Airspace Booking Co-ordination Cell
MAM	Military Airspace Manager
MAP	Missed Approach Point
MARSA	Military Accepts Responsibility for Separation of Aircraft
MATS	Manual of Air Traffic Services
MATS Pt 1	Manual of Air Traffic Services Part 1 (Produced by CAA as CAP 493)
MATS Pt 2	Manual of Air Traffic Services Part 2 (Produced by an ANSP)
MATZ	Military Aerodrome Traffic Zone
MCTOM	Maximum Certified Take-off Mass
MDA	Minimum Descent Altitude
MDH	Minimum Descent Height
MEDA	Military Emergency Diversion Aerodrome
MET	Meteorological or Meteorology
METAR	Routine aviation aerodrome weather report

MHz	Mega-hertz
Mil AIP	Military Aeronautical Information Publication
MLAT	Multilateration
MLS	Microwave Landing System
mm	Millimetre(s)
MoD	Ministry of Defence
MOR	Mandatory Occurrence Report
MoU	Memorandum of Understanding
MSA	Minimum Sector Altitude
MTA	Military Training Area
MTI	Moving Target Indicator

N

NAM	Non-AMC Managed Area
NATMAC	National Air Traffic Management Advisory Committee
NDB	Non-Directional Beacon
NDS	Non-Deviating Status
NERL	NATS En-Route PLC
NGO	Non-Governmental Organisation
NM	Nautical Mile(s)
NMOC	Network Management Operations Centre (formerly CFMU)
NOZ	Normal operating zone
NPA	Non-Precision Approach
NPP	National Performance Plan
NPR	Noise Preferential Route
NPZ	Non-standard Planning Zone
NSA	National Supervisory Authority
NSF	Non-Standard Flight
NSL	NATS Services Limited

NTZ No transgression zone

O

OACC	Oceanic Area Control Centre
OAS	Offshore Aeronautical Service
OAT	Operational Air Traffic
OCA	Oceanic Control Area
OCA	Obstacle Clearance Altitude
OCH	Obstacle Clearance Height
OCU	Operational Conversion Unit
OCS	Offshore Communication Service
OPC	Operational Control Communications
OPMET	Operational Meteorological
ORS	Official Record Series
OSAACT	Open Skies ATC and Airspace Co-ordination Team

P

PA	Precision Approach
PAPI	Precision Approach Path Indicator
PAR	Precision Approach Radar
PBC	Performance-based communication
PBN	Performance-based navigation
PBS	Performance-based surveillance
PC	Prestwick Centre (Area Control Centre)
PIB	Pre-flight Information Bulletin
PIC	Pilot in command
PinS	Point in Space
PLOC	Prolonged Loss of Communications
POB	(Total) Persons on Board
PSR	Primary Surveillance Radar

Q

QDM	Magnetic heading (zero wind) (Sometimes employed to indicate magnetic heading of a runway)
QDR	Magnetic bearing
QFE	Atmospheric pressure at aerodrome elevation
QNE	Landing altimeter reading when subscale set 1013.2 hPa
QNH	Regional atmospheric pressure at sea level
QTE	True Bearing

R

RA	Resolution Advisory
RAF	Royal Air Force
RAG	Range and Azimuth Gating
RCA	Reduced Co-ordination Airspace
RCC	Rescue Co-ordination Centre
RCP	Required communication performance
RCSA	Release of Controlled and Segregated Airspace (Policy)
RFFS	Rescue and Fire Fighting Service
RMZ	Radio Mandatory Zone
RN	Royal Navy
RNAV	Area Navigation
RNP	Required Navigational Performance
RO	Radio Operator
RoTA	Rules of the Air Regulations
RP	Reporting Period
RPAS	Remotely Piloted Aircraft System
RPS	Regional Pressure Setting
RSP	Required surveillance performance
RTF	Radiotelephony

RVR	Runway Visual Range
RVSM	Reduced Vertical Separation Minimum

S

SAR	Search and Rescue
SARG	Safety and Airspace Regulation Group (of the CAA)
SARPs	(ICAO) Standards and Recommended Practices
SBAS	Satellite-Based Augmentation System
SDD	Safety Data Department
SDF	Stepdown Fix
SERA	Standardised European Rules of the Air
SES	Single European Sky
SFN	Special Flight Notification
SI	Supplementary Instruction
SID	Standard Instrument Departure
SMAA	Surveillance Minimum Altitude Area
SMAC	Surveillance Minimum Altitude Chart
SMGCS	Surface Movement Guidance and Control System
SMR	Surface Movement Radar
SMS	Safety Management System
SPI	Special Position Identification
SRA	Surveillance Radar Approach
SSR	Secondary Surveillance Radar
STAR	Standard Instrument Arrival
SUA	Special Use Airspace
SVFR	Special VFR

T

TA	Traffic Advisory
TA	Transition Altitude

TACAN	Tactical Air Navigation
TAF	Terminal Aerodrome Forecast
TAS	True Airspeed
TAWS	Terrain Avoidance and Warning System
TCAS	Traffic Alert and Collision Avoidance System
TDOA	Time difference of arrival
TL	Transition Level
TMA	Terminal Control Area
TMZ	Transponder Mandatory Zone
TOI	Temporary Operating Instruction
TORA	Take Off Run Available
TQHF	The Queen's Helicopter Flight
TRA	Temporary Reserved Area
TRG	Training
TSA	Temporary Segregated Area
T-VASIS	T Visual Approach Slope Indicator System

U

UAA	Unusual Aerial Activity
UAS	Upper Air Space
UAS	Unmanned Aircraft System
UHF	Ultra High Frequency
UIR	Upper Flight Information Region
UK	United Kingdom
UKAB	United Kingdom AIRPROX Board
UK FIS	United Kingdom Flight Information Services
UK SERA	UK Standardised European Rules of the Air
UTC	Co-ordinated Universal Time
UTM	Unmanned aircraft system Traffic Management

UUP	Updated Airspace Use Plan
-----	---------------------------

V

VASIS	Visual Approach Slope Indicator System
VDF	VHF Direction Finding
VFR	Visual Flight Rules
VGS	Volunteer Gliding Squadron
VHF	Very High Frequency
VIP	Very Important Person
VLOS	Visual Line Of Sight
VMC	Visual Meteorological Conditions
VOLMET	Meteorological information for aircraft in flight
VOR	VHF Omni-directional Range
VORTAC	VHF Omni-directional Range Tactical Air Navigation
VRP	Visual Reference Point
VTOL	Vertical Take off Landing
VVIP	Very Very Important Person