

## (2) Rolls Royce (Bristol Siddeley) Cheetah Engines

UK National Airworthiness Directives previously published in CAP 476 – Mandatory Aircraft Modifications and Inspections Summary

**CAA AD No:** 1457 PRE 80

**Associated Material:** E792

**Description:** Auxiliary drive shaft oil hole deleted.

**Applicability – Compliance – Requirement**

Applicable to types 9, 15 and 19 installed in Anson aircraft only. Compliance required before flight.

**CAA AD No:** 1458 PRE 80

**Associated Material:** E722

**Description:** Improved air intake heater muff.

**Applicability – Compliance – Requirement**

Applicable to type 10 only. Compliance required before flight.

**CAA AD No:** 1459 PRE 80

**Associated Material:** E763

**Description:** Strengthened air intake heater muff clamping straps.

**Applicability – Compliance – Requirement**

Applicable to types 9, 10, 19, 15 and 17. Not applicable when Mods. E793 and E800 are fitted. Compliance required before flight.

**CAA AD No:** 1460 PRE 80

**Associated Material:** E769

**Description:** Alteration of jet sizes when air cleaner cowlings installed.

**Applicability – Compliance – Requirement**

Applicable to type 9 with Modifications E740, 744 and 745 embodied. Compliance required before flight.

**CAA AD No:** 1461 PRE 80

**Associated Material:** E786

**Description:** Deletion of slow running pressure balance duct.

**Applicability – Compliance – Requirement**

Applicable to types 9, 10, 15 and 19 with Claudel Hobson type AV70M or ME carburettors. Compliance required before flight.

**CAA AD No:** 1462 PRE 80

**Associated Material:** E809

**Description:** Protective gauze screens for hot and cold air intake.

**Applicability – Compliance – Requirement**

Applicable to types 9, 10, 19, 15 and 17. Compliance required before flight.

**CAA AD No:** 1463 PRE 80

**Associated Material:** E820

**Description:** New Magneto timing (port 19° BTDC) (stbd. 21° BTDC).

**Applicability – Compliance – Requirement**

Applicable to types 15 and 17. Compliance required before flight.

**CAA AD No:** 1464 PRE 80

**Associated Material:** E832

**Description:** Increased capacity auxiliary rear scavenge pump.

**Applicability – Compliance – Requirement**

Applicable to types 15, 17, 9, 10 and 19 (only if Heywood Compressor is fitted). Compliance required before flight.

**CAA AD No:** 1465 PRE 80

**Associated Material:** E834

**Description:** Higher range main jet and deletion of power valve cam.

**Applicability – Compliance – Requirement**

Applicable to type 15 with Claudel Hobson carburettor type AV70MG fitted. Compliance required before flight.