



TYPE-CERTIFICATE DATA SHEET

NO. EASA.A.592

for
SportStar RTC

Type Certificate Holder
Evektor, spol. s r.o.
Letecka 1008
686 04 Kunovice
CZECH REPUBLIC

For models: SportStar RTC



TCDS No.:
Issue: xx

Type

Date: dd month yyyy

Intentionally left blank



SECTION A: MODEL A DESIGNATION	4
A.I. General	4
1. Type/ Model/ Variant	4
2. Airworthiness Category	4
3. Manufacturer	4
4. EASA Type Certification Application Date	4
5. State of Design Authority.....	4
6. State of Design Authority Type Certificate Date.....	4
7. EASA Type Certification Date.....	4
A.II. EASA Certification Basis	4
1. Reference Date for determining the applicable requirements	4
2. Airworthiness Requirements	4
3. Special Conditions.....	4
4. Exemptions	4
5. (Reserved) Deviations	4
6. Equivalent Safety Findings	4
7. Environmental Protection.....	4
A.III. Technical Characteristics and Operational Limitations.....	5
1. Type Design Definition.....	5
2. Description.....	5
3. Equipment.....	5
4. Dimensions	5
5. Engine	5
6. Load factors	5
7. Propeller	5
8. Fluids.....	6
9. Fluid capacities.....	6
10. Air Speeds	6
11. Flight Envelope	6
12. Approved Operations Capability.....	6
13. Maximum Masses.....	6
14. Centre of Gravity Range.....	6
15. Datum	6
16. Control surface deflections.....	6
17. Levelling Means	7
18. Minimum Flight Crew	7
19. Maximum Passenger Seating Capacity	7
20. Baggage/ Cargo Compartments.....	7
21. Wheels and Tyres.....	7
22. (Reserved).....	7
1. Flight Manual	8
2. Maintenance Manual.....	8
3. Structural Repair Manual.....	8
4. Weight and Balance Manual.....	8
5. Illustrated Parts Catalogue	8
A.V. Notes	8



SECTION A: MODEL A DESIGNATION

SportStar RTC

A.I. General

1. Type/ Model/ Variant

1.1 Type SportStar RTC

1.2 Model SportStar RTC

1.3 Variant -

2. Airworthiness Category Restricted

3. Manufacturer EVEKTOR-AEROTECHNIK a.s.
Okruzni 234
293 06 BRADLEC

4. EASA Type Certification Application Date 20 December 2010

Note: State of Design Authority certification application date for grandfathered products

5. State of Design Authority

6. State of Design Authority Type Certificate Date

7. EASA Type Certification Date

A.II. EASA Certification Basis

1. Reference Date for determining the applicable requirements 20 December 2010

2. Airworthiness Requirements As defined in CRI A-01, latest issue
CS-LSA, initial issue, dated 27 June 2011,
CS-LSA, Amendment 1, dated 29 June 2013 for KW-31 Major change
3. Special Conditions SC-OLSA-div-01 (CRI A-01) VFR night flights for LSA (Note 1), and
CAI E-01 Equipment qualification

4. Exemptions None

5. (Reserved) Deviations None

6. Equivalent Safety Findings None

7. Environmental Protection ICAO, Annex 16, Volume 1, Chpt. 10



A.III. Technical Characteristics and Operational Limitations

1. Type Design Definition Final assembly S0 00-08 01 SportStar RTC in the state of the date 11 May 2012
2. Description Single engine, two-seater, all metal, cantilever low-wing monoplane with two side-by-side seats, fixed tricycle landing gear, tractor propeller.
3. Equipment The minimum equipment is listed in approved Pilot's Operating Handbook, Doc. No. ERTC020-10-AS
4. Dimensions
- | | | |
|-----------|---------------------|--------------|
| Span | 8.646 m | (28.37 ft) |
| Length | 5.98 m | (19.62 ft) |
| Height | 2.476 m | (8.12 ft) |
| Wing Area | 10.6 m ² | (114.1 sqft) |
5. Engine
- 5.1.1. Model ROTAX 912 ULS2
- 5.1.2. Type Certificate Certified as part of the aircraft
- 5.1.3. Limitations
- | | |
|----------------------|-------------------|
| Max take-off speed | 5800 rpm (5 min.) |
| Max continuous speed | 5500 rpm |
| Idle speed | approx. 1400 rpm |
- For power-plants limits refer to Pilot's Operating Handbook, Doc. No. ERTC020-10-AS
- or alternative
- 5.2.1. Model ROTAX 912 S2
- 5.2.2. Type Certificate EASA.E.121
- 5.2.3. Limitations
- | | |
|----------------------|-------------------|
| Max take-off speed | 5800 rpm (5 min.) |
| Max continuous speed | 5500 rpm |
| Idle speed | approx. 1400 rpm |
- For power-plants limits refer to Pilot's Operating Handbook, Doc. No. ERTC020-10-AS
6. Load factors
- Maximum positive load factor +4.0,
Maximum negative load factor -2.0
7. Propeller
- 7.1.1. Model Woodcomp KLASSIC 170/3/R
- 7.1.2. Type Certificate None
- 7.1.3. Number of blades 3
- 7.1.4. Diameter 1708 ± 4 mm
- 7.1.5. Sense of Rotation Clockwise
- or alternative
- 7.2.1. Model Woodcomp KW-31-A-E-3-0-0-F/R-173-033
- 7.2.2. Type Certificate TCDS.P.177
- 7.2.3. Number of blades 3
- 7.2.4. Diameter 1726 ± 4 mm
- 7.2.5. Sense of Rotation Clockwise



8. Fluids

- 8.1 Fuel Automotive gasoline with octane index min. RON 95 or AVGAS 100 LL or AVGAS UL91 (unleaded)
For more details see Pilot's Operating Handbook, Doc. No. ERTC020-10-AS, Section 2
- 8.2 Oil Performance classification SG or higher
For more details see Pilot's Operating Handbook, Doc. No. ERTC020-10-AS, Section 2
- 8.3 Coolant Conventional or waterless coolant
For more details see Operators Manual for Rotax engine type 912 series, Doc. No. OM-912

9. Fluid capacities

- | | | |
|-----------------------------|-----------|------------|
| 9.1 Fuel | Total: | 120 litres |
| | Usable: | 118 litres |
| 9.2 Oil | MAX mark: | 3.0 litres |
| | MIN mark: | 2.5 litres |
| 9.3 Coolant system capacity | approx. | 1.5 litres |

10. Air Speeds

- Design Manoeuvring Speed VA:
90 KIAS 167 km/h IAS
- Maximum Flap Extended Speed VFE:
70 KIAS 130 km/h IAS
- Design cruising speed VC
115 KIAS 214 km/h IAS
- Never exceed speed VNE:
146 KIAS 270 km/h IAS

Airplane with Woodcomp KW-31-033 propeller

- Design Manoeuvring Speed VA:
88 KIAS 163 km/h IAS
- Design cruising speed VC
113 KIAS 209 km/h IAS

11. Flight Envelope

Maximum operating altitude: 15 820 ft (4822 m)

12. Approved Operations Capability

Day-VFR

Night VFR (Note 1)

Flight into expected or actual icing conditions is prohibited.

13. Maximum Masses

- Take-off: 600 kg (1323 lb)
Landing: 600 kg (1323 lb)

14. Centre of Gravity Range

- Forward limit: 20% MAC
Rear limit: 32% MAC
MAC: 1.25 m

15. Datum

Reference datum is the wing leading edge

16. Control surface deflections

Refer to AMM



17. Levelling Means	Lengthwise	levelling point 1 and 2
	Crosswise	levelling point 5 and 7
18. Minimum Flight Crew		1 (Pilot)
19. Maximum Passenger Seating Capacity		1
20. Baggage/ Cargo Compartments	Location	Behind the Seats
	Max. allowable Load	25 kg (55.1 lbs)
21. Wheels and Tyres	Nose Wheel Tyre Size	15 x 6.00 – 6
	Main Wheel Tyre Size	15 x 6.00 – 6
22. (Reserved)		-



A.IV. Operating and Service Instructions

1. Flight Manual Pilot's Operating Handbook,
Doc. No. ERTC020-10-AS
2. Maintenance Manual Airplane Maintenance Manual,
Doc. No. ERTC022-10-AS (incl. Airworthiness Limitations)
3. Structural Repair Manual Refer to Airplane Maintenance Manual, Doc. No.
ERTC022-10-AS
4. Weight and Balance Manual Refer to Pilot's Operating Handbook,
Doc. No. ERTC020-10-AS and Airplane Maintenance Manual,
Doc. No. ERTC022-10-AS
5. Illustrated Parts Catalogue Illustrated Parts Catalogue, Doc. No.
SPORTSTAR-0396G-02712-00

A.V. Notes

Note 1 – Supplement No. 31 „VFR Night Operation“ must be contained in Pilot's Operating Handbook when the SportStar RTC airplane is equipped for VFR Night operation



SECTION ADMINISTRATIVE

I. Acronyms & Abbreviations

AMM	Aircraft Maintenance Manual
CAI	Certification Action Item
CRI	Certification Review Item
CS-LSA	Certification Specification for Light Sport Aeroplanes
EASA	European Aviation Safety Agency
IAS	Indicated Airspeed
KIAS	Indicated Airspeed [knots]
MAC	Mean Aerodynamic Chord
POH	Pilot's Operating Handbook
RPM	Rotations per Minute
TCDS	Type Certificate Data Sheet

II. Type Certificate Holder Record

Evektor, spol. s r.o.
Letecka 1008
686 04 Kunovice
CZECH REPUBLIC

III. Change Record

Issue	Date	Changes	TC Issue No. & Date
Issue 01	24 May 2012	Initial issue	Initial Issue, 01, 24 May 2012
Issue 02	23 Octo 2015	Addition of propeller KW-31-033 and repair of Woodcomp Klassic 170/3/R diameter.	Initial Issue, 01, 24 May 2012
Issue 03	16. April 2019	VFR Night operation	Initial Issue, 01, 24 May 2012
Issue 04	10 Sept 2019	Correction of type mistake	Initial Issue, 01, 24 May 2012

-END-

